

ICETI

ENGINEERING TECHNOLOGY INNOVATION

**INTERNATIONAL CONFERENCE ON
ENGINEERING TECHNOLOGY
AND INNOVATION**

BOOK OF ABSTRACTS

www.iceti.org

March 22-26 2017 Sarajevo Bosnia and Herzegovina



Organized by



Partners



INTERNATIONAL CONFERENCE ON ENGINEERING TECHNOLOGY AND INNOVATION

ISBN 978-605-83575-2-5

**BOOK OF ABSTRACTS OF THE
INTERNATIONAL CONFERENCE ON ENGINEERING TECHNOLOGY AND
INNOVATION
22-26 MARCH SARAJEVO**

Edited by
Prof. Dr. Özer Çınar

Published, 2017

info@iceti.org
www.iceti.org

This work is subject to copyright. All rights are reserved, whether the whole or part of the material is concerned. Nothing from this publication may be translated, reproduced, stored in a computerized system or published in any form or in any manner, including, but not limited to electronic, mechanical, reprographic or photographic, without prior written permission from the publisher.

info@iceti.org

The individual contributions in this publication and any liabilities arising from them remain the responsibility of the authors.

The publisher is not responsible for possible damages, which could be a result of content derived from this publication.

SCIENTIFIC COMMITTEE

1. Prof. Dr. Adisa Parić - University of Sarajevo
2. Prof. Dr. Aleksandar Dimitrov - Ss. Cyril and Methodius University
3. Prof. Dr. Anita Grozdanov - Ss. Cyril and Methodius University
4. Prof. Dr. Asif Šabanović – International University of Sarajevo
5. Prof. Dr. Christos Douligeris - University of Erlangen-Nurnberg
6. Prof. Dr. Dragutin T. Mihailović - University of Novi Sad
7. Prof. Dr. Erkan Şahinkaya – İstanbul Medeniyet University
8. Prof. Dr. Falko Dressler - University of Paderborn - Germany
9. Prof. Dr. Harry Miller – International University of Sarajevo
10. Prof. Dr. Ian F. Akyıldız – Georgia Institute of Technology
11. Prof. Dr. İsmail Usta - Marmara University
12. Prof. Dr. Liljana Gavrilovska - Ss Cyril and Methodius University
13. Prof. Dr. Lukman Thalib - Qatar University
14. Prof. Dr. M. Asghar Fazel – University of Environment
15. Prof. Dr. Mehmet Akalin - Marmara University
16. Prof. Dr. Mehmet Kitiş – Süleyman Demirel University
17. Prof. Dr. Özer Çınar – Yıldız Technical University
18. Prof. Dr. Perica Paunovic - Ss. Cyril and Methodius University
19. Prof. Dr. Rifat Škrijelj – University of Sarajevo
20. Prof. Dr. Samir Đug, Faculty of Science Sarajevo
21. Prof. Dr. Tanju Karanfil – Clemson University
22. Prof. Dr. Ümit Alver – Karadeniz Technical University
23. Prof. Dr. Wolfgang Gerstaecker - University of Erlangen-Nurnberg
24. Prof. Dr. Yılmaz Yıldırım - Bülent Ecevit University
25. Assoc. Prof. Dr. Ahmet Doğan – Yıldız Technical University
26. Assoc. Prof. Dr. Izudin Dzafic - International University of Sarajevo
27. Assoc. Prof. Dr. Muhamed Hadziabdic - International University of Sarajevo
28. Assoc. Prof. Dr. Nusret Drešković - University of Sarajevo
29. Assoc. Prof. Dr. Senija Tahirovic - International University of Sarajevo
30. Assist. Prof. Dr. Faruk Berat Akçeşme - International University of Sarajevo
31. Assist. Prof. Dr. Fouzi Tabet - German Biomass Research Center
32. Assist. Prof. Dr. Haris Gavranovic - International University of Sarajevo
33. Assist. Prof. Dr. Murat Karakaya - Atılım University
34. Assist. Prof. Dr. Sasan Rabieh - Shahid Beheshti University
35. Assist. Prof. Dr. Ševkija Okerić - University of Sarajevo
36. Dr. Hasan Bora Usluer - Galatasaray University
37. Dr. Muhammet Uzun - RWTH Aachen University

ORGANIZATION COMMITTEE

Chairman(s) of the Conference

Prof. Dr. Özer Çınar – Yıldız Technical University

Prof. Dr. Ümit Alver - Karadeniz Technical University

Members of the Committee

Assoc. Prof. Dr. Nusret Drešković- University of Sarajevo

Assoc. Prof. Dr. Samir Đug, Faculty of Science Sarajevo

Assist. Prof. Dr. Sasan Rabieh - Shahid Beheshti University

Teaching Asistant Amra Banda - University of Sarajevo

Teaching Asistant Amina Sivac - University of Sarajevo

Teaching Asistant Boris Avdic - University of Sarajevo

Senior Teaching Asistant Edin Hrelja - University of Sarajevo

WELCOME TO ICETI 2017

On behalf of the organizing committee, we are pleased to announce that the International Conference On Engineering Technology And Innovation is held from March 22 to 26, 2017 in Sarajevo, Bosnia-Herzegovina.

ICETI 2017 provides an ideal academic platform for researchers to present the latest research findings and describe emerging technologies, and directions in Engineering Technology And Innovation. The conference seeks to contribute to presenting novel research results in all aspects of Engineering Technology And Innovation.

The conference aims to bring together leading academic scientists, researchers and research scholars to exchange and share their experiences and research results about all aspects of Engineering Technology And Innovation. It also provides the premier interdisciplinary forum for scientists, engineers, and practitioners to present their latest research results, ideas, developments, and applications in all areas of Engineering Technology And Innovation. The conference will bring together leading academic scientists, researchers and scholars in the domain of interest from around the world. ICETI 2017 is the oncoming event of the successful conference series focusing on Engineering Technology And Innovation.

The International Conference on Engineering Technology and Innovation (ICETI 2017) aims to bring together leading academic scientists, researchers and research scholars to exchange and share their experiences and research results about all aspects of Engineering Technology and Innovation. It also provides the premier interdisciplinary forum for scientists, engineers, and practitioners to present their latest research results, ideas, developments, and applications in all areas of Engineering Technology and Innovation. The conference will bring together leading academic scientists, researchers and scholars in the domain of interest from around the world. The conference's goals are to provide a scientific forum for all international prestige scholars around the world and enable the interactive exchange of state-of-the-art knowledge. The conference will focus on evidence-based benefits proven in technology and innovation and engineering experiments.

Best regards,

Prof. Dr.Özer ÇINAR

CONTENT	PAGE
Decision Support Software In Rate Of Innovation Adoption: Inoapp	1.
The Flame Retardant Effect Of Tri Butyl Phosphate (Tbp) Chemical On The Leather	2.
Electromagnetic High Frequency Transients Measurements Of Some Household Devices	3.
Effect Of Co Addition On The Electrical Properties Of Ni-Mn-O Ntc Thermistors	4.
Influence Of Electron Concentration On The Martensitic Transformation And Structural Properties Of Cu-Al-Fe High-Temperature Shape Memory Alloys	5.
An Efficient Mechanical Design Optimization Framework Based On Ann-Surrogate Model And Particle Swarm Optimization	6.
Position Dependent Mass Effects On Hydrogen Atom In Debye Plasma	7.
Effects On Forage Quality Of Sweet Sorghum Silage With Addition Of Mung Bean (Vigna Radiata)	8.
Appropriate User Acceptance Criteria For New Social Media Sites	9.
A Wireless Robot Arm Simulating Hand Movements	10.
Evaluating The Determinants Of Customer Loyalty In The Turkish Smart Phone Market Via Samsung Smart Phone Users	11.
Condition Monitoring Of The Uncoated Carbide Cutting Tool In Turning Process Of The Aluminum Alloy 6061 Via Vibration Signal Analysis	12.
Numerical Investigation Of Mhd Forced Flow In A Three-Dimensional Cylindrical Pipe	13.
Effect Of Various Drill Bits On Thrust Force In Drilling Of Carbon Fiber Reinforced Plastic	14.
Influence Of Pouring Temperature On The Formation Of Spheroidal And Lamellar Graphite In Cast Iron	15.
Investigation Of The Fading Time Effects On Microstructure And Mechanical Properties In Vermicular Cast Iron	16.
A Case Study: The Effect Of The Use Of Augmented Reality Applications On Building Marketing Process	17.

Influence Of Heat Treatment On Thermal, Mechanical And Microstructural Characterization Of Al Based Mg-Al-Sb Eutectic Alloy	18.
Optical And Structural Properties Of Znse Thin Films With Chemical Bath Deposition	19.
Forage Yield And Some Quality Characteristics Of Sweet Sorghum (Sorghum Bicolor Var. Saccharatum) As Affected By Plant Densities Under Mediterranean Climatic Conditions	20.
Agent-Based Modeling And Simulation Of The Sunn Pest -Wheat Relation And Of The Struggle Against Sunn Pest In Turkey	21.
Using Machine Learning Techniques On Predicting Wastage Amount In Textile Factories	22.
Designing A Vivaldi Fed Antenna For Passive Millimeter Wave Imaging System In Ka Band	23.
Design Of Band Stop Filter With Frequency Selective Surfaces Analysis By Implementing The Golden Ratio Rule	24.
Information Security Risk Assessment In Health Institutions And Measurement Of Users' Awareness On Information Security	25.
Transport Properties Of Mortar Mixture Containing Metakaolin	26.
Comparision Of Mechanical And Thermal Properties Of Different Agricultural Plastic Mulch Films	27.
Do Turkish Consumers Prefer Converged Products? Smartphone Example	28.
Comparison Of Machining Characteristics Between Aa 6082 And Aa 6082 T6 Material With Cryogenic Cooling	29.
Construction And Demolition Waste Management In Turkey	30.
C&D Waste Management In Turkey	31.
The Investigation Of Discharge Coefficient For Different Upstream Crest Lengths In Triangular Labyrinth Side Weir	32.
Effects Of Selective Laser Sintering (Sls) Method On Microstructural Features Of Ti6al4v Powder Alloy	33.
Sulfate Resistance Of Polypropylene Fiber Reinforced Concrete	34.

Modeling And Simulation Of The Resistance Of Bacteria Against Antibiotics	35.
Monitoring And Analysing Of Looms To Improve Performance Of Weaving Hall	36.
The Effect Of Osmotic Dehydration Pretreatment Applied To Apples On The Quality Parameters Of This Fruits And Kinetic Modeling	37.
Use Of Quick Couplings In Design Of Work Dies	38.
Mechanical And Comfort Properties Of Fabrics Produced With Hollow Yarns	39.
Creating Alternative Production Lines By Using Simulation Technique In Apparel Production	40.
Thermodynamic Analysis Of Simav Geothermal District Heating System Assisted By Solar Energy	41.
Future Based On Additive Manufacturing Technologies: 3d Printing	42.
Determining The Work Flow And Standard Unit Times Of A Shirt Production Line	43.
Numerical Analyses Of A Heat Exchanger In A Thermal Energy Storage System	44.
Textural Parameters And Ultrastructural Changes Of Amasya Apples By Applied With Osmotic Dehydration Pretreatment	45.
A New Titanium Mesh Cage Design For Lumbar Spine Stabilization Following Corpectomy	46.
Investigation Of A Chemical Modification Method Which Enable Polyamide/Elastane Fabrics To Be Dyed At Lower Temperatures	47.
Programming Encryption Algorithms With Steganograph	48.
Microprocessor Controlled Respiratory Function Test Simulator	49.
Microstructural Evaluation Of T6-Treated A380 Alloy Manufactured By Semi-Solid Metal Casting	50.
Investigation Of The Dyeability Of Cotton Knitted Fabrics With With Various Dye Plants In The Presence Of Potassium Aluminum Sulfate Mordant	51.
Corrosion, Mechanical And Microstructural Characteristics Of Modified Navy G Bronze Casts	52.
Surface Plasmon Resonance Based On Molecular Imprinted Sensor For Melamine Detection	53.

Synthesis Of Polyoxometalate/Multi-Walled Carbon Nanotubes Hybrid And Application For Rutin Detection	54.
Electrochemical Sensor Via Graphene Quantum Dots For Determination Of Ascorbic Acid	55.
Sensitive Determination Of L-Tyrosine Based On Graphene Oxide Nanomaterial	56.
A Novel Determination Of L-Tryptophan Via Au@Ag Nanoparticles On Polyoxometalate	57.
Development Of Novel Molecular Imprinted Electrochemical Sensor Based On Polyoxometalate/Carbon Nitride Nanotubes Nanocomposite For Determination Of Quercetin	58.
Development Of A Test Device Capable Of Performing Static Loading Tests Of Carpets Automatically	59.
Conjugation Of Aldehyde Dextran With Horseradish Peroxidase And Decolorization Of Synthetic Dye Wastewater	60.
Logical Key Hierarchy Implementation In Cloud Computing	61.
The Effect Of Different Aftertreatments On Coloration Of Wool Fabrics With Hazelnut Shells	62.
Extrusion And Comparative Investigation Of Pristine And Nanoparticle Added Polypropylene Filaments For Piezoelectric Smart Textile Applications	63.
Investigation Of Jet-Strip And Production Cylinder Surfaces Used In The Production Of Nonwoven Fabrics In Cross-Laid Line With Hydro-Entanglement Technology	64.
Production Of Cp-Ti Reinforced A356 Aluminum Composite By Vacuum-Assisted Investment Casting	65.
A Mathematical Programming Model For Multi-Objective Optimization In Flexible Manufacturing Cells	66.
Determination Of Air Permeability Property Of Air-Laid Nonwoven Fabrics Using Regression Analyses	67.
Peroxidase-Like Activity Of Apoferritin Paired Silver Clusters And Its Biomemory Applications	68.
Play Street: The Future Of Residential Streets	69.
Microstructural Aspects Of Nickel-Based Surfacing Deposited By Gas Metal Arc Welding	70.

(Gmaw)

Comparative Analysis Of Web Application Security Scanners	71.
Loop Based Column-Switching Lc×Lc System Couple With Evaporative Light Scattering Detector For The Characterization Of Triglycerides In Refined Commercial Edible Oils	72.
Application Of Diode Array Detection With A C30 Reverse Phase Stationary Phase For The Separation And Identification Of Unsaturated Fatty Acids	73.
Start Up Of Anammox Reactor And Short Term Effects Of Tio₂ Nanoparticles On Anammox Bacteria	74.
Comparison Of Welding Methods For Joining Similar And Dissimilar Stainless Steels	75.
Finite Element Model Of Lumbar Spine Stabilization With Bone Graft Supported Titanium Mesh Cage	76.
Controlling The Building Model Using High Order Sliding Mode Control Optimized By Multi Objective Genetic Algorithm	77.
Android Based Mobile C# Programming Education Application	78.
Comparison Of Nato Bullets And 6.8 Mm Remington	79.
A Modal Analysis Of Tlp With Tendons	80.
Design And Analysis Of Light Quadcopter Body	81.
Green And Sustainable Approach For Design Of Antibacterial Wound Care Dressings	82.
Carbon Nitride Nanotubes Decorated With Graphene Quantum Dots As Microbial Fuel-Cell Electrode	83.
Development Of Molecular Imprinted Polymer Based Qcm Nanosensor For Determination Of Amoxicillin	84.
The Effect Of Hydraulic Radius On Aeration Performance In High-Head Gated Conduits	85.

Variation Of Microstructure And Mechanical Properties Of 2205 Duplex Stainless Steel For Different Solution Treatment	86.
The Importance Of System Simulation Softwares At Industrial Engineering Education: A Case Study From Turkey	87.
Ecological Approaches In Textile Sector: The Effect Of R-Pet Blend Ratio On Ring Spun Yarn Tenacity	88.
A Novel Colorimetric And Fluorescent Chemosensor For Ph In Organo-Aqueous Medium	89.
New Approaches To The Peptid Synthesis & Characterization	90.
Determining Dispersing Media In The Inverse Suspension Polymerization Of Polyacrylic Acid	91.
Principles, Objectives And Technical Difficulties In Smart Grid Control	92.
Design Of A Solar - High Temperature Pem Fuel Cell Hybrid System For Micro Combined Heat And Power Application For Renewable Energy Communities	93.
Comparison Of Dioramas And 2d Renderings As Design Expression Tools	94.
Influence Of Solution Heat Treatment At 1180 °C On The Properties Of 2.4879 Alloy	95.
Green Supplier Selection: A Review Of Methodologies And Criteria	96.
An Adaptation Of Matrix Encoding Technique For Data Hiding In Rgb Images	97.
Novel Amperometric Xanthine Biosensor Based On Xanthine Oxidase Immobilized On Electrochemically Polymerized 10-[4h-Dithieno(3,2-B:2',3'-D)Pyrrole-4-Yl]Decane-1-Amine Film	98.
Voltage Output And Current Density Of 3-D Piezoelectric Fabric Under Various Applied Loads	99.
Determining The Effect Of Hardening Type On Cyclic Plasticity Modeling Using Finite Element Analysis	100.

Research Of Mechanical Properties Of Poly(Lactic Acid) And Green Composites	101.
Comparison Of Analytical And Numerical Calculations Of A Cold Rolling Process	102.
Design Of A Microcomputer Based Realtime Ecg Holter Device	103.
Closed Loop Laser Diode Temperature Control System Design	104.
Rapid Surface Hardening Of Aisi 1045 Steel For Automotive Application By Electrolytic Plasma Treatment	105.
Investigation Of Mechanical And Thermal Properties Of Poly(Ethylene)-Poly(Lactic Acid) Mulch Films	106.
Variable Neighborhood Search For The Heterogeneous Fixed Fleet Vehicle Routing Problem	107.
Noise Reduction Of Emg Signals Using Wavelet Transform	108.
An Effective Modelling Method Based On Mlp-Based Artificial Neural Networks For Obtaining V-Curve Characteristics Of Synchronous Motor	109.
Use Of Green Tea In Dyeing Of Cellulosic Fibers	110.
Microwave Energy Fixation For Discharge Printing On Cotton Fabric	111.
Potassium Permanganate Bleaching Of Natural Pineapple Fibers	112.
Variable Neighborhood Search For Portfolio Optimization	113.
Ant Colony Optimization For Portfolio Optimization	114.
Activity And Stability Of Tio₂ Catalysts In Catalytic Decomposition Of Formaldehyde In Supercritical Water	115.
Urban Green Spaces In The Context Of Change And Interaction	116.

Preparation And Properties Of Controlled-Release Fertilizers Coated With Crosslinked Hydrogels	117.
Determining The Location Of A Waste Electrical And Electronic Equipment (Weee) Recycling Plant In The Aegean Region Of Turkey	118.
Review Of Estimation Methods For E-Waste Quantities And The Application Of Simple Delay Method For The Case Of Turkey	119.
Inhibitory Effects Of Zinc Oxide Nanoparticles On Anammox Process	120.
Preparation And Properties Of Polyphenyl Ethers Containing Multiple Bonds In The Main Chain	121.
Mesenchymal Stem Cell Released From Cytokines And Chemokines, Its Effect On Colon Primer, Metastatic Adenocarcinoma And Cancer Stem Cells	122.
Therapeutic Efficacy Of Honey Loaded Scaffolds In Full-Thickness Wounds Of Rats	123.
Properties In The Composites Of Epoxy-Cement-Pzt Ceramics Powder	124.
Design Of Ipm Synchronous Motor For Gearless Elevator Applications	125.
Correlating Surface Potential With Irregular Plastic Deformation	126.
An Examination Of Daylight Usage Of Firat University Faculty Of Architecture Building With Bim	127.
The Comparision Of Mone's Building Types Projects With Mone's Education Building Standards And The Evaluation Of Their Consistency	128.
A Mathematical Model For Allocation And Distribution Of Humanitarian Relief To Disaster Are	129.
Stability And Activity Of Zirconium Oxide In Catalytic Supercritical Water Gasification Of Formaldehyde	130.
Investigation Of The Effects Of Different Chemical Structures On The Color Of The Softeners Used In The Finish	131.

Improving The Color Yield And Wet Fastnesses By Synthesizing The New Disperse Azo Dye	132.
Research Of Growth Mechanism Of Micro Arc Oxidation Coatings On Magnesium Alloys	133.
Optimization And Valuation Of Expansion Flexibility In Manufacturing Industry	134.
Diagnosis Of Diabet Disease By Using Different Machine Learning Techniques	135.
Neoantigen Based Immunotherapy In Personalized Cancer Treatment	136.
Compression Properties Of Woven Carpet Performance Under Dynamic Loading	137.

DECISION SUPPORT SOFTWARE IN RATE OF INNOVATION ADOPTION: INOAPP

MURAT OTURAKCI^{a*}, HACIRE OYA YUREGIR^b

^aINDUSTRIAL ENGINEERING DEPARTMENT ADANA SCIENCE AND TECHNOLOGY UNIVERSITY

^bINDUSTRIAL ENGINEERING DEPARTMENT CUKUROVA UNIVERSITY

*moturakci@adanabtu.edu.tr

Abstract:

Usage of ERP software increases in line with technological developments, it is seen that innovation and rate of adoption concepts started to be settling inside the enterprise cultures. Hence, companies feel obligated to manage innovation and practice adoption of innovation. The aim of this study is to develop a decision support software (DSS) that indicates what kind of actions need to be taken by companies to obtain the maximum efficiency from e-business software users whom are working in different type of department or companies. DSS, which is called InoApp, has been developed in RAD Studio 10.1 platform with Delphi programming language. To obtain data and decision rules for InoApp, five innovation characteristics', which Rogers argue that they affect the rate of adoption for innovation, effects on 403 ERP software users have been analyzed categorically by using Self Organizing Maps (SOM) technique. InoApp, contains 10 sections such as software type, gender, age, education, major, total/current work experience, sector, department, and frequency of usage. Combination of sub-sections creates 1536 user types for companies. InoApp provides what types of actions need to be taken by companies and suggestions for companies for each type of user under five innovation characteristics.

Implementation of InoApp, is conducted with E-business application users in four departments of a Furniture Company in Turkey. After 33 users from the departments of Foreign Trade, Accounting, Purchasing and Production used the InoApp, suggestions have been collected from the software and comparisons by departments and company have been made and actions which are needed to be taken are designated. According to the results, training and support service for E-business application which company is using need to be provided and some of the users from departments need to be rotated. By this way, effectiveness of an employee and business will be affected positively.

Keywords: Decision Support Software (DSS), Inoapp, Innovation Characteristics, Rogers, E-Business

THE FLAME RETARDANT EFFECT OF TRI BUTYL PHOSPHATE (TBP) CHEMICAL ON THE LEATHER

SAFIYE MERIC ACIKEL^{a*}, CEM CELIK^b, ALI SERDAR GULTEK^c, AHMET ASLAN^d

^aLEATHER TECHNOLOGY PROGRAMME, TECHNICAL VOCATIONAL SCHOOL, ISTANBUL
UNIVERSITY

^bLEATHER RESEARCH AND APPLICATION CENTER, ISTANBUL UNIVERSITY

^cPRIVATE SECURITY AND GUARD, TECHNICAL VOCATIONAL SCHOOL, ISTANBUL UNIVERSITY

^dLEATHER ENGINEERING DEPARTMENT, ENGINEERING FACULTY, ISTANBUL UNIVERSITY

mericgokalp@gmail.com

Abstract:

Nowadays, some applications in leather manufacture have not been still made why the leather is an organic material and more different material than textile. Flame retardant leather is one of these applications. When catching fire, leather can burn easily and release a lot of toxic gases and smoke because the leather products could contain some inflammable and harmful organic compounds after tanning, fat liquoring, dyeing and finishing processes. However the production of flame retardant leather is so important for some leather types as cyclist jackets, flr or automotive upholstery leathers. If these type leathers ignite lately, they will provide gaining time in order to rescue humans during the fire. For this reason, in this research was aimed to product flame retardant leather and the flame retardant effect of leathers treated with tributyl phosphate (TBP) were investigated. Tri butyl phosphate (TBP) chemical solutions were applied to the leathers at %0, %7, %14 and %21 different rates by padding finishing technique and after the flame retardant application, the leathers were finished with traditional finishing recipe. Flame retardant property of leathers were researched by vertical (TS ISO 6941:2007) and horizontal (TS ISO 3795: 1999) fire resistance tests The thermal stability and morphology of the flame retardant leathers were characterized by TG+DTG and SEM. The results showed that TBP treated leathers has good flame retardant properties and can enhance effectively the fire retardancy of leathers.

Keywords: Leather, Tri Butyl Phosphate, Flame Retardant, Fire

ELECTROMAGNETIC HIGH FREQUENCY TRANSIENTS MEASUREMENTS OF SOME HOUSHOLD DEVICES

SABAN SELIM SEKER^{a*}, OSMAN CEREZCI^b, FATIH BAYINDIR^a

^aBOGAZICI UNIVERSITY

^bSAKARYA UNIVERSITY

seker@boun.edu.tr

Abstract:

Electric and electronic devices are contributing to our exposure to wide range of electromagnetic frequencies, therefore causing an increase of electromagnetic pollution in both rural and urban environments. This exposure to spiking and frequencies of electromagnetic radiation on overburdened wires has been known as “dirty electricity”. Furthermore, it is more specifically the “transients” and “harmonics”, which are tiny spikes in the electricity turning house wiring into an antenna, radiating the formed spikes’ frequencies. This arising dirtiness has the potential to cause and exacerbate health problems existing in some people. Some experts consider dirty electricity to be the most biologically active electromagnetic pollution. Although the exact magnitude of effects of EMF on population health cannot be assessed, largely due to misclassification and bias in the assessment of, most studies suggest that risks, if present, are likely to be moderate. Given that most people nowadays are routinely exposed to EMF, this would however imply that potentially large numbers of people could suffer from adverse health effects or diminished well being related to EMF exposure. Large research study, such as for example the INTERPHONE , have been initiated to address public concern regarding effects of EMF. Some of the incidence of headaches, general weakness, dry eye or mouth, facial flushing, depression, mood, dizziness, pain, incidence of asthmatic symptoms and other respiratory symptoms, skin irritation, clarity of thought and more energy. Some students with attention deficit disorder (ADD) or attention deficit hyperactivity (ADHD) might be more sensitive to EMF energy.

In this study, we would like to emphasize dirty electricity has some harmful effects on human body. For this purpose, electromagnetic spectrum analysis and electric and magnetic field measurements of some household devices like hair dryer, old ray tube television, blender, electrical heater, toaster, vacuum cleaner and microwave oven are measured and discussed.

Keywords: Electromagnetic Household Devices, High Frequency Transient, Measurement

EFFECT OF CO ADDITION ON THE ELECTRICAL PROPERTIES OF NI-MN-O NTC THERMISTORS

GOKHAN HARDAL^{a*}, BERAT YUKSEL PRICE^a

^aISTANBUL UNIVERSITY

*gokhan.hardal@ogr.iu.edu.tr

Abstract:

Temperature sensors such as thermocouples, resistance temperature detectors, NTC thermistors are widely used for monitoring of temperature. NTC thermistors have various advantages such as fast response time, low cost, small size, large changes in resistance versus temperature.

Nickel manganite based NTC thermistors are derived from two or more metal oxide powders such as manganese oxide, iron oxide, cobalt oxide, nickel oxide, copper oxide, and zinc oxide. In commercial spinel-based NTC thermistors, the material constant "B" is between 2000 and 5000 K and sensitivity coefficient at 25oC is in the range between -2.2 and -5.5 %/K.

In this study, the influence of Co addition on the electrical properties of Ni_{0.5}Co_xMn_{2.5-x}O₄ (x=0.5, 0.8 and 1.1) NTC thermistors was investigated. The samples manufactured by the conventional solid-state reaction method. The powders were calcined at 900oC for 2 hours and were pressed to form disc shaped samples. The samples were sintered at 1300oC for 5 hours in air. The bulk density of the sintered samples was calculated using Archimedes principle. The microstructure of samples was observed using a scanning electron microscope. The sintered samples were coated with silver paste to form electrodes. The electrical resistance was measured in a temperature programmable furnace, logged every 0.1oC, between 25 and 85oC.

The electrical resistivity at room temperature and B value of Ni_{0.5}Co_{0.5}Mn₂O₄ sample were 1127 Ω.cm and 3735 K. These values were decreased to 1042 Ω.cm and 3648 K when the Co content was increased to 0.8. The electrical resistivity and B value further decreased to 548 Ω.cm and 3510 K when Co content was 1.1. Similarly, activation energy and sensitivity coefficient of samples were decreased with the increasing Co content. As a result, the addition of Co can be used as a dopant to improve the electrical conductivity of NTC thermistors.

Keywords: Cobalt Oxide, Electrical Properties, NTC Thermistors

INFLUENCE OF ELECTRON CONCENTRATION ON THE MARTENSITIC TRANSFORMATION AND STRUCTURAL PROPERTIES OF CU-AL-FE HIGH-TEMPERATURE SHAPE MEMORY ALLOYS

KOKSAL YILDIZ^{a*}, ESRA BALCI^a, MEDIHA KOK^a, SINAN AKPINAR^a

^aFIRAT UNIVERSITY

*kyildiz@firat.edu.tr

Abstract:

Nowadays, shape memory alloys with high operating temperatures suitable for use in space and aerospace industries are needed. Especially because of their low cost, CuAl-based alloy systems are of great interest as high-temperature shape memory alloys among different shape memory alloy groups. In this work, martensitic transformation and structural properties of high-temperature Cu-Al-Fe shape memory alloy systems with different electron concentrations (e/a ratio) were studied by means of differential scanning calorimeter (DSC), X-ray diffractometer (XRD) and scanning electron microscope (SEM) measurements. DSC analysis showed that all alloy samples exhibited high-temperature shape memory characteristics and that the martensitic transformation properties of the alloys changed depending on the e/a ratios. From the thermal analysis results, it was found that the operating temperatures of the alloy samples decreased with increasing e/a ratios: the values of martensite start (M_s) and thermodynamic equilibrium (T₀) temperatures of the alloy samples decreased from 261 °C to 195.6 °C and from 310 °C to 279.85 °C, respectively. Structural and morphological analysis revealed that the main martensitic phase in the alloy samples was 18R martensite and microstructures of the alloy samples contained different precipitate phases. It was also found that phase components of the alloys were not affected by the increased e/a ratio.

Acknowledgement: This work was supported by Management Unit of Scientific Research projects of Firat University (FUBAP) (Project Number: FF.15.16)

Keywords: Cu-Al-Fe; Electron Concentration; Martensitic Transformation

AN EFFICIENT MECHANICAL DESIGN OPTIMIZATION FRAMEWORK BASED ON ANN-SURROGATE MODEL AND PARTICLE SWARM OPTIMIZATION

MURAT MAYDA^{a*}

^aKARAMANOGLU MEHMETBEY UNIVERSITY

*mmayda@kmu.edu.tr

Abstract:

The optimization of the designs including simulated data or experimental data is still challenging since most of the design problems involves dealing with the characteristics of non-linearity and non-differentiate. To that end, there is a need to easily and efficiently utilize the integration of surrogate models and simulation-based optimization methods. In this work, a framework to optimize these kind of design problems by using ANN-based surrogate model and PSO algorithm is proposed. A case study is considered to show the applicability and efficacy of the proposed optimization framework, and it is observed that this framework can handle the design problems having non-linearity and non-differentiate functional characteristic through the integration of ANN and PSO.

Keywords: ANN, Mechanical Design Optimization, Particle Swarm Optimization, Surrogate Model.

POSITION DEPENDENT MASS EFFECTS ON HYDROGEN ATOM IN DEBYE PLASMA

MUSTAFA KEMAL BAHAR^{a*}

^aKARAMANOGLU MEHMETBEY U. FACULTY OF ENGINEERING

*mussiv58@gmail.com

Abstract:

In order to investigate the plasma screening and position dependent mass effects on the hydrogen atom in Debye plasma, the effective Schrödinger equation including more general exponential screened Coulomb potential is approximately solved analytically. The effects of the screening parameters on energies are investigated approximately by solving the effective Schrödinger equation using asymptotic iteration method.

Keywords: Hydrogen Atom, Energy, Debye Plasma, Position Dependent Mass

EFFECTS ON FORAGE QUALITY OF SWEET SORGHUM SILAGE WITH ADDITION OF MUNG BEAN (*VIGNA RADIATA*)

HAKAN GEREN^{a*}, YASAR TUNCER KAVUT^a

^aEGE UNIVERSITY

*hakan.geren@ege.edu.tr

Abstract:

Sweet sorghum is known to be an annual C4 plant of tropical origin and is an interesting crop. It is well adapted to sub-tropical and temperate regions, being highly biomass productive and water efficient. Sweet sorghum which can be grown under widely differing climatic conditions, has been identified as a promising crop with the potential to provide for a wide spectrum of forage or energy uses. Sweet sorghum is ensiled to preserve its nutritive value and it has high metabolic energy value, but crude protein is low. Many studies have been conducted to assess the benefits to dry matter yield and nutritive value of combining sorghums with annual legumes. This study was conducted to evaluate nutritive value of sweet sorghum (*Sorghum saccharatum*) silage when ensiled with different proportions of mung bean (*Vigna radiata*). Sweet sorghum was harvested at the late dough stages of kernel maturity and mung bean was harvested at a vegetative stage in two consecutive years (2013-2014) at Ege University, Faculty of Agriculture, Department of Field Crops, Izmir, Turkey. Crops were chopped using a conventional chopper. Sweet sorghum was mixed with mung bean at ratios of 100:0, 75:25, 50:50, 25:75, and 0:100%, respectively. For each mixture, 1 kg of fresh material was vacuum sealed in a plastic bag and fermented for 60 days, four bags per mixture. Crude protein (CP) increased as proportion of mung bean increased in the mixture. In addition, pH, lactic and acetic acids increased when mung bean was added. Silage with 100% mung bean had the highest pH and lowest lactic acid concentration. It is concluded that mixing mung bean with sweet sorghum for silage increased CP concentration of the mixture. Additional research is needed to assess mixtures that produce silage with more desirable fermentation characteristics.

Keywords: Sweet Sorghum, Mung Bean, Silage Quality, Crude Protein Content

APPROPRIATE USER ACCEPTANCE CRITERIA FOR NEW SOCIAL MEDIA SITES

MIRSAT YESILTEPE^{a*}, MUHAMMET KURULAY^a

^aYILDIZ TECHNICAL UNIVERSITY

mirsatyesiltepe@hotmail.com

Abstract:

Nowadays social media sites have attracted a number of users and they have become the mostly commonly used websites for general public. These websites are used by individuals, small and even big organizations for various purposes, such as meeting your old friends, sharing your own experiences, sharing pictures and videos, promoting businesses, sharing knowledge etc. Their popularity is increasing at an increasing rate. User's needs are endless so there will be some new area for creating new social media sites. There are two main ideas for creating new social media sites. Firstly, one should identify the new needs of users which are not fulfilled by the current websites. Secondly, the new website must incorporate those features which are mostly liked by end users and add further functionality into the website that attract more users. It is really important to know the criteria based on which the users prefer one website over the other. Therefore, the objective of this study is to compare the use of social media and find the acceptance criteria that why an end user prefers one social media over the other. This user feedback based information will help social media developers to incorporate new user needs into future social media to increase user satisfaction. We performed experiments on data collected fifteen most commonly used and popular social media websites in current era. The test data were collected till May 08, 2016.

Keywords: Social Media Sites, Sloppy Mail, Accessing From Devices

A WIRELESS ROBOT ARM SIMULATING HAND MOVEMENTS

SUKRU KITIS^{a*}, HASBI APAYDIN^b

^aDUMLUPINAR UNIVERSITY

*sukru.kitis@dpu.edu.tr

Abstract:

This study was performed on the purpose of providing needs by giving access to robot arm remotely in environment that are undesirable for people or in chemical areas which can be damaged on human hands. In this work, a robot arm design simulating hand movements was designed. This robot was designed as Cartesian robot that can move in X, Y, Z axis linearly and that has arm holding and transportation properties. This robot works wirelessly as distinct of literature. Flex sensors was placed on a glove for every finger in order to provide simulating hand movements. Flex sensors are 4.5" namely 112,5*6,38*0,5 mm sizes and 0.5 g weight. They have resistance properties between 10-20 kilohms. Data taken from fingers sends to control point wirelessly with a serial module card that has 2.4 GHZ telecommunication frequencies. A relay card with 8 channeled, 433 MHz wireless RF receptor was preferred for receiving and processing data coming from robot arm section. Micro servo motor has 0,1 sec/600 turning angle, 9 g weight, 23,1*12,2*29 sizes and 4,8 V-7 V working range. Arduino uno was chosen in the aim of system control. Arduino uno has atmega 328 microcontroller, 40 mA current, 25 g weight, and sizes of 68,6*53,4 *29 mm.

Flex sensors put up 10 kilohm resistances when they are not twisted. However; this value can be up to 20 kilohm as they are twisted. Thus, it can be understood that how much fingers are twisted and, accordingly, simulating robot provides running of servo motors that has 0,1 sec/600 turning angle and twisting fingers of arms in the same ratio, as well. Control was performed with designed algorithm and wireless duplexer via Arduino uno.

Keywords: Robot Arm, Arduion Uno, Wireless, Flex Sensor

EVALUATING THE DETERMINANTS OF CUSTOMER LOYALTY IN THE TURKISH SMART PHONE MARKET VIA SAMSUNG SMART PHONE USERS

MUSTAFA BAYSAL^{a*}

^aDUMLUPINAR UNIVERSITY

*mustafa.baysal@dpu.edu.tr

Abstract:

The purpose of this study is to examine the effect of customer satisfaction on customer loyalty and to evaluate the effects of usage characteristics in the Turkish smart phone market through Samsung smart phone users.

To test the research model, we collected data from 219 Samsung smart phone users via face-to-face and online survey. The results show that customer satisfaction is a significant influence on customer loyalty. The features of the device (functions, usability and design) and corporate factors (customer support and corporate image) significantly affect customer satisfaction.

Data collected from 219 respondents were tested using partial least squares Structural Equation Modeling (PLS) approaches.

Results; Functional value, emotional value, social value and brand identification positively affect smart phone brand loyalty.

In particular, this study investigates the level of customer satisfaction, loyalty, brand image, corporate image and impact on the source country.

This study includes t-test, factor and regression analyzes applied to an online and face-to-face questionnaire. The results demonstrate administrative and theoretical results for satisfaction and customer relationship management.

Keywords: Customer Satisfaction; Loyalty; Predictors; Results; Smartphone, Samsung

CONDITION MONITORING OF THE UNCOATED CARBIDE CUTTING TOOL IN TURNING PROCESS OF THE ALUMINUM ALLOY 6061 VIA VIBRATION SIGNAL ANALYSIS

OTHMAN INAYATULLAH^{a*}, VICKNESWARAN SINNASAMY^b

^aUNIVERSITY COLLEGE OF TECHNOLOGY SARAWAK

^bDEPARTMENT OF MECHANICAL AND MANUFACTURING ENGINEERING, FACULTY OF ENGINEERING, UNIVERSITI PUTRA MALAYSIA

*drothman@ucts.edu.my

Abstract:

This study have been conducted in an attempt to monitor the changing of tool wear caused by increasing the cutting speed, depth of cut and feed rate. The signal processing analysis was done on the raw signal, the vibration signal then which is analyses by using MATLAB software. The relationship among several parameter of vibration signal, such as energy and maximum amplitude with cutting speed and depth of cut was studied. The material machined was Aluminum Alloy 6061 and uncoated carbide as a cutting tool. At the same time, the cutting temperature was also monitored. The results show that vibration signal can be one of the method to monitor tool wear in turning process via in-situ and therefore can be obtained useful for establishing the end of tool life in these operation. Based on the results the suitable speed and depth of cut range was identified to maximize the tool life.

Keywords: Cutting Tool, Turning, Vibration, Aluminum Alloy 6061, Tool Life

NUMERICAL INVESTIGATION OF MHD FORCED FLOW IN A THREE-DIMENSIONAL CYLINDRICAL PIPE

MURAT ERDEM^{a*}, YASIN VAROL^a, MUJDAT FIRAT^a

^aFIRAT UNIVERSITY, TURKEY

*muratrdm01@gmail.com

Abstract:

In this work, laminar three-dimensional magneto-hydrodynamic (MHD) forced convection has numerically investigated. 3D cylindrical-pipe is under the influence of externally magnetic field. The wall temperature of channel is different from liquid temperature. Numerical study has analyzed for three different magnetic field strengths and without magnetic field but constant inlet velocity. The study has designed in ANSYS-WORKBENCH and has analyzed with the ANSYS-FLUENT commercial software. The working fluid has selected as lithium. As a result, the liquid lithium flow rate has seemed to be strongly influenced by of the magnetic field force.

Keywords: Magneto Hydro Dynamic, MHD, Forced Convection, Magnetic Field

EFFECT OF VARIOUS DRILL BITS ON THRUST FORCE IN DRILLING OF CARBON FIBER REINFORCED PLASTIC

UGUR KOKLU^{a*}, SEZER MORKAVUK^a

^aKARAMANOGLU MEHMETBEY UNIVERSITY

*ugurkoklu@gmail.com

Abstract:

The usage of carbon fiber reinforced plastic is increasing day by day in several industries such as aerospace and automotive due to its high strength to weight ratio and perfect fatigue strength. Conventional drilling process is widely used to make a hole in a material and a hole is needed for assembly with rivet or bolt. In drilling process, thrust force is a crucial performance evaluation criteria since it effects machinability directly. Besides thrust force is responsible for delamination damage occurred during drilling of polymer composites. Therefore, thrust force occurred during drilling process must be reduced as far as possible. In this study, the effects of various drill bits that have three different geometry and cutting parameters on thrust force were experimentally investigated. The results indicated that thrust force decreased as cutting speed increased. In addition to that thrust force increased with increasing of feed rate. Whereas larger thrust forces occurred in drilling with drill bit C, lower thrust forces occurred in drilling with drill bit A. Maximum thrust force occurred at the combination of 0.18 mm/rev feed rate, 18 m/min cutting speed and drill bit C parameters. Minimum thrust force occurred at the combination of 0.06 mm/rev feed rate, 42 m/min cutting speed and drill bit A.

Keywords: Drilling, Carbon Fiber Reinforced Plastic

INFLUENCE OF POURING TEMPERATURE ON THE FORMATION OF SPHEROIDAL AND LAMELLAR GRAPHITE IN CAST IRON

MEHMET EKICI^{a*}

^aYALOVA UNIVERSITY

*mekici@yaloa.edu.tr

Abstract:

The objective of this research is to investigate the effect of pouring temperature on the microstructure of the cast iron. The pattern was designed with 300 mm of width and the thickness variations are 1.25 mm and poured at five different temperatures; 1300, 1325, 1350, 1375 and 1400°C. Several cast irons, prepared with different chemical compositions and microstructures (three lamellar and three spheroidal structures) have been examined by extensive mechanical testing and optical microscopy. The fluidity of spheroidal and lamellar graphite in cast iron increases with the pouring temperature. The numbers of nodules were decreased by increasing pouring temperature for spheroidal structures. Whereas, the numbers of flakes of lamellar structures changed by both pouring temperature and chemical composition. In general, with increasing pouring temperature, the amount of pearlite in the internal structure of both lamellar and spheroidal graphite cast iron materials were increased.

Keywords: Spheroidal Graphite Cast Iron, Lamellar Graphite In Cast Iron, Pouring Temperature, Tensile Test, Impact Test

INVESTIGATION OF THE FADING TIME EFFECTS ON MICROSTRUCTURE AND MECHANICAL PROPERTIES IN VERMICULAR CAST IRON

MEHMET EKICI^{a*}

^aYALOVA UNIVERSITY

*mekici@yaloa.edu.tr

Abstract:

In this study, the fading time affecting the mechanical properties and microstructures of vermicular cast iron were studied. Pig iron and steel scrap weighing about 12 kg were charged into the high frequency induction furnace crucible and completely melted for production of vermicular cast iron. The slag was skimmed using a common flux. After fading time was set at 1.3 and 5 minutes. In this way three vermicular cast iron was produced that same composition but different phase structures. The microstructure of specimens were investigated and uni-axial tensile test and the Charpy impact test were performed and their micro-hardness measurements were done in order to characterize the mechanical behaviours of vermicular cast iron.

Keywords: Vermicular Cast Iron, Fading Time, Hardness, Tensile Test, Impact Test

A CASE STUDY: THE EFFECT OF THE USE OF AUGMENTED REALITY APPLICATIONS ON BUILDING MARKETING PROCESS

FAZIL AKDAG^a, ZUBEYDE OZLEM PARLAK BICER^{a*}

^aERCIYES UNIVERSITY

parlakoz@yahoo.com

Abstract:

With the emerging technologies, virtual living spaces has become a part of daily life. Today, the line between the virtual and the real is getting blurry and virtuality leaves its place into a mixed environment between the real and the virtual. Tehcnologies like augmented reality (AR) enable many possibilities in many different fields. AR is formed by the combination of the real and the computer generated virtual objects in the real physical world. Today AR systems are used in many different fields like; education, medicine, games and commercials and military. The use of AR in architecture is increasing every day. The architectural design implementation is a interdisciplinary process where the architect, the client and other technical experts and engineers coexist. The AR, gives opportunity to observe the architectural designs in their real environments before they are built. With this feature, AR contributes implementation process positively. Especially the clients will be able to interact with the virtual architectural models in the real environment and will have the opportunity of examining them in many ways which will make them understand the designs better. Thus, problems based on marketing and client expectations will be solved before the implementation. Additionally production of designs that will meet the clients' expectations will be eased. In this study, the effect of the use of AR on architectural design marketing was researched. In this case study; 2D renderings and 3D AR models of the same design has been showed to the 25 clients which are chosen with random selection method. Afterwards, effectiveness of both methods is researched. Regarding to the applied survey results, the importance of the use of AR in architectural design marketing was determined. It's expected for this report to contribute especially the future works in this field.

Keywords: Augmented Reality, Architecture, Marketing Method

INFLUENCE OF HEAT TREATMENT ON THERMAL, MECHANICAL AND MICROSTRUCTURAL CHARACTERIZATION OF AL BASED MG-AL-SB EUTECTIC ALLOY

F. MEYDANERI TEZEL^a, E. VARLIK^{a*}, B. ENGIN^a, B. BULUT^a, O. OZBAY^a

^aKARABUK UNIVERSITY

*ertugrulvarlik@gmail.com

Abstract:

Al based Mg-Al-Sb eutectic alloy was melted by induction furnace, and was casted into kokil mould. Then, samples were annealed at 573 K with vacuum furnace. The values of enthalpy of fusion (ΔH) and the specific heat capacity (C_p) of the solid phase for Al based Mg-Al-Sb eutectic alloy were measured with DSC. The crystal structure parameters and the grain sizes for the tempered and the untempered alloys were investigated by XRD diffraction. The microhardness for the alloys was measured from approximately 5 different points with Vickers microhardness device. The mechanical properties of the alloys were obtained with compression test. Before and after deformation, the break surface morphology of the alloys were investigated by using Scanning Electron Microscopy (FESEM), and its compositions were determined by Energy Dispersive X-Ray (EDX) analysis.

Keywords: Heat Treatment, Specific Heat Capacity, Enthalpy, Microstructure, Mechanical Properties

OPTICAL AND STRUCTURAL PROPERTIES OF ZNSE THIN FILMS WITH CHEMICAL BATH DEPOSITION

F. MEYDANERI TEZEL^a, I. A. KARIPER^a, S. KORKMAZ^a, E. VARLIK^{a*}

^aKARABUK UNIVERSITY

*ertugrulvarlik@gmail.com

Abstract:

Zinc selenide (ZnSe) thin films were deposited on glass substrate using the chemical bath deposition method at 80 C from aqueous solutions of zinc sulphate and sodium selenosulphide in which was employed as producing selenium source with solid selenium. The structural and optical properties of ZnSe thin films were analyzed at different pH. Optical properties such as transmission, reflectance, absorbance, refractive index and dielectric constant were determined using the absorbance and transmission measurements from Hach Lange 500 spectrophotometer, at normal incidence of light in the wavelength range of 300-1000 nm. From absorbance and transmittance spectra, the band gap energies were determined ranged between 2.08 eV and 2.35 eV. The hexagonal form was observed by XRD. The pH values were scanned at 8-11. Also, the film thicknesses were measured by AFM, and were reduced with increased pH.

Keywords: Znse, Chemical Bath Deposition, Thin Film, Ph Effect, Optical Properties

FORAGE YIELD AND SOME QUALITY CHARACTERISTICS OF SWEET SORGHUM (SORGHUM BICOLOR VAR. SACCHARATUM) AS AFFECTED BY PLANT DENSITIES UNDER MEDITERRANEAN CLIMATIC CONDITIONS

HAKAN GEREN^{a*}, YASAR TUNCER KAVUT^a, HAYRULLAH BORA UNLU^a

^aEGE UNIVERSITY

hakan.geren@ege.edu.tr

Abstract:

Plant density is one of the important factor determines growth, development and yield. Plant density selection to allow for expression of maximum forage yield is a management practice that would make sorghum production more economical. Cultivation of plants with desirable density has positive effect on crop yield components, so that the suitable will be achieved by optimum plant density. This study was conducted to evaluate the effects of plant density on forage yield and some quality characteristics of sweet sorghum (*Sorghum bicolor* var. *saccharatum*) grown in summer second crop production period, on the experimental fields of Faculty of Agriculture, Ege University under Mediterranean ecological conditions of Izmir, Turkey during two years in 2013-2014. The experiment was carried out with a randomized complete block design with three replication; five plant spacings 70 cm among the rows and 5, 10, 15, 20 and 25 cm within the rows (D1:285,714; D2:142,857; D3:95,238; D4:71,428 and D5:57,142 plant ha⁻¹, respectively) were tested. 'Keller' cultivar of sweet sorghum was used as crop material. Some traits were tested in the experiment such as plant height, stem diameter, fresh & dry matter yields, sugar content, crude protein (CP) concentration, NDF and ADF contents. Average result of two years indicated that there were significant effects of plant densities on the fresh or dry matter yield and some forage quality parameters of sweet sorghum. Densely populated stands (D1 and D2) gave higher CP content compared to sparsely populated stands (D4 and D5). D3 was the most successful planting density of sweet sorghum regarding dry matter yield and crude protein yield to the regions with Mediterranean-type climates under irrigation, and it is recommended for production.

Keywords: Sweet Sorghum, Plant Density, Forage Yield, Forage Quality

AGENT-BASED MODELING AND SIMULATION OF THE SUNN PEST - WHEAT RELATION AND OF THE STRUGGLE AGAINST SUNN PEST IN TURKEY

CENAB BATU BORA^{a*}, SEVCAN EMEK^b, HUSEYIN KOSE^a

^aUSKUDAR AMERICAN ACADEMY

^bEGE UNIVERSITY

*sebnem.bora@ege.edu.tr

Abstract:

Wheat is a cereal of which agriculture has primarily been done and which is an important nutritional source for people. One of the most important problems encountered in wheat cultivation is plant mites. In this study, the struggle being performed against sunn pest, a plant mite, has been modelled in the virtual platform. Various methods have been used in the struggle against the sunn pest in our country and in the world. The effect of these methods on the sunn pest and wheat has not been simulated up to this time in the computer platform, that's why this project has arisen. In this project, the biological life cycle of the sunn pest and its effects on wheat during its active periods, the chemical and biological struggles performed were modelled after the relevant literature scan has been carried out, and were programmed in Repast Symphony 2.1 agent-based simulation platform, making use of the agents, a new generation programming paradigm. The biological growth stages of sunn pest and wheat have primarily been modelled in this study. As a result of the struggles simulated in the virtual platform, the amount of variability of the sunn pest and yielding wheat output were analyzed graphically. Biological developmental stages of the sunn pest and wheat can be observed throughout the simulation. From the findings of this study, the epidemic years of the sunn pest and the damage it will cause in future can be estimated. Making contribution to agricultural researches has been targeted by this project.

Keywords: Sunn Pest, Wheat, Predator, Agent Based Modeling And Simulation

USING MACHINE LEARNING TECHNIQUES ON PREDICTING WASTAGE AMOUNT IN TEXTILE FACTORIES

OZGUR ALTUNSOGUT^{a*}, ERDEM UCAR^a

^aTRAKYA UNIVERCITY

*ozgur@ilgisoft.com

Abstract:

Textile enterprises have a variety of processes for the processed fabric. Production of colored fabrics, which have dye or hem, completed through wide range of processes. Due to this process variety, faulty product problem inevitably arises. It is extremely important in terms of cost and profitability of the enterprise to predict this wastage which occurs during the manufacturing of processed fabrics.

This study provides information about machine learning techniques, which is one of the important work area of computer science and artificial intelligence, and also informs how to use of these techniques in order to predict wastage in the textile business. Also, the test results of a sample machine learning technique for estimation of wastage is evaluated. Subsequently, some recommendations are given how to other machine learning techniques can be used.

Keywords: Predicting, Textile, Wastage, Machine Learning, Data Mining

DESIGNING A VIVALDI FED ANTENNA FOR PASSIVE MILLIMETER WAVE IMAGING SYSTEM IN KA BAND

MEHMET DUMAN^{a*}, A. ORAL SALMAN^a

^aKOCAELI UNIVERSITY

*dumanmehmet54@gmail.com

Abstract:

This antenna will be used for Passive Millimeter Wave Imaging System (PMWIS) which has 35 GHz operating frequency described as Ka Band. The antenna should work in that specific frequency because of having low attenuation in that region according to frequency behavior in misty conditions. Antenna also should have approximately 50 ohm input impedance value so that perfect matching to the active circuits will occur. The input reflection coefficient, S_{11} , has to be under -20 dB and the gain of the antenna, G , has to be over 10 dB value for better efficiency. Micro-strip Vivaldi Fed Antenna provides all of the conditions for imaging system was designed by using Antenna Magus Computer Program and later it was designed in detail with CST Computer Program. The last format of the Vivaldi Fed Antenna has -25 dB input reflection coefficient, 48.5 ohm input impedance and 12.3 dB gain for 35 GHz operating frequency. It is ready to connect to the low noise amplifier and detector, which are active circuits of the Passive Millimeter Wave Imaging System. At the end, the detector will be connect to the video amplifier and computer. The receiver of PMWIS is composed to the Vivaldi Fed Antenna connected to the other equipment will scan elevation and azimuth angles, as a result; the video amplifier will transfer the signals to the computer. Computer will show to the user the scanning area image. In this system, antenna is the most important section and particular attention was given to the antenna in this study.

Keywords: Vivaldi Antenna, Passive Millimeter Imaging, Ka Band

DESIGN OF BAND STOP FILTER WITH FREQUENCY SELECTIVE SURFACES ANALYSIS BY IMPLEMENTING THE GOLDEN RATIO RULE

MEHMET DUMAN^{a*}, MERVE GUNEY DUMAN^b

^aKOCAELI UNIVERSITY

^bSAKARYA UNIVERSITY

dumanmehmet54@gmail.com

Abstract:

The designs which are made with frequency selective surfaces (FSS) analysis can be in different shapes and sizes. Square, round, plus, triangle, snowflake etc... are some of them. In this article, band stop filter (BSF) is designed by using frequency selective surfaces with the Golden Ratio Rule which is found by Fibonacci. In Golden Ratio Rule, each number is the sum of two numbers coming before that number and the ratio of every sequential number equals approximately 1.618, exact 1.618 at last. In design, Golden Ratio Rule is used while forming thickness, width and length. All of the simulations are run in CST Studio computer program between 700 MHz and 1700 MHz in frequency domain section. There isn't any active or passive components in the design. Only 80 cm X 130 cm copper plate and the shapes over it, the BSF with 1.35 GHz center frequency and 44 MHz band width frequency is formed and has become ready to perform. If shapes and sizes are changed while preserving the ratio, it can be reachable different center and band width frequency. After obtaining the operating frequency, the design will block the electromagnetic effects in accordance with BSF, and electric or magnetic waves cannot transmit from the copper plate, as a result; side effects which are harmful for human body can be stopped.

Keywords: Band Stop Filter, Frequency Selective Surfaces, Golden Ratio Rule

INFORMATION SECURITY RISK ASSESSMENT IN HEALTH INSTITUTIONS AND MEASUREMENT OF USERS' AWARENESS ON INFORMATION SECURITY

HACIRE OYA YUREGIR^{a*}, NAZLI BASDINKCI^a

^aCUKUROVA UNIVERSITY

oyuregir@yahoo.com

Abstract:

With increasing dependence on developing technology and computer use, national and international laws and obligations, along with the increasing risks today's information security has been a critical issue. Attacks on information systems, destruction of information and the information falling into the third parties indicate the size of the risks.

This study was aimed to make a risk assessment of information security for the purpose of measuring the level of information security awareness of users working at two different health organizations located in Adana.

In the study, 251 persons have been taken part in the survey and the threat level was determined according to the information systems users in hospitals. The collected data was analyzed with using SPSS software in order to find out the highest level of risks and list the threats according importance and existence. The relationships between these threats and individual's age, gender, educational background, professional experience, levels of computer information and information security have been revealed.

As a result, the most important threat was sharing password according to the users. The other threats were respectively : leaking patients' health information, sabotage and lack of ensuring information security system.

Information security is a critical issue for all employees and especially for managers. For this reason, information security policies should be developed by institutions, these policies should be shared with all employees and information security awareness training should be given to users.

Keywords: Information Security, Information Systems, Risk Management In Information Systems, Health Organizations, Survey

TRANSPORT PROPERTIES OF MORTAR MIXTURE CONTAINING METAKAOLIN

ALI MARDANI-AGHABAGLOU^{a*}, SULEYMAN OZEN^a

^aULUDAG UNIVERSITY DEPARTMENT OF CIVIL ENGINEERING

*suleymanozen44@gmail.com

Abstract:

In this study, effect of utilization of metakaolin on fresh and transport properties of mortar mixture was investigated. For this aim, 5, 10 and 15 wt% of cement was replaced with metakaolin. In all mortar mixtures, water/cement ratio, sand/binder ratio and flow value were kept constant as 0.485, 2.75 and 250 ± 20 mm, respectively. A naphthaline-based water reducing admixture was used for providing desired flow value. The changed in the flow values of mortar mixtures in 15 minutes time intervals up to 60 minutes were measured. 1, 3, 7, 28 and 90-day compressive strength of mortar mixtures was obtained on 50 mm cube specimens. In addition, transport properties of mortar mixtures was determined by monitoring of 3 different tests such as water absorption, water sorptivity and chloride ion penetration at the end of 90 days curing. According to the test result, fresh properties of mortar mixture were affected negatively upon using metakaolin. Mentioned effect was more pronounced by increasing replacement level of metakaolin. In spite of having lower early compressive strength, mortar mixtures containing metakaolin showed higher compressive strength compared to control mixture beyond 28 day. The fact is reported to be both due to the physical pore-filling effect and to the pore refinement upon formation of additional C-S-H through pozzolanic reaction. Besides, Transport properties of mortar mixtures improved by using metakaolin. It was more pronounced by increasing metakaolin content.

Keywords: Mortar Mixture, Metakaolin, Water Absorption, Water Sorptivity, Chloride Ion Penetration

COMPARISON OF MECHANICAL AND THERMAL PROPERTIES OF DIFFERENT AGRICULTURAL PLASTIC MULCH FILMS

MITHAT CELEBI^{a*}, OZGUR CEYLAN^a, MEHMET ARIF KAYA^a

^aYALOVA UNIVERSITY

mithat.celebi@yaloa.edu.tr

Abstract:

Mulch films are used to control the environmental conditions of plants such as temperature, moisture, growing weeds etc. In addition, mulch films enhance product yield of vegetables and fruits such as tomatoes, peppers and strawberries. These films are classified as synthetic and biodegradable plastic materials. Biodegradable mulch films have some advantages because of mulch film degradation after harvesting and do not require cost of collection. Low density poly(ethylene) (LDPE) is used traditionally in agricultural mulch applications. They have varried with different colors such as white, black and grey or transparent ones according to climate conditions and plant. In this study, mechanical and thermal properties of synthetic mulch films produced from LDPE with different colors was determined and their performances were evaluated.

Keywords: Mulch, Biodegradable, Synthetic

DO TURKISH CONSUMERS PREFER CONVERGED PRODUCTS? SMARTPHONE EXAMPLE

ULAS AKKUCUK^{a*}

^aBOGAZICI UNIVERSITY

ulas.akkucuk@boun.edu.tr

Abstract:

The smartphone market is facing a huge growth in the last few years, now reaching a sales projection for 2017 close to 15 million which makes Turkey one of the top ranked countries in smartphone market growth. Convenience and personalization are the main features of the Smartphones. Newer generation convergence products (all-in-ones, camera phones) offer consumers high quality product performance that rivals their dedicated versions. This increased availability of options starts another dilemma in the minds of consumers about purchase consideration. This paper investigates the choice patterns of Turkish university students for product forms (converged vs. dedicated) in different technological performance levels. In the end, managerial implications are addressed and directions for future research are suggested, as well as comparison of the results to previous studies.

Keywords: Smartphone, Converged Product, Dedicated Product, Technology Convergence, Turkey

COMPARISON OF MACHINING CHARACTERISTICS BETWEEN AA 6082 AND AA 6082 T6 MATERIAL WITH CRYOGENIC COOLING

BILGE DEMIR^{a*}, EMRE KOLE^a

^aKARABUK UNIVERSITY

*bdemir@karabuk.edu.tr

Abstract:

In this study, AA 6082 and AA 6082 T6 material were machined by using different cutting parameters. Here the tool geometry (tip radius and rake angle) , cutting speed, feedrate factor is used as the main variable. 134a refrigerant gas was used for cryogenic cooling. Surface roughness measurements were made to determine the most appropriate cutting parameters. As a result, it was decided to determine the best cutting conditions with optimal parameters .

Keywords: Machining, Cutting Al Alloys

CONSTRUCTION AND DEMOLITION WASTE MANAGEMENT IN TURKEY

IBRAHIM DEMIR^a, OSMAN ATILLA AR^a, KADRIYE ELIF MACIN^{a*}

^aISTANBUL TECHNICAL UNIVERSITY, CIVIL ENGINEERING FACULTY, ENVIRONMENTAL

*macin@itu.edu.tr

Abstract:

Migrations from rural areas to cities has been increasing in many parts of the world, especially in developing countries. This situation has led to an increase in construction, demolition and renovation works. Today, around 50% of the consumed products and 45% of generated solid wastes are related to the construction sector. Turkey has initiated urban transformation activities around the country with the law promulgated in 2012 and amount of C&D waste has been growth rapidly. The purpose of this study is present current C&D management system in Turkey. In this context; first definition and type of C&D wastes are given. Then, information about amount of C&D waste collected is given and some estimations were done when they were necessary. C&D waste management methods are explained and finally C&D waste management in Turkey is evaluated. C&D waste management regulations prepared by Ministry of Environment and Urbanisation and practice by city and district municipalities. Totally, 67 million ton C&D waste and excavation soil were produced only in Istanbul and according to estimations 130 million ton was produced across the country in 2013. It is expected that 150 million ton C&D waste and excavation soil will be produced in Istanbul in 2033. Currently reuse and recycling ratios are below the targets but with urban transformation activities and regulations they will increase.

Keywords: C&D Waste, Management, Recycling, Regulation.

C&D WASTE MANAGEMENT IN TURKEY

KADRIYE ELIF MACIN^{a*}, IBRAHIM DEMIR^a, OSMAN ATILLA ARIKAN^a

^aISTANBUL TECHNICAL UNIVERSITY

macin@itu.edu.tr

Abstract:

Migrations from rural areas to cities has been increasing in many parts of the world, especially in developing countries. This situation has led to an increase in construction, demolition and renovation works. Today, around 50% of the consumed products and 45% of generated solid wastes are related to the construction sector. Turkey has initiated urban transformation activities around the country with the law promulgated in 2012 and amount of C&D waste has been growth rapidly. The purpose of this study is present current C&D management system in Turkey. In this context; first definition and type of C&D wastes are given. Then, information about amount of C&D waste collected is given and some estimations were done when they were necessary. C&D waste management methods are explained and finally C&D waste management in Turkey is evaluated. C&D waste management regulations prepared by Ministry of Environment and Urbanisation and practice by city and district municipalities. Totally, 67 million ton C&D waste and excavation soil were produced only in Istanbul and according to estimations 130 million ton was produced across the country in 2013. It is expected that 150 million ton C&D waste and excavation soil will be produced in Istanbul in 2033. Currently reuse and recycling ratios are below the targets but with urban transformation activities and regulations they will increase.

Keywords: C&D Waste, Management, Recycling, Regulation.

THE INVESTIGATION OF DISCHARGE COEFFICIENT FOR DIFFERENT UPSTREAM CREST LENGTHS IN TRIANGULAR LABYRINTH SIDE WEIRS

YUSUF DOGAN^{a*}, NIHAT KAYA^b

^aCONSTRUCTION DEPARTMENT, TUNCELI VOCATIONAL COLLEGE, MUNZUR UNIVERSITY

^bCIVIL ENGINEERING, ENGINEERING FACULTY, FIRAT UNIVERSITY

*yusufdogan14@hotmail.com

Abstract:

Weirs are the most simple hydraulic structures in terms of practical and the oldest used for centuries for purposes such as flow measurement and flood control. There are three main types: sharp-crested, broad crested and labyrinth weirs. It is also classified in the form of overflow weirs and side weirs. It is observed in literature reviews that there isn't any flow in side weirs, high froude numbers, part of the upstream crest length. This leads to decrease of discharge capacity. For this purpose a series of experiments have been carried out for different upstream crest lengths. Thus, the main purpose of this study is to examine in detail the effect of the change of the upstream crest length in sharp-crested labyrinth side weirs on the discharge capacity. Present experiments have been carried out on a triangular section with a 0.25 m weir length in the straight channel and a 45 degree apex angle for 0.12, 0.16, 0.20 m crest heights. The weir upstream crest length was closed and readings were taken in three stages at each crest height. The experiments were carried out by taken a flow change of 8-145 L/s and froude number of 0.08-0.90. The experiments have been carried out under subcritical flow regime and steady flow conditions. Readings were obtained for minimum 30 mm nape thickness, Froude numbers and discharge coefficients were calculated and necessary graphics were plotted. De Marchi method was used in this study. It has been determined that there is decrease in discharge coefficient as a result of the study. Parallel to the differences in comparison to the process and methods applied in the literature reviews, the study in terms of both theoretical and experimental basis will make a significant contribution to the subject of triangular labyrinth side weirs.

Keywords: Straight Channel, Discharge Coefficients, Side Weirs

EFFECTS OF SELECTIVE LASER SINTERING (SLS) METHOD ON MICROSTRUCTURAL FEATURES OF Ti6Al4V POWDER ALLOY

MEHMET CENGİZ KAYACAN^{a*}, KORAY OZSOY^b, YUNSU EMRE DELIKANLI^b, BURHAN DUMAN^b

^aSULEYMAN DEMİREL UNIVERSITY, ENGINEERING FACULTY, MECHANICAL ENGINEERING

^bSULEYMAN DEMİREL UNIVERSITY, SENİRKENT VOCATIONAL SCHOOL

*cengizkayacan@sdu.edu.tr

Abstract:

Additive Manufacturing is one of the methods of modern (non-traditional) manufacturing. The fundamental of this method is based on adding materials layer by layer on top of each other. The purpose of this method is manufacturing the parts that cannot be manufactured by traditional machining process because of their geometrical complexity, disposing the limits of manufacturing. Nowadays Laser Sintering and Melting machines can rapidly manufacture the parts that cannot be manufactured by traditional machining process because of their geometrical complexity in many fields by using various metal powders.

In this article, test specimens were manufactured via Selective Laser Sintering of Additive Manufacturing Method by using Ti6Al4V metal powder. Test specimens were manufactured via SLS method, different machining parameters as laser power, laser hatching speed, hatching distance and in various energy density values based on these parameters by their island and grid hatching strategies. After the grinding, polishing and etching processes of Ti6Al4V alloys that were manufactured with different machining parameters via SLS method, in their microstructural analysis, pore distribution and dimension, α/β phase transformation were examined. Besides, EDX elemental analysis was performed. The results were benchmarked. Findings were compared with the literature.

Keywords: Additive Manufacturing, Selective Laser Sintering, Ti6Al4V, Microstructure

SULFATE RESISTANCE OF POLYPROPYLENE FIBER REINFORCED CONCRETE

ALI MARDANI-AGHABAGLOU^a, SULEYMAN OZEN^{a*}, KAMBIZ RAMYAR^b

^aULUDAG UNIVERSITY, DEPARTMENT OF CIVIL ENGINEERING

^cEGE UNIVERSITY, DEPARTMENT OF CIVIL ENGINEERING

*suleymanozen44@gmail.com

Abstract:

In this study, sulfate resistance of polypropylene fiber reinforced concrete was investigated. For this purpose, two series of concrete mixtures having 0.45 water/cement ratio were prepared. A CEMI 42.5 R type portland cement and crushed limestone aggregate having a maximum particle size of 25 mm were used. The gradation of combined aggregate, obtained by mixing 60% 0-5 mm, 20% 5-15 mm and 20% 15-25 mm aggregate size fractions (by mass) was confirmed with standard gradation limits. In addition to the control mixture containing no fiber, concrete mixture containing 0.4% by volume polypropylene fiber with 5 mm length was produced. In all mixtures, cement content and slump value were kept constant as 350 kg/m³ and 12±20 mm, respectively. A polycarboxylate ether-based high range water reducing admixture was used for providing the desired slump value. The slump loss of concrete mixtures within 60 minutes was measured in 20 minutes time intervals. 7 and 28-day compressive strength of concrete mixtures were measured on 150 mm cube specimens. The 150 mm prism specimens were prepared for sulfate resistance tests. The specimens were immersed in 5% sodium sulfate solution. The length changes of concrete samples were measured every 30 days until 150 days. According to test results, the required water reducing admixture content for providing desired slump value increased by adding polypropylene fiber into the concrete mixtures. Utilization of the polypropylene fiber has not significant effect on compressive strength of concrete mixtures. However, length changes of concrete mixtures arisen from sulfate attack decreased by using fiber.

Keywords: Concrete Mixture, Fresh Properties, Compressive Strength, Sulfate Attack, Polypropylene Fiber

MODELING AND SIMULATION OF THE RESISTANCE OF BACTERIA AGAINST ANTIBIOTICS

CENAB BATU BORA^a, SEVCAN EMEK^b, VEDAT EVREN^c, SEBNEM BORA^{d*}

^aUSKUDAR AMERICAN ACADEMY

^bEGE UNIVERSITY

^cEGE UNIVERSITY, FACULTY OF MEDICINE, DEPARTMENT OF PHYSIOLOGY

^dCOMPUTER ENGINEERING DEPARTMENT, EGE UNIVERSITY

*sebnem.bora@ege.edu.tr

Abstract:

Nowadays, the unnecessary use of antibiotics comes up as an important health problem. Unnecessary and inappropriate use of antibiotics causes antibiotic resistance which has become an important problem in the community and in hospitals. Antibiotic resistance causes antibiotic to lose its ability for killing a particular bacteria or blocking its reproduction. This issue leads to the increase in the number of patients suffering seriously from both society-induced and medical infections, and the failure of treatment, even cases resulting in death. While the resistant bacteria continue to increase, surviving against antibiotic; it causes for disease to last longer, prolongation of treatment and cost increase. It was aimed in this study to investigate the interactions among the bacteria, immune system cells and antibiotics in a Repast Symphony 2.1 agent based simulation environment, having been modelled, and to observe the effects of variability of antibiotic resistance on the infection process. We have found as a result of the study that the increase of antibiotic resistance has become a serious threat against the results of the treatment of bacterial infections.

Keywords: Agent Based Modeling, Simulation, Antibiotic Resistance, Immune System

MONITORING AND ANALYSING OF LOOMS TO IMPROVE PERFORMANCE OF WEAVING HALL

BEDRI BAHTIYAR^{a*}

^aPAMUKKALE UNIVERSITY

*bedribahtiyar@pau.edu.tr

Abstract:

Efficiency of weaving machines is a very effective parameter on the cost of productions. In this study, in order to improve the performance of a weaving hall, data are gathered from looms individually and collected in a central computer by the designed system which is implemented real textile industry in Denizli in Turkey. Thus the statuses of all looms in weaving hall are monitored on-line on the screen of the central computer and an increase on the performance of weaving hall is achieved by analyzing these data.

Keywords: Monitoring, Improving Performance, Weaving Machines, Embedded Systems

THE EFFECT OF OSMOTIC DEHYDRATION PRETREATMENT APPLIED TO APPLES ON THE QUALITY PARAMETERS OF THIS FRUITS AND KINETIC MODELING

FERIT AK^{a*}, ALPER GUVEN^a, MUKERREM KAYA^b

^aFOOD ENGINEERING, FACULTY OF ENGINEERING, MUNZUR UNIVERSITY

^bFOOD ENGINEERING, FACULTY OF AGRICULTURE, ATATURK UNIVERSITY

*feritak@munzur.edu.tr

Abstract:

The aim of present study is to analyse the effect of osmotic dehydration pretreatment applied to apples on the quality parameters of this fruits and kinetic modeling. For this purpose, at the end of time periods as 0, 60, 120, 240, 360 and 480 minutes of 8 hours immersion time, the effect of 25%, 45%, 55% and 65% sucrose concentrations and 25°C, 35°C and 45°C immersion temperatures on apple cubes has been studied. Mass transfer mechanisms have been modeled by calculating kinetic parameters such as water loss, solid gain and weight decrease of samples. Besides, the results have been evaluated with the analyses of water activity value, colour and rehydration rate.

During the osmotic dehydration process as associated with water loss and solid gain parameters. L* colour values of fruits have decreased compared to fresh samples, however this decrease has less in high sucrose concentrations. It has been remarked b* colour values of fruits have increased during osmotic process. When It has determined that fruit samples with osmotic process have had less rehydration rate than non-processed samples, this rate has been measured as 4.84 in apple. It has been determined that P% values of samples except 25% sucrose concentrations are low and emprical results are very suitable to the model when Azuara et al. (1992) and Hawkes and Flink (1978) mass transfer models have been analysed in order to carry out the equilibrium water loss and equilibrium solid gain values. Equilibrium water loss values of apple samples have been obtained at 45°C in 65% sucrose concentration as 75.18%

It has been conclusion that the osmotic dehydration process have a positive effect on quality values and kinetic parameters of apple samples.

Keywords: Osmotic Dehydration, Mass Transfer, Modeling, Texture, Apple

USE OF QUICK COUPLINGS IN DESIGN OF WORK DIES

IDRIS KARAGOZ^{a*}

^aYALOVA UNIVERSITESI

*idris.karagoz@yalova.edu.tr

Abstract:

Work dies are generally equipment with complete machine and equipment, enhance their function, enable integrity of measurement and location and ease the production and make it possible for a work to be carried out more easily and effectively. In this study a clamping work dies was designed by using quick couplings in bonding plastic or metal plates with friction stir welding (FSW) in high-speed CNC machine. In the design specific criteria were considered such as input-output direction of welding set, shoulder width measurement, equal distribution of the pressure applied on metals, light and portable dies, rapid assemble and disassemble of the plates. With the designed work dies, friction stir welding practices were done on Poly ethylene (PE) plates for trial. It was observed that the work dies which was created as a result of design is compatible with its aim and with what was expected at the beginning of design and can be used successfully in friction stir welding practices. Especially in automotive industry, fixtures are used for serial welding of equipment whose assembling is difficult and complex. It was determined that quick couplings which are used in the design would provide us convenience and practicability fort hey can be used together with both work dies and fixtures in such practices.

Keywords: Work Dies, Manufacturing, Welding, Quick Couplings, Automotive Industry

MECHANICAL AND COMFORT PROPERTIES OF FABRICS PRODUCED WITH HOLLOW YARNS

ILKEM AYTAÇ^a, PELİN GÜRKAN UNAL^{a*}

^aNAMIK KEMAL UNIVERSITY, CORLU ENGINEERING FACULTY, TEXTILE ENGINEERING DEPARTMENT

*pelingurkan@gmail.com

Abstract:

In the scope of this study, core yarns in the yarn count of 59 Tex were produced by using cotton, viscose, and polyester fibres in the mantle and different ratios of polyvinylalcohol(PVA) in the core. After completion of yarn production on ring spinning frame, winding process was performed in order to get packages. These yarns in the form of packages, were used to produce plain knitted fabrics. Single jersey fabrics were produced on laboratory typed knitting machine and after the fabric production, fabrics were divided into two classes according to washed and non-washed fabrics. Washing process was performed in order to remove PVA-core from the yarn structures to obtain hollow yarn structure which will enhance the comfort properties of the fabrics produced with these type of yarns whereas will influence negatively the mechanical properties of the fabrics. The comfort and mechanical properties of washed and non-washed single jersey fabrics were measured under standard laboratory conditions. These performed tests were mass per unit area, air permeability, water vapour permeability, wicking, pilling and bursting strength. As a result of these tests; it was observed that before and after washing process, results of air and water vapour permeability, wicking, pilling, bursting strength test measurements are significantly influenced by the mantle-core proportion. In this way, due to high permeability characteristics of fabrics made of hollow yarns have been determined that it may be used for sports clothing.

Keywords: Core Yarn, Hollow Yarn, PVA, Air Permeability, Water Vapour Permeability, Wicking, Pilling, Bursting Strength.

CREATING ALTERNATIVE PRODUCTION LINES BY USING SIMULATION TECHNIQUE IN APPAREL PRODUCTION

CAN UNAL^{a*}

^aNAMIK KEMAL UNIVERSITY

*cunal@nku.edu.tr

Abstract:

In this study, discrete-event system simulation technique is used in order to create a smooth work flow in t-shirt production line. In accordance with this purpose; work flow of t-shirt model is created, input data is collected by using time study in order to determine statistical distribution of all operations by using Stat-fit for Simul8 software. Model translation phase is executed in Simul8 Software. Then for the purpose of verification & validation process, actual system data and simulation model outputs are compared statistically by using normality test and two-sample t-test in Minitab Software. Once the simulation model of the actual system is properly validated, alternative models which are considering less operators in order to acquire more output and have a smoother line balance are generated. Finally, to analyze the difference of alternative models, two sample t-test is performed. The best alternative model is selected by considering output rate per operator.

Keywords: Apparel Industry, Simulation Technique, Productivity, Line Balancing

THERMODYNAMIC ANALYSIS OF SIMAV GEOTHERMAL DISTRICT HEATING SYSTEM ASSISTED BY SOLAR ENERGY

HALIT ARAT^{a*}, MERVE SENTURK ACAR^b, OGUZ ARSLAN^a

^aDUMLUPINAR UNIVERSITY/MECHANICAL ENGINEERING DEPARTMENT

^bDUMLUPINAR UNIVERSITY/ELECTRICITY AND ENERGY DEPARTMENT

*halit.arat@dpu.edu.tr

Abstract:

In this study, the usage of the evacuated tube solar collectors in a large district heating system was investigated. By this way, Simav geothermal district heating system, located in the southern part of the Simav graben system (39° latitude, 28°4' longitude) at Kutahya province in western Anatolia of Turkey, were taken into account. The proposed system consists of four sub-circuits. The Circuit I is geothermal flow cycle which transfers the heat from the geothermal fluid (98°C and 400 kPa) to the heat exchanger, Circuit II is solar heat storage cycle which save the heat from getting the solar collector, Circuit III is district heating cycle and Circuit IV is residential heating cycle which utilize the radiator with an inlet temperature of 55°C and outlet temperature of 45°C. The effect of monthly solar radiation employing the different number of the solar collectors was evaluated in the proposed system in point of changing the parameter of the thermal energy storage inlet temperature using energy and exergy analysis. According to calculations, the number of heated residences by solar energy change between 384 and 1,363. The number of the used solar collector per the heated residence calculated between 4 and 16.

Keywords: Energy-Exergy Analysis, Geothermal, Solar Collector, District Heating.

FUTURE BASED ON ADDITIVE MANUFACTURING TECHNOLOGIES: 3D PRINTING

SINAN APAK^{a*}

^aMALTEPE UNIVERSITY

*sinanapak@maltepe.edu.tr

Abstract:

The availability of the product is vital as the consumer needs increase. Difficulties in production and supply chain cause manufacturers to quickly adopt new technologies. Nowadays, 3D printing (3D-P), one of the new technologies that mentioned as an additive manufacturing (AM), is a solution to many production problems. AM is building 3D objects by adding layer-upon-layer of material, whether the material is plastic, metal or concrete. The 3D-P, which have been chosen because of the fact that they can only make rapid prototypes, and because they speed up the design process very much, have come to the level of being used for the final product production with the development of the technology used. Today, 3D AM technology is used for modeling, prototype manufacturing, tool manufacturing, limited production parts, and specific parts manufacturing applications. More recently, 3D AM is being used to fabricate end-use products in aircraft, electronic circuits, dental restorations, education, space researches, medical implants, aircraft engines, automobiles, and even fashion products. The main advantages of 3D AM technology are the freedom to design, the production of complex designs at much cheaper cost, the inadequacy of team needs, the possibility of lighter designs, and the elimination of a few of the production steps in one go. The most positive aspect of this technology is that the products that are simple structures with three-dimensional printers can be produced by everyone, that is, they are the same as those that produce and consume. Innovations that 3D AM will bring; much faster product development and commissioning processes; production strategies and methods to be prepared from scratch; change in profit and raw material sources; brand new abilities; new competitors. This research compiles the development process, usage areas and innovations of 3D AM technology.

Keywords: Additive Manufacturing, 3D Printing,

DETERMINING THE WORK FLOW AND STANDARD UNIT TIMES OF A SHIRT PRODUCTION LINE

CAN UNAL^{a*}

^aNAMIK KEMAL UNIVERSITY

*cunal@nku.edu.tr

Abstract:

It is difficult to determine the productivity of production units because of the complexity of operations and the variability of operators. Therefore, certain techniques have been developed to collect necessary data and measure productivity. Time study is one of these techniques which is based establishing an actual allowed time standard for performing a given task, with due allowance for fatigue and for personal and unavoidable delays.

In this study, production flows are created for three different models produced in a shirt production band of an apparel factory where suits are produced. Then, time study is applied in shirt production band and the standard unit times of three different models are determined by dividing the operations into elements, watching the operator for several cycles and recording the time with a stopwatch. During the time study process, the number of observations' cycle is calculated statistically in order to compose an equitable standard. Owing to determined standard unit times, it is possible to estimate the due date of the future orders.

Keywords: Apparel Industry, Work Flow, Time Study, Productivity

NUMERICAL ANALYSES OF A HEAT EXCHANGER IN A THERMAL ENERGY STORAGE SYSTEM

MELTEM KOSAN^{a*}, H. MEHMET SAHIN^a

^aDEPARTMENT OF ENERGY SYSTEMS ENGINEERING, GAZI UNIVERSITY

*mltmkosan@gmail.com

Abstract:

In this study, a numerical calculation has been performed to compare the experimental results in the literature. In this respect, thermal behavior and heat transfer characteristics of Paraffin Wax (melting point between 45°C and 51°C) as the phase change material (PCM) have been investigated during constrained melting and solidification processes inside a shell-and-tube type of heat exchanger. Due to PCMs low thermal conductivity, the influence of fins applying in the heat exchanger has studied for enhancing the heat transfer in the melting processes. Two-dimensional transient numerical simulations have been carried out using the ANSYS Fluent 16.2 commercial software package. The simulations results have indicated that as the length of fins increases, the heat transfer increases and the melting time decreases. Furthermore, the length of fins and natural convection play important roles during the melting process.

Keywords: Latent Heat Energy Storage, Phase Change Material, Melting, Fins

TEXTURAL PARAMETERS AND ULTRASTRUCTURAL CHANGES OF AMASYA APPLES BY APPLIED WITH OSMOTIC DEHYDRATION PRETREATMENT

FERIT AK^{a*}, ALPER GUVEN^b, MUKERREM KAYA^c

^aMUNZUR UNIVERSITY

^bFOOD ENGINEERING, FACULTY OF ENGINEERING, MUNZUR UNIVERSITY

^cFOOD ENGINEERING, FACULTY OF AGRICULTURE, ATATURK UNIVERSITY

*feritak@munzur.edu.tr

Abstract:

The aim of present study is to analyse the effect of osmotic dehydration pretreatment applied to Amasya apples on the textural parameters and ultrastructural changes of this fruits. For this purpose, at the end of time periods as 0, 60, 120, 240, 360 and 480 minutes of 8 hours immersion time, the effect of 25%, 45%, 55% and 65% sucrose concentrations and 25°C, 35°C and 45°C immersion temperatures on apple cubes has been studied. The results have been evaluated by analyzing on scanning electron microscope with the aim of determining microscopic structure changes and by using Texture Profile Analyser textural characteristics.

During the osmotic dehydration process as associated with water loss and solid gain parameters, the increase in adhesiveness, cohesiveness and elasticity values has been determined while there has been the decrease in textural values such as hardness, springiness, gumminess, and chewiness in texture profile analysis of fruit samples. It has been determined that there are ultrastructural changes generally such as collapse and shrinkage in the cells, contraction in the intracellular spaces, deformation in the cell's walls and largening in intercellular spaces when microscopic structure of fruit samples having osmotic dehydration process by scanning electron microscope has been examined.

Consequently, the hardness is one of the most important parameters in fruits. During the osmotic dehydration, it has been identified that the hardness values of apple samples increasingly decreased along with an increased in solution concentration and process temperature. This decreased has been explained with water loss which occurred in osmotic dehydration and therefore turgor pressure diminished in the cells. Because the differences where in microscopic structure of apple samples arised from in cells and intercellular spaces, it has been determined that ultrastructural changes and textural characteristics are related each other.

Keywords: Amasya Apple, Osmotic Dehydration, Texture Profile Analysis, Microscopic Structure.

A NEW TITANIUM MESH CAGE DESIGN FOR LUMBAR SPINE STABILIZATION FOLLOWING CORPECTOMY

HUSEYIN LEKESIZ^{a*}, ILYAS DEDEGIL^a, SENA BAYRAKTAR^a, KAUR BHULLAR^a

^aBURSA TECHNICAL UNIVERSITY

huseyin.lekesiz@btu.edu.tr

Abstract:

Corpus of a vertebra transmits the 80% of the axial load and therefore it has a critical importance for the stability of spine. This part of vertebra can become malfunctioned due to various reasons and removal of this part (corpectomy) may be inevitable in some cases such as trauma or tumor. Titanium mesh cages (TMC) are widely used in stabilization of spine followed by corpectomy and bone grafting in TMC to create a fusion between vertebrae may be required for better stabilization. Various designs of cages are available for application, however, biomechanical characteristics of stabilized spine is not examined in detail in literature.

In this study, a healthy human lumbar spine with L1-L2-L3 segment including the intervertebral disks and all ligaments is modeled mechanically using Finite Element Method (FEM). A stabilized segment with corpectomy of L2 followed by cage and bone graft insertion is also analyzed again using FEM. The integrity of cage for all possible motions; left/right bending, flexion/extension, torsion and compression are considered in biomechanical investigation. The cage is designed with re-entrant cell shape which brings the unique characteristic known as the auxeticity.

When the healthy spine and stabilized spine is compared for all motions, stabilized spine with auxetic TMC+Bone Graft presents very close stress distribution only with slightly higher stress values in stabilized model. This is a desired situation because lower stress values may lead weakening of bones in recovery stage. These results indicate that auxetic mesh cage and bone graft contributes the stability of spine significantly and can be alternative method for spinal fixation. It also brings the advantage of auxetic structure where cage will contract itself under high compressive loadings where it will avoid moving towards the posterior region of cage and protect the spinal cord under traumatic or progressively improving instabilities.

Keywords: Spine, Titanium Mesh Cage, Auxetic, Finite Element Method

INVESTIGATION OF A CHEMICAL MODIFICATION METHOD WHICH ENABLE POLYAMIDE/ELASTANE FABRICS TO BE DYED AT LOWER TEMPERATURES

RIZA ATAV^{a*}, MUHAMMED FATIH YUKSEL^a, ISMAIL YAKIN^b

^aNAMIK KEMAL UNIVERSITY, DEPARTMENT OF TEXTILE ENGINEERING

^bSETAS KIMYA SANAYI A.S.

riza_atav@yahoo.com

Abstract:

Within this study, dyeability of the polyamide/elastane fabrics, which are commonly used in textile industry, below the boiling temperature with 1:2 metal complex dyes without causing loss of efficiency was examined. For this aim, firstly studies on developing a cationization agent which can modify fibers chemically was investigated. Then its application process was determined with the aim of making possible to dye polyamide/elastane fabrics at low temperature (80°C). As a result of experiments, optimum conditions of cationization treatment were determined as pH 7, 60°C, 30 min. and a concentration of 5% for decreasing dyeing temperature to 80°C. Fabric samples treated at these conditions were dyed at 80°C and results were compared with the untreated sample dyed at 100°C. It was seen that it was possible to decrease dyeing temperature from 100°C to 80°C without a loss in color efficiency or decrease in fastness values if cationization treatment was done. All results were also proved by industrial scale experiments.

Keywords: Polyamide, Elastane, Dyeing, Cationization, Color Yield, Fastness

PROGRAMMING ENCRYPTION ALGORITHMS WITH STEGANOGRAPHY

MUHARREM TUNCAY GENCOGLU^{a*}

^aFIRAT UNIVERSITY

*mtgencoglu23@gmail.com

Abstract:

In this paper a different cryptographic method is introduced by using Power series transform, science of steganographi. Here,we produce a new algorithm for cryptology,we use Expanded Laplace transformation of the exponential function for encrypting the plain text and we use codes of ASCII for support to the confidentiality of the chipertext. After, Chipertext have embedded by steganographic method in another plaintext to hide the existence of chipertext. We show corresponding inverse of Power Series transform for decryption. Then; Experimental results were obtained by writing a computer program for crypto machines.

Keywords: Cryptology, Encryption, Decryption, Laplace Transform, Steganography, Programming For Encryption Algorithms.

MICROPROCESSOR CONTROLLED RESPIRATORY FUNCTION TEST SIMULATOR

HASBI APAYDIN^{a*}, SUKRU KITIS^a

^aDUMLUPINAR UNIVERSITY

*hasbi.apaydin@dpu.edu.tr

Abstract:

In this study, simulator design that everybody can use easily was performed for respiratory function test applied to people having shortness of breath, stertorous respiration, expectorating complaints, to people who smokes cigarette for a long time whether they have complaints or not, to people thinking illness that exists in another organ of the body affects lung, to athletes, to people to be given inhaler, relieving inflammation, and preservative medications because of their illness, and to people that effect of medications want to be investigated.

Among function tests; air volume entering and exiting to lungs during relaxation or exercise, maximum air amount (FEV1) to be exhaled in one second while lungs are full, and reversibility that are measurements test about whether velocity increases or not with expander medications (bronkodilators) by this simulator.

A PIC16F877 based design was performed for this. Analogue signals obtained with blowing flow meter flow sensor are translated to digital information by PIC. LED group consisting from 16 groups was designed as 5 levels. These 5 levels will become active in stages according to age groups or volume given by lungs during blowing, and it will assist to be informed of us.

Respiratory function tests can also be used to observe response to the treatment as well as they are subsidiary tests for diagnosis. As much as respiratory function tests assist diagnosing some diseases, especially asthma and COPD, they are important tests playing role on determining of severity of these diseases, and on evaluating response of the treatment. Not only these tests are used by chest diseases clinics, but also they are used to measure the effect of rheumatic, neurologic, hematologic diseases on lung functions, and to evaluate response to the treatment. It will be contributed to observe conditions of lungs by this designed device.

Keywords: Respiratory Function Test-Microprocessor Control-Simulator

MICROSTRUCTURAL EVALUATION OF T6-TREATED A380 ALLOY MANUFACTURED BY SEMI-SOLID METAL CASTING

RIDVAN GECU^{a*}, SERHAT ACAR^a, ALPTEKIN KISASOZ^a, KEREM ALTUG GULER^a, AHMET
KARAASLAN^a

^aYILDIZ TECHNICAL UNIVERSITY

ridvangecu@gmail.com

Abstract:

Semi-solid metal (SSM) processes have been widely used in aluminum production as an alternative to conventional casting methods for many years. It is possible to obtain uniform non-dendritic microstructure with less porosity by using SSM techniques. Low superheat casting (LSC) is a kind of SSM method that operates at just above the liquidus temperature of subjected alloy. This method causes equiaxed grain formation instead of dendrites due to the combination of low heat input and rapid cooling. Reheating after LSC process provides transformation of equiaxed grains into spherical particles. In this study, A380 aluminum alloy was poured at 615°C in LSC technique and non-dendritic formation was achieved. Samples were reheated at a semi-solid temperature of 575°C after LSC and held there for varied times from 20 to 80 min. After reheating part, specimens were solution treated at 520°C, quenched and artificial aged at 180°C. Image analyser assisted optical microscopy and Brinell hardness test equipment were used to determine microstructural evaluation and related mechanical behavior of A380 alloy. It was concluded that spherisation of α -Al grains was increased with increasing reheating time and T6 heat treatment process leads to improve hardness by newly formed precipitates.

Keywords: Low Superheat Casting, A380 Alloy, Aluminum, Aging

INVESTIGATION OF THE DYEABILITY OF COTTON KNITTED FABRICS WITH WITH VARIOUS DYE PLANTS IN THE PRESENCE OF POTASSIUM ALUMINUM SULFATE MORDANT

RIZA ATAV^{a*}, KAYA KARABULUT^a

^aNAMIK KEMAL UNIVERSITY

*riza_atav@yahoo.com

Abstract:

As the certain chemical compounds present in synthetic dyes are carcinogenic, mutagenic and allergic, dyes obtained from natural sources are increasingly gaining importance in the textile dyeing field. In the content of this study, cotton fabrics were dyed in the presence of potassium aluminum sulfate mordant with 39 different dye plants. Then both color efficiency and fastness properties of dyed samples were evaluated. Dye plants that give both good color efficiency and sufficient fastness values were determined. According to the experimental results it can be said that for yellow pomegranate rind or turmeric; for green myrobalan; for yellowish brown onion hell; for reddish brown catechu give the best results.

Keywords: Cotton, Natural Dye, Mordant, Fastness, Color Yield

CORROSION, MECHANICAL AND MICROSTRUCTURAL CHARACTERISTICS OF MODIFIED NAVY G BRONZE CASTS

MEHMET TURKER^a, SERHAT ACAR^{b*}, ZEKERIYA YASAR COMERT^b, ALPTEKIN KISASOZ^b, KEREM ALTUG GULER^b

^aTURKISH NAVAL ACADEMY

^bYILDIZ TECHNICAL UNIVERSITY

seacar@yildiz.edu.tr

Abstract:

High tin bronze alloys have been widely applied in various fields including marine industry due to their high strength, good wear properties and good corrosion resistance. In this study modified navy g bronze was cast via conventional sand mould casting (SMC) technique. Chemical composition of the alloy was determined with optical emission spectroscopy. Mechanical properties were investigated through Brinell hardness, tensile and Charpy impact tests. Also the microstructure of the specimen was examined with optical microscope and energy-dispersive X-ray spectroscopy in order to better understanding of related properties. Corrosion tests were conducted by immersion of the specimens in three different media (0.5 M HCl, 0.5 M H₂SO₄ and 3,5% NaCl solutions) and carried out according to ASTM G1 – 03. Whole collected results were evaluated by comparing with the properties of other standardized materials in the industry.

Keywords: Navy G Bronze, Sand Mould Casting, Mechanical Characterization, Corrosion Testing

SURFACE PLASMON RESONANCE BASED ON MOLECULAR IMPRINTED SENSOR FOR MELAMINE DETECTION

NECIP ATAR^{a*}, MEHMET LUTFI YOLA^b

^aDEPARTMENT OF CHEMICAL ENGINEERING, ENGINEERING FACULTY, PAMUKKALE
UNIVERSITY

^bDEPARTMENT OF METALLURGICAL AND MATERIALS ENGINEERING, FACULTY OF
ENGINEERING, SINOP UNIVERSITY

*necipatar@gmail.com

Abstract:

Melamine is used primarily in the synthesis of melamine formaldehyde resins for manufacturing laminates, plastics, coatings, commercial filters, glues or adhesives, dishware, and kitchenware. It has been illegally added to dairy products to obtain high readings of total nitrogen content as the false measurement of protein level [2,3]. In this report, we developed surface plasmon resonance (SPR) sensor [3] for the sensitive determination of melamine (MEL) in milk sample. Firstly, the modification of gold surface of SPR chip was performed by allyl mercaptane. Then, MEL-imprinted poly(2-hydroxyethyl methacrylate–methacryloylamidoglutamic acid) [p(HEMAGA)] nanofilm was generated on the allyl mercaptane modified gold surface. The unmodified and imprinted surfaces were characterized by fourier transform infrared (FTIR) spectroscopy, ellipsometry and contact angle measurements. The developed method was validated according to the ICH guideline. The linearity range and the detection limit were obtained as 0.1 – 1.0 ng/mL and 0.030 ng/mL, respectively. The developed imprinted nanosensor was applied to the milksamples for the determination of MEL. In addition, isotherm models were applied to data to explain adsorption process.

Keywords: Melamine; SPR; Molecular Imprinting

SYNTHESIS OF POLYOXOMETALATE/MULTI-WALLED CARBON NANOTUBES HYBRID AND APPLICATION FOR RUTIN DETECTION

NECIP ATAR^{a*}, MEHMET LUTFI YOLA^b

^aPAMUKKALE UNIVERSITY, FACULTY OF ENGINEERING, DEPARTMENT OF CHEMICAL ENGINEERING

^bDEPARTMENT OF METALLURGICAL AND MATERIALS ENGINEERING, FACULTY OF ENGINEERING, SINOP UNIVERSITY

*necipatar@gmail.com

Abstract:

Flavonoids are polyphenolic compounds and constitute a significant part of the human diet. The antioxidant and anti-inflammatory properties of these compounds are indicated [1]. Rutin belongs to the flavonoid family that is distributed in fruits and vegetables. Carbon nanotubes are expected to play a significant role in the design and manufacture of many nano-material devices in the future. Carbon nanotubes exhibit many unique properties which generate strong interests in studying their applications [2]. Polyoxometalates (POMs) are highly redox-active material with great potential for electrochemical sensors. Due to their chemical versatility and stability, they can be utilized in catalysis, energy studies, and nano-electronics [3]. The prepared surfaces were characterized by electrochemical impedance spectroscopy (EIS) and scanning electron microscope (SEM). The developed electrochemical sensor was also applied for the determination of rutin in food sample and the linearity range of rutin was 1.0×10^{-8} - 1.0×10^{-5} M with the detection limit of 2.0×10^{-9} M.

References

[1] A. Wojdyło, et al., Food Chem. 105 940 (2007)

[2] P.M. Ajayan, Chem. Rev. 99 1787 (1999)

[3] T. Eren, et al., Ionics 21 2193 (2015)

Keywords: Rutin; Nanocomposite; Detection

ELECTROCHEMICAL SENSOR VIA GRAPHENE QUANTUM DOTS FOR DETERMINATION OF ASCORBIC ACID

ASLI ATAR^{a*}, MEHMET LUTFI YOLA^b, CEREN GODE^c, NECIP ATAR^d

^aRESEARCH AND DEVELOPMENT CENTER, MENDERES TEXTILE, DENIZLI

^bDEPARTMENT OF METALLURGICAL AND MATERIALS ENGINEERING, FACULTY OF ENGINEERING, SINOP UNIVERSITY

^cPAMUKKALE UNIVERSITY, SCHOOL OF DENIZLI VOCATIONAL TECHNOLOGY, PROGRAM OF MACHINE

^dPAMUKKALE UNIVERSITY, FACULTY OF ENGINEERING, DEPARTMENT OF CHEMICAL ENGINEERING

*asliatar84@gmail.com

Abstract:

Ascorbic acid is an important vitamin and the insufficient intake shows symptoms of scurvy [1]. Graphene/graphene oxide has been crucial material in sensor technology because of its catalytic effect. Graphene quantum dots (GQDs) are smaller than graphene sheets. The edge properties of GQDs cause effective surface area and high electrochemical effect [2,3]. GQDs are also single atomic layer as graphite. Therefore, the studies about GQDs in chemistry and nanotechnology have increased recently. In this study, a simple electrochemical sensor has been developed on GQDs. The developed surfaces characterized by scanning electron microscope (SEM) and electrochemical impedance spectroscopy (EIS). The glassy carbon electrode (GCE) modified with GQDs was applied to the determination of ascorbic acid in food sample.

References

[1] A. A. Ensafi, M. Taei and T. Khayamian, J. Electroanal. Chem, 633 (2009) 212

[2] S. Stankovich, D.A. Dikin, G.H.B. Dommett, K.M. Kohlhaas, E.J. Zimney, E.A. Stach, R.D. Piner, S.T. Nguyen, R.S. Ruoff, Nature, 442 (2006) 282-286

[3] J. Shen, Y. Zhu, X. Yang, C. Li, Chemical Communications, 48 (2012) 3686-3699

Keywords: Ascorbic Acid; Graphene Quantum Dots; Electrochemical Sensor

SENSITIVE DETERMINATION OF L-TYROSINE BASED ON GRAPHENE OXIDE NANOMATERIAL

ASLI ATAR^{a*}, MEHMET LUTFI YOLA^b, CEREN GODE^c, NECIP ATAR^d

^aDUMLUPINAR UNIVERSITY

^bDEPARTMENT OF METALLURGICAL AND MATERIALS ENGINEERING, FACULTY OF ENGINEERING, SINOP UNIVERSITY

^cPAMUKKALE UNIVERSITY, SCHOOL OF DENIZLI VOCATIONAL TECHNOLOGY, PROGRAM OF MACHINE

^dPAMUKKALE UNIVERSITY, FACULTY OF ENGINEERING, DEPARTMENT OF CHEMICAL ENGINEERING

*asliatar84@gmail.com

Abstract:

L-tyrosine (L-Tyr) is also a kind of important amino acid and maintain nutritional balance. The lack of L-Tyr causes depression, and other psychological diseases. However an overdose of L-Tyr results in chromatid exchange [1,2]. In this study, an electrochemical sensor based on graphene oxide (GO) modified glassy carbon electrode (GCE) was presented for determination of L-Tyr [3]. The prepared surfaces and nanomaterials were characterized by transmission electron microscopy (TEM), electrochemical impedance spectroscopy (EIS) and cyclic voltammetry (CV). The electrochemical determination of L-Tyr was performed by square wave voltammetry (SWV) with GO nanocomposite (GO/GCE). The developed electrochemical sensor was also applied for the determination of L-Tyr in spiked serum sample and the linearity range of L-Tyr was 1.0×10^{-9} - 1.0×10^{-7} M with the detection limit of 1.5×10^{-10} M.

References

- [1] J.M. Silván, et al., Journal of Pharmaceutical and Biomedical Analysis, 41 1543 (2006)
- [2] Q. Xu, and S.-F. Wang, Microchimica Acta, 151 47 (2005)
- [3] M. L. Yola, et al., RSC Advances, 5 65953 (2015)

Keywords: L-Tyrosine; Electrochemistry; Graphene Oxide

A NOVEL DETERMINATION OF L-TRYPTOPHAN VIA AU@AG NANOPARTICLES ON POLYOXOMETALATE

CEREN GODE^{a*}, MEHMET LUTFI YOLA^b, NECIP ATAR^c

^aPAMUKKALE UNIVERSITY

^bDEPARTMENT OF METALLURGICAL AND MATERIALS ENGINEERING, FACULTY OF ENGINEERING, SINOP UNIVERSITY

^cPAMUKKALE UNIVERSITY, ENGINEERING FACULTY, DEPARTMENT OF CHEMICAL ENGINEERING

*cgode75@gmail.com

Abstract:

L-tryptophan (L-trp) is one of the most important amino acids which are used in the food industry as an antioxidant for several biological reactions [1]. L-trp is not synthesized in humans and other animals. Especially, core-shell nanoparticles are developed for the sensor technology [2]. Polyoxometalates (POMs) are highly redox-active material with great potential for electrochemical sensors. Due to their chemical versatility and stability, they can be utilized in catalysis, energy studies, and nano-electronics. In reduced forms, their electron and proton transfer make them act as efficient donors or acceptors [3]. In this work, a voltammetric sensor based on glassy carbon electrode (GCE) modified with gold@silver nanoparticles (Au@Ag) involved in a polyoxometalate (H₃PW₁₂O₄₀, POM) is prepared for the determination of L-trp. The preparation and characterization of core-shell nanoparticles involved in a polyoxometalate are performed. Then, the developed sensors are applied to milk samples and the linearity range of L-Trp is 1.0×10⁻¹⁰ - 1.0×10⁻⁸ M with the detection limit of 2.0×10⁻¹¹ M.

References

- [1] J.M. Silván, et al., Journal of Pharmaceutical and Biomedical Analysis, 41 1543 (2006)
- [2] M.L. Yola and N. Atar, Electrochimica Acta, 119 24 (2014)
- [3] Tanju Eren, et al., Ionics 21 2193 (2015)

Keywords: L-Tryptophan; Milk Sample; Polyoxometalate; Electrochemical Sensor

DEVELOPMENT OF NOVEL MOLECULAR IMPRINTED ELECTROCHEMICAL SENSOR BASED ON POLYOXOMETALATE/CARBON NITRIDE NANOTUBES NANOCOMPOSITE FOR DETERMINATION OF QUERCETIN

CEREN GODE^{a*}, MEHMET LUTFI YOLA^b, NECIP ATAR^c

^aPAMUKKALE UNIVERSITY

^bDEPARTMENT OF METALLURGICAL AND MATERIALS ENGINEERING, FACULTY OF ENGINEERING, SINOP UNIVERSITY

^cPAMUKKALE UNIVERSITY, ENGINEERING FACULTY, DEPARTMENT OF CHEMICAL ENGINEERING

*cgode75@gmail.com

Abstract:

Quercetin belongs to the flavonoid family that is distributed widely in fruits and vegetables. It has antiviral, anti-cancer, anti-inflammatory, anti-allergic and anti-tumor activity and antioxidant properties [1]. Carbon nitrides are a class of polymeric materials consisting mainly of carbon and nitrogen. They can be obtained from carbon materials with substitution of the carbon atoms by nitrogen [2]. Graphitic carbon nitride (g-C₃N₄) is prepared as an effective organic semiconductor catalyst. Polyoxometalates (POMs) are highly redox-active molecular components with great potential for electrochemical energy storage and sensors. Because POMs are a class of anionic metal oxides based on high-valent transition metals, the structure and reactivity of POMs is significant over a wide range [3]. In this report, a novel molecular imprinted voltammetric sensor based on glassy carbon electrode (GCE) modified with polyoxometalate (H₃PW₁₂O₄₀, POM) functionalized carbon nitride nanotubes was prepared for the determination of quercetin in orange juice. The developed molecular imprinted voltammetric sensor was characterized by using x-ray photoelectron spectroscopy (XPS) and electrochemical impedance spectroscopy (EIS). Quercetin imprinted GCE was prepared via electropolymerization process of 100 mM phenol as monomer in the presence of phosphate buffer solution (pH 6.0) containing 25 mM quercetin. The linearity range and the detection limit of the method were calculated as 1.0×10⁻¹¹ - 1.0×10⁻⁹ M and 1.0×10⁻¹² M, respectively.

References

- [1] V.S. Neergheen, M.A. Soobrattee, T. Bahorun, O.I. Aruoma, J. Plant Physiol. 163 (2006) 787.
- [2] Hu, M., Wang, Y., Xiong Z., Bi, D., Zhang, Y., Xu, Y., "Iodine-Sensitized Degradation of 2,4,6-Trichlorophenol under Visible Light", Environmental Science & Technology, 46, 9005-9011, 2012
- [3] Song, Y.-F., Tsunashima, R., "Recent advances on polyoxometalate-based molecular and composite materials", Chemical Society Reviews, 41, 7384-7402, 2012

Keywords: Quercetin; Carbon Nitride Nanotubes; Polyoxometalate; Electrochemical Sensor

DEVELOPMENT OF A TEST DEVICE CAPABLE OF PERFORMING STATIC LOADING TESTS OF CARPETS AUTOMATICALLY

HALIL IBRAHIM CELIK^{a*}, HATICE KUBRA KAYNAK^a, BURAK SAHIN^b

^aTEXTILE ENGINEERING, FACULTY OF ENGINEERING, GAZIANTEP UNIVERSITY

^bMECHANICAL ENGINEERING, FACULTY OF ENGINEERING, GAZIANTEP UNIVERSITY

*hcelik@gantep.edu.tr

Abstract:

The appearance of the cut-pile carpets are deteriorated due to foot traffic and long time heavy loadings. The most important factor affecting appearance of carpets is thickness loss after static loads due to being under furniture for long time. There are two standards; "BS 4939:1987, ISO 3416-1986 Method for determination of thickness loss of textile floor coverings after prolonged heavy static loading" and "ISO 3415:1986 Textile floor coverings - Determination of thickness loss after brief, moderate static loading" for testing carpet thickness loss performance after static loading. In today's technology, the static loading is applied manually to the carpet sample by means of a moment arm. Two loading masses (700 kPa for prolonged-heavy static loading and 220 kPa for brief-moderate static loading) must be prepared and the loading time required in related standards is followed by the user. On the other hand, for both standards it is required that the static loading must be applied on at least five specimens of a sample. Since static loading duration is 24 hours for prolonged-heavy static loading and 2 hours for brief-moderate static loading for each specimen and only one specimen can be applied on the moment arm, the test duration for one carpet sample take very long time. This time consuming due to tests' duration cause to serious problems in terms of carpet manufacturers whereas long time is needed to take test results for academic studies. In the scope of this study, a carpet static loading test instrument which is capable of performing static loading on five different specimens at same time according to both of two standards; BS 4939:1987 and ISO 3415:1986 will to be developed. Thus, static loading tests can be performed automatically an in shorter time durations.

Keywords: Carpet, Pro-Long Heavy Static Loading, Brief Moderate Static Loading, Automation, Carpet Static Loading Test Device

CONJUGATION OF ALDEHYDE DEXTRAN WITH HORSERADISH PEROXIDASE AND DECOLORIZATION OF SYNTHETIC DYE WASTEWATER

MITHAT CELEBI^{a*}, ZAFER OMER OZDEMIR^b

^aPOLYMER ENGINEERING, YALOVA UNIVERSITY

^bENERGY SYSTEMS ENGINEERING, KIRKLARELI UNIVERSITY

*ozdemirz@gmail.com

Abstract:

This work is aim to conjugation reaction of Horseradish Peroxidase with aldehyde dextran and enzymatic decolorization of Reactive Blue 19 dye using the conjugate. Horseradish Peroxidase-aldehyde dextran covalent conjugate was synthesized in laboratory conditions. Aldehyde dextran was obtained from oxidation of dextran. With the conjugation, Horseradish Peroxidase enzyme is immobilized on aldehyde dextran and the effect time of the enzyme is maximized. The conjugate was characterized with Gel Permeation Chromatography. Enzymatic decolorization of Reactive Blue 19 dye carried out with Horseradish Peroxidase and the conjugate at pH:5.5 and different temperatures (21 °C, 33 °C, 37 °C, 43 °C, and 47 °C).

Keywords: Aldehyde Dextran, Conjugation, Decolorization, Horseradish Peroxidase

LOGICAL KEY HIERARCHY IMPLEMENTATION IN CLOUD COMPUTING

HUSEYIN BODUR^{a*}, RESUL KARA^a

^aDUZCE UNIVERSITY

*huseyinbodur@duzce.edu.tr

Abstract:

Cloud computing is a system that keeps the system, software or data contained in remote data centers and enables them to access at a desired time and on a desired device over the internet. Various schemes have been developed to transmit the data to multiple users by a single sender. The most commonly used among these schemes is Logical Key Hierarchy (LKH). In this study, the problems that can be encountered during the implementation of LKH structure in a cloud system are presented.

Keywords: Cloud Computing, Logical Key Hierarchy, Broadcasting

THE EFFECT OF DIFFERENT AFTERTREATMENTS ON COLORATION OF WOOL FABRICS WITH HAZELNUT SHELLS

ZEHRA GOZUTOK^a, M. IBRAHIM BAHTIYARI^{a*}

^aERCIYES UNIVERSITY, TEXTILE ENGINEERING DEPARTMENT

bahtiyari@erciyes.edu.tr

Abstract:

Dyeing of textile materials with natural sources is a well-known process and it has used since pre-historic times. Today natural dyeing has started to attract attention because it is believed that natural dye sources are less harmful to humans and environment. In natural dyeing different natural sources like herbal sources can be used. In this study hazelnut shells were used for the coloration of the wool fabrics. By this way it was planned to show the usability of a herbal waste in a dyeing process. The dyeing processes were conducted with different mordanting agents and also not mordanted but dyed samples were evaluated too. After dyeing, different chemical processes containing hydrogen peroxide, sodium dithionite, sodium carbonate or tartaric acid were managed. Then the dyed samples were analyzed in terms of CIE L*a*b* color values, color changes and color efficiencies. It was observed that hazelnut shells can be used for the coloration of the wool fabrics and depending on the mordanting agent and aftertreatments different colors can be observed.

Keywords: Hazelnut Shell, Mordant, Natural Dye, Aftertreatment, Wool

EXTRUSION AND COMPARATIVE INVESTIGATION OF PRISTINE AND NANOPARTICLE ADDED POLYPROPYLENE FILAMENTS FOR PIEZOELECTRIC SMART TEXTILE APPLICATIONS

DERMAN VATANSEVER BAYRAMOL^{a*}

^aNAMIK KEMAL UNIVERSITY

*dvbayramol@nku.edu.tr

Abstract:

Polymer-based piezoelectric materials are good candidates for smart e-textile applications. However, there is a limited number of polymers which can exhibit piezoelectric effect. Researchers have been working on both finding new polymers/copolymers and increasing the piezoelectric behaviour of existing polymers. This presentation will focus on nanoparticle addition into isotactic polypropylene (PP). Three sets of PP filaments were extruded via a laboratory scale single-screw melt extruder. Pristine PP, 1wt% Multiwalled Carbon Nanotube (MWCNT) added PP and 1wt% Tourmaline (TM) added PP filaments have been successfully produced. Masterbatch preparation, filament extrusion and sample preparation processes have been studied. Masterbatches were prepared via a ThermoFisher Scientific Prism EuroLab16 twin-screw compounder. Filament extrusion and sample preparation parameters were kept the same for each set of filament. Filaments were subjected to a high voltage (15kV) during the filament formation in the drawing area at an elevated temperature. Mechanical and thermal characteristics of the produced piezoelectric filaments have been comparatively investigated. The evaluation results of peak-to-peak voltage output of produced filaments upon an applied mechanical stimulus have been reported. A comparative investigation has been done for the produced filaments and fiber composite samples. The results showed that both MWCNT and TM added composite PP filaments generated higher peak voltages under an applied constant impact as compared to pristine PP filaments. The highest peak voltage output was observed on 1wt% TM added PP filament while the peak voltage output of 1wt% MWCNT added PP filaments were in between the TM added PP and pristine PP filaments. This experimental study reveals that appropriate nanoparticle addition can contribute further the voltage generation of the polymeric piezoelectric materials. These produced smart filaments can easily be integrated into textile structure for smart textile applications.

Keywords: Piezoelectric, Filament Extrusion, Voltage Generation, Smart Textiles

INVESTIGATION OF JET-STRIP AND PRODUCTION CYLINDER SURFACES USED IN THE PRODUCTION OF NONWOVEN FABRICS IN CROSS-LAID LINE WITH HYDRO-ENTANGLEMENT TECHNOLOGY

PELIN GURKAN UNAL^{a*}

^aNAMIK KEMAL UNIVERSITY, CORLU ENGINEERING FACULTY, TEXTILE ENGINEERING DEPARTMENT

*pelingurkan@gmail.com

Abstract:

In this study, 100% PES nonwoven fabric production was made by changing the machine settings such as using flat patterned cylinders and micro porous shell (MPS) cylinders. The tensile strength, elongation at break and water absorbance values of the produced fabrics were measured. On the machine, the power of the pump and the cycle of the pump were observed. As a result of the measurements made, increase in the fabric strengths, decrease in the water absorption values, the pump cycle, and the pump power consumption were observed. As a result of these tests, a considerable energy saving has been achieved. In other experiments, different jet-stripes and different pressures have been tried in the production of nonwoven fabrics, which had different patterns and were made of different fibres with different ratios. On the fabrics, tensile strength, elongation at break, water absorption values were measured. As a result of the measurements, it was seen that the fabric strength values were increased and the water absorption values were changed based on the fibre blend ratios. These results mean that higher strength values of nonwoven fabrics can be obtained with using less energy; in other words remarkable results have been obtained in terms of nonwoven fabric production.

Keywords: Nonwoven Fabric, PES, MPS Cylinder, Energy Saving, Hydro-Entanglement, Cross Laid Line.

PRODUCTION OF CP-TI REINFORCED A356 ALUMINUM COMPOSITE BY VACUUM-ASSISTED INVESTMENT CASTING

RIDVAN GECU^{a*}, AHMET KARAASLAN^a

^aYILDIZ TECHNICAL UNIVERSITY

*ridvangecu@gmail.com

Abstract:

This study aims to manufacture aluminum based metal-metal composite (MMC) reinforced with sawdusts which provide strengthening of matrix alloy in an environment-friendly way. Commercially pure titanium (CP-Ti) was used as a reinforcement and A356 aluminum alloy was chosen as a matrix material. CP-Ti sawdusts were compressed in an attempt to obtain porous monoblock preform which was infiltrated by A356 melt under vacuum atmosphere. Plaster mould investment casting technique was performed in order to keep cooling rate as low as possible. Casting operation was carried out at varied temperatures from 700 to 790°C. The effect of pouring temperature on interface bonding performance between CP-Ti and A356 alloy was investigated. Light optical microscopy and energy-dispersive X-ray spectroscopy (EDS) were conducted for microstructural analysis and characterization of interfacial region.

Keywords: Titanium, Aluminum, Composite, Investment Casting

A MATHEMATICAL PROGRAMMING MODEL FOR MULTI-OBJECTIVE OPTIMIZATION IN FLEXIBLE MANUFACTURING CELLS*

EMINE BOZOKLAR^{a*}, EBRU YILMAZ^b

^aDEPARTMENT OF INDUSTRIAL ENGINEERING, FACULTY OF ENGINEERING, TOROS UNIVERSITY, 33140, MERSIN, TURKEY.

^bDEPARTMENT OF INDUSTRIAL ENGINEERING, FACULTY OF ENGINEERING AND ARCHITECTURE, CUKUROVA UNIVERSITY, 01330, ADANA, TURKEY.

*eminebozoklar@gmail.com

Abstract:

Flexible manufacturing systems have a chance of responding quickly to changing customer requests. Because the systems are developing technological and highly automated manufacturing systems. In this study, a mathematical programming model that considers a weighted approach to minimize the total inter cell and intra cell part movements, total machine-system workload unbalance, total labor-system workload unbalance, and the total number of tools on all machines in cells according to optimum alternative routes of parts, is developed. The proposed mathematical programming model is formulated as a mixed integer linear programming. First, an illustrative example problem and then related sensitivity analysis are performed to show how to carry out the proposed model using LINGO optimization software. In this study, the objective function elements that mentioned above are optimized according to the optimal alternative routings selected for all parts due to the proposed mathematical model.

*: This study is from currently continuing MSc. Thesis.

Keywords: Flexible Manufacturing Systems, Mathematical Programming Model, Alternative Routing Flexibility.

DETERMINATION OF AIR PERMEABILITY PROPERTY OF AIR-LAID NONWOVEN FABRICS USING REGRESSION ANALYSES

HALIL IBRAHIM CELIK^{a*}

^aTEXTILE ENGINEERING, FACULTY OF ENGINEERING, GAZIANTEP UNIVERSITY

*hcelik@gantep.edu.tr

Abstract:

Nonwoven fabrics are defined as textile products which are produced as textile sheets from staple or filament fibers and entangled by mechanical, chemical, thermal processes. Products from nonwoven fabrics are widely used in application areas such as hygiene, medical, agriculture, civil, home textile, automotive, filtration, ready-made production, food packaging. With wide variety of application areas and production techniques, nonwoven fabric production rate is increased day by day in Turkey, and the production is carried out in Gaziantep, Istanbul and Corlu, predominantly. Airlaid nonwoven fabrics are generally used for hygienic care products such as diaper, adult nappy and sanitary napkins. Air permeability is one of the foremost properties that affect the usage performance of hygienic care products. The structural properties of airlaid nonwoven fabrics; thickness, weight, fiber type and the pore size influence air permeability performance with a wide range. Among these properties, pore size is the determinant parameter for air permeability property. Since this type of fabrics have thin structure, determining the pore size properties by using image processing techniques seems possible. In this study, 17 different airlaid nonwoven fabric samples are produced. The pore sizes of these samples are determined by digital image processing methods. Pore sizes of the samples are calculated as the proportion of covered area of the fabric to the total area. In order to get a reliable data, five image frames are acquired from different regions and analyzed. Air permeability of the samples is tested by digital air permeability test device. Then regression analyses were applied to the experimental results using SPSS 21.0 package program. Finally regression equation was obtained for prediction of air permeability by using thickness, weight, fiber type and the pore size parameters, before production.

Keywords: Airlaid Nonwovens, Air Permeability, Pore Size, Image Processing, Regression Analysis

PEROXIDASE-LIKE ACTIVITY OF APOFERRITIN PAIRED SILVER CLUSTERS AND ITS BIOMEMORY APPLICATIONS

SUKRIYE NIHAN KARUK ELMAS^{a*}, REMZIYE GUZEL^b, ARZU ERSOZ^c, RIDVAN SAY^c

^aKARAMANOGLU MEHMETBEY UNIVERSITY

^bDICLE UNIVERSITY

^cANADOLU UNIVERSITY

^dANADOLU UNIVERSITY

*snihankaruk@gmail.com

Abstract:

Ferritin, an iron storage and detoxification globular protein, is a nanoscale naturally. Ferritin composed of 24 homologous polypeptide subunits of the heavy chain (H-ferritin) and light chain (L-ferritin) with an external diameter of 12 nm and an 8 nm diameter cavity. Horse radish peroxidase (HRP) is a metalloenzyme, catalyzes the oxidation by hydrogen peroxide. Peroxidase activities of some nanoenzymes have been prepared such as ceria NPs, carbon NPs and Pt NPs. Bionanomaterials which have multi faces and functionalities (Janus) have synthesized using apoferritin biomolecules embedding of metal atoms into lattice of this protein. These bionanostructures have obtained using photosensitive amino acid-monomers linkage method (ANADOLUCA). In this study, the synthesis of nanoapoferritins has prepared in the presence of bis (2-2'-bipyridil) MATyr-MATyr-rutenyum (II) photosensitive monomers by microemulsion. Then, silver atoms have organised into lattices of apoferritin nanostructures and these multi functional structures were have characterised by transmission electron microscopy (TEM). Michaelis-Menten kinetics of Janus model bionanomaterials have proved with 3,3',5,5'-tetramethylbenzidine (TMB). The effect of pH, temperature and substrate concentrations on the activity of these bionanomaterials have analyzed. Using cyclic voltammetry (CV) and chronoamperometry (CA) the memory function of the fabricated biodevice was validate

Keywords: Apoferritin, Biomemory, Bionanomaterials, Peroxidase

PLAY STREET: THE FUTURE OF RESIDENTIAL STREETS

NERIMAN KARA^{a*}, ASLI SUNGUR ERGENOGLU^a

^aYILDIZ TECHNICAL UNIVERSITY

*asungur@gmail.com

Abstract:

Roaming freely and playing on the street and at the doorstep of the house, have a remarkable place in today's adults' childhood memories. Streets are vital for cities and for children's development, with the variety of playing opportunities and irreplaceable gradual experience of urban environment. Unfortunately, today's children are detached from the street, due to adult's fear of crime, security, alienation and dominance of traffic. This situation creates inactive children under the threat of immune system diseases, obesity and lack of social skills.

Many parents in cities prefer to live in gated communities, at least to meet the outdoor space necessity. This situation decreases the life-span period of the houses in urban areas and damages the sense of belonging and urban sustainability.

In Turkey, as in many parts of the World, local authorities who are aware of child's right to play, define streets under the name of "Child's Street" or "Play Street" in order to encourage children to play out. Even under different child oriented local management movements, this street type takes possession over "standard" streets. "Play Street"s are rapidly spreading and has many impacts on residential community and urban environment.

This study defines and compares street play environments, describing variety of types, including temporary traffic closure, permanent street arrangements, housing design impacts and urban design at neighborhood scale within the context of space for children's play.

As a conclusion, the benefits of streets where children can safely spend time and learn to live together with all age groups and all parts of the community as a micro-urban experience are stated together with the challenges to reach the "ideal" play street and its probable negative and positive effects on the urban environment.

Keywords: Social Innovation, Play Street, Inclusion, Children's Environment, Urban Space

MICROSTRUCTURAL ASPECTS OF NICKEL-BASED SURFACING DEPOSITED BY GAS METAL ARC WELDING (GMAW)

NURSEN SAKLAKOGLU^{a*}, SARPER DOGAN^a, SIMGE GENCALP IRIZALP^a, IBRAHIM ETEM SAKLAKOGLU^b, selCuk demirok^c

^aCELAL BAYAR UNIVERSITY

^bEGE UNIVERSITY

^cEGEMET FORGE METAL INDUSTRY AND TRADE LIMITED COMPANY

*nursen.saklakoglu@cbu.edu.tr

Abstract:

Nickel-based alloy coating was deposited on AISI 1.2714 tool steel substrate using by gas metal arc welding (GMAW). The deposit was characterized by hardness measurements, microstructural examination and EDS / XRD analyses. It was investigated the influence of mixing the base metal and a filler metal and the influence of microstructural evolution. There were no cracks or other defects observed in the hardfacing coating. The microstructure of the hardfacing deposit predominantly consisted of the γ -Ni phase and the interdendritic eutectic mixture. These studies also revealed the presence of niobium-rich carbides. Hardness testing revealed that the average hardness of the hardfacing was lower than that of substrate.

Keywords: Hardfacing, Ni-Based Alloy, Microhardness, Microstructure

COMPARATIVE ANALYSIS OF WEB APPLICATION SECURITY SCANNERS

MUHAMMED ALI KOSAN^{a*}, HACER KARACAN^b

^aCOMPUTER SCIENCE, INSTITUTE OF INFORMATICS, GAZI UNIVERSITY

^bCOMPUTER ENGINEERING, FACULTY OF ENGINEERING, GAZI UNIVERSITY

*ceo.muhammed@gmail.com

Abstract:

The websites that are used for social activities make our daily life easier but we are likely to be hurt by them because of their unprevented security risks. In particular, most web application owners do not have information about the security requirements of web applications. For this reason, many tools have been developed for web application developers, security experts and web site owners to ensure the security of their websites. In this study, functional and behavioral analysis of W3AF, Paros Proxy, Grabber, Arachni Scanner, Skipfish and Vega web application security scanners is performed for scanning their security vulnerabilities such as SQL Injection, Cross Site Scripting, etc. The results are presented to show the effectiveness level of the web application development processes that include the security analysis with current tools. In addition, the strengths and weaknesses of these applications in different cases are reported. Certain questions about which features that a good web application security scanner should include have been tried to be answered by unifying the complementary features of the missing aspects of these tools and their good aspects.

Keywords: Website Security, Vulnerability Scanners, Website Vulnerabilities

LOOP BASED COLUMN-SWITCHING LC×LC SYSTEM COUPLE WITH EVAPORATIVE LIGHT SCATTERING DETECTOR FOR THE CHARACTERIZATION OF TRIGLYCERIDES IN REFINED COMMERCIAL EDIBLE OILS

FATMA NUR ARSLAN^{a*}, HUSEYIN KARA^b

^aDEPARTMENT OF CHEMISTRY, FACULTY OF SCIENCE, UNIVERSITY OF KARAMANOGLU MEHMETBEY

^bDEPARTMENT OF CHEMISTRY, FACULTY OF SCIENCE, UNIVERSITY OF SELCUK

*arslanfatmanur@gmail.com

Abstract:

Two-dimensional liquid chromatography techniques have become an attractive analytical tool for the separation of complex compounds due to its enhanced selectivity, peak capacity, and resolution compared with one-dimensional liquid chromatography. In recent times, more attention has been drawn on the application of this chromatographic technique in studies concerning lipidic compounds. Herein, we have developed a novel loop based, column-switching LC×LC system couple with evaporative light scattering detector (ELSD) for the characterization of triglycerides in refined edible oils. In accordance with this purpose, automated column-switching system was designed and set up by modifying Agilent 1200 Series HPLC in our laboratory. This system consists two G1311A model quaternary pump, a G1328B model standard auto-sampler, G1316A model thermostatted column compartment, 385 model ELSD. To provide the desired flow path of the mobile phase in the system, two G4231A model 2-position/6-port valve systems and a G4232A model 2-position/10-port valve system were adapted. To hold the lipid fractions two flexible stainless steel loops were adapted onto the 2-position/10-port valve system. Inertsil Sil 100Å (50 and 250×4.6 mm i.d. 5 µm) and ChromSpher 5 Lipids silver ion columns (250×4.6 mm id., 5 µm) were used together in system. By using this system, a complete lipid profile of the vegetable oil samples was achieved in a very short time with a single injection. The operation of system could be carried out, by using five major steps/positions sequentially applied.

In this part, we report a loop based, column-switching LC×LC-ELSD method to characterize the triglyceride isomers in commercial refined sunflower, corn, olive, palm, canola and soybean edible oils, by using positions-I, II and III respectively. Obtained results showed that triglycerides in oil samples were well separated. Therefore, the proposed loop based and column-switching LC×LC method and instrumentation provide a powerful tool for characterization of triglycerides in refined oils.

Keywords: Column-Switching, LC×LC, Triglyceride, Refined Vegetable Oil, Evaporative Light Scattering Detector

APPLICATION OF DIODE ARRAY DETECTION WITH A C30 REVERSE PHASE STATIONARY PHASE FOR THE SEPARATION AND IDENTIFICATION OF UNSATURATED FATTY ACIDS

FATMA NUR ARSLAN^{a*}

^aDEPARTMENT OF CHEMISTRY, FACULTY OF SCIENCE, UNIVERSITY OF KARAMANOGLU
MEHMETBEY

*arslanfatmanur@gmail.com

Abstract:

The aim of this study was to develop a stable and high-efficiency reverse phase HPLC method that would allow the effective separation and identification of cis/trans- isomers of long-chain fatty acids (FAs). The study also aimed to employ diode array detection (DAD) to determine chromatographic peak purity and to identify the FAs from their spectral characteristics. To achieve an excellent separation of FAs, the method parameters was optimized by using central composite design (CCD) and response surface methodology (RSM). In optimization study, we studied by using Develosil C30 column (25 cm×0.46 cm, 5 μm). Three experimental parameters were chosen as independent variables: mobile phase composition, flow rate of mobile phase and temperature of column compartment. A multivariate experimental design was used to establish a quadratic model as a functional relationship between the efficiency of chromatographic separation parameters and three independent variables. The significance of a polynomial model for predicting the optimal values of method parameters was evaluated. Three-dimensional RSM plots for the interactions between the variables were also constructed. The peak chromatographic factors were significantly affected by the %ACN content and column temperature. Regression analysis with R² values showed good agreements between the experimental results and predicted values. Thus, by performing fewer experiments, CCD and RSM provide more information along with individual as well as interactive effect of all the experimental parameters involved in this study for a satisfactory separation of FAs. Furthermore, in terms of adequacy, accuracy and significance, the proposed application of DAD with a C30 reversed phase stationary phase, appeared to be comparable to gas chromatography applications.

Keywords: Optimization, Response Surface Methodology, Central Composite Face-Centered Design, Chromatography

START UP OF ANAMMOX REACTOR AND SHORT TERM EFFECTS OF TiO₂ NANOPARTICLES ON ANAMMOX BACTERIA

AYSE OZLEM YAR^{a*}, DENIZ AKGUL^a

^aMARMARA UNIVERSITY

*ayseozlemyar@gmail.com

Abstract:

Biological nitrogen removal is widely accomplished by conventional nitrification and denitrification processes in wastewater treatment systems. Conventional nitrification and denitrification processes lead to high operation cost due to oxygen requirement and external carbon addition. Even if this process is successful, there is some serious difficulties during wastewater treatment, especially industrial wastewater treatment. In recent years, anammox (anaerobic ammonium oxidation) has been discovered as a new approach for ammonium removal. In this process, ammonium is used as electron donor and nitrite is used as electron acceptor and mainly nitrogen gas and some nitrate are produced. These systems produce less sludge compared to conventional nitrification and denitrification processes, consume less oxygen and do not require external carbon addition.

Nowadays, metallic and metal oxide nanoparticles are being used at medical and electrical industries, personal care products. Eventually, these nanoparticles are discharged to domestic wastewater treatment plants. In literature, there is no study which investigates the nanoparticle inhibition on Anammox systems.

The first objective of this study is to investigate the inhibitory effects of TiO₂ on enriched Anammox culture. In this context, short and long term inhibition levels of titanium dioxide (TiO₂) will be determined in both batch and continuous systems. The second objective of the study is the recovery of anammox process by TiO₂ nanoparticle inhibition. Both batch and continuous experiments has been performed during the study. Firstly, 0-10 mg/L TiO₂ nanoparticle concentrations used according to literature information. Concentration of TiO₂ nanoparticle increased step by step if there is no inhibition in the system. After the inhibition experiments, anammox bacteria subjected to recovery tests which consist of EDTA washing procedure. Anammox bacteria centrifuged and then they shaken with EDTA washing solution to get rid of the TiO₂ nanoparticles from the bacteria.

Keywords: Anammox, TiO₂, Inhibition, Nitrogen Removal

COMPARISON OF WELDING METHODS FOR JOINING SIMILAR AND DISSIMILAR STAINLESS STEELS

ORKUN OZSAVANER^{a*}, RIDVAN GECU^a, ALPTEKIN KISASOZ^a, AHMET KARAASLAN^a

^aYILDIZ TECHNICAL UNIVERSITY

*karaas@yildiz.edu.tr

Abstract:

The effect of welding method and additional wire on the weld quality was investigated in this study. Samples were selected as three different groups: AISI 430 / AISI 430, SAF 2205 / SAF 2205 and AISI 430 / SAF 2205. Each group was welded with tungsten inert gas (TIG), metal inert gas (MIG) and laser beam welding methods. In welding processes, additional low C-containing L-type welding wires (ER 316L for TIG, ER 308L for MIG, ER 318L and ER 316L for laser beam) were used to prevent undesirable sigma phase and chromium carbide deposition in the weld zone of post-weld stainless steels. The mechanical properties of the welded specimens were determined by hardness, tensile and impact tests at room temperature while the microstructures of the weld seam and the heat affected zones (HAZ) were observed with an optical microscope. The highest tensile strength was obtained at SAF 2205 / SAF 2205 metal pair produced by laser beam welding using ER316L wire. The most prominent grain growth was occurred in the ferritic parts of TIG and MIG welded samples. Recrystallization effect was increased grain size due to heat input in HAZ. The grain size of laser welded samples was not significantly changed because heat input in laser beam welding was lower than other welding methods.

Keywords: Welding

FINITE ELEMENT MODEL OF LUMBAR SPINE STABILIZATION WITH BONE GRAFT SUPPORTED TITANIUM MESH CAGE

HUSEYIN LEKESIZ^{a*}, SENA BAYRAKTAR^a, ILYAS DEDEGIL^a

^aBURSA TECHNICAL UNIVERSITY

*huseyin.lekesiz@btu.edu.tr

Abstract:

Clear understanding the biomechanics of spine stabilization is very important to overcome the issues related to stabilization techniques and advancing new techniques. Titanium mesh cages (TMC) are extensively utilized in stabilization with bone grafting in and out of TMC to create a better fusion between vertebrae. 41% of stabilization operations following corpectomy, a.e. removing the corpus of a vertebra due to some medical conditions, take place in lumbar area. In this study, both intact and stabilized L1-L2-L3 segment (L2 having corpectomy) are modeled with finite element method (FEM) to explain differences in stresses and deformations occurring as a result of stabilization. For TMC, a commercially available cage model with circular holes is used in FE Models. Also, TMC is supported with bone grafting in stabilization and all ligaments kept intact in stabilized model except anterior and posterior longitudinal ligaments. All material properties for bones, ligaments and cage are taken from literature. Structural integrity of cage for all possible motions; left/right bending, flexion/extension, torsion and compression are tested by comparing FE Analysis results for both intact and stabilized models. When the intact and stabilized spine is compared for all motions, stabilized spine presents close Von-Mises stress. Maximum value of Von-Mises stress value in L3 is slightly higher in stabilized model. However, this is not an undesired situation because lower stress values may weaken bones in recovery stage. Maximum displacement values are almost same for both intact and stabilized models.

Keywords: Finite Element Method, Spine Stabilization, Titanium Mesh Cage,

CONTROLLING THE BUILDING MODEL USING HIGH ORDER SLIDING MODE CONTROL OPTIMIZED BY MULTI OBJECTIVE GENETIC ALGORITHM

HASAN OMUR OZER^{a*}, YUKSEL HACIOGLU^b, NURKAN YAGIZ^b

^aPROGRAMME OF AIR CONDITIONING AND REFRIGERATION TECHNOLOGY, VOCATIONAL SCHOOL OF TECHNICAL SCIENCE, ISTANBUL UNIVERSITY

^bDEPARTMENT OF MECHANICAL ENGINEERING, FACULTY OF ENGINEERING, ISTANBUL UNIVERSITY

*omurozer@istanbul.edu.tr

Abstract:

High Order Sliding mode control (HOSMC) has been used in many mechanical systems and structural system due to its accuracy, chattering attenuate and high control performance. How-ever, choosing controller parameters for systems is still an important research area. This study presents a numerical analysis to decrease the effect of earthquake vibrations on building model having Active Tuned Mass Damper (ATMD). The system is excited by an earthquake and a linear motor is used as the control device. ATMD is installed on top floor of building model. Tuning of High Order Sliding Mode Controller (SMC) using Super Twisting Algorithm with Multi Objective Genetic Algorithm (MOGA) is designed for a three storey building model with ATMD. HOSMC parameters have been chosen by MOGA with multiple objective functions. Then, simulation results of uncontrolled and controlled model are compared. The results show that building model with HOSMC tuned by MOGA is effective to decrease the effects of vibrations.

Keywords: High Order Sliding Mode Controller, Multi-Objective Genetic Algorithm, Building Model, Active Tuned Mass Damper, Simulation.

ANDROID BASED MOBILE C# PROGRAMMING EDUCATION APPLICATION

FATIH KAYAALP^{a*}, HUSEYIN BODUR^a, SULTAN ZAVRAK^a

^aDUZCE UNIVERSITY

*huseyinbodur@duzce.edu.tr

Abstract:

Computer technology is improving day by day and software is one of the most important parts of it. Software can be called as group of special codes written for a specific purpose. Operating systems and application programs are examples of software. Software are produced by using different programming languages known as high level (C#, Java, Python languages), mid-level (C, IBM PL/S languages) or low level (Assembly language, Machine language) programming languages. Algorithm is the start point of programming. A novice programmer should learn designing algorithm at first. After designing the algorithm, it is turn to code the algorithm in a specific programming language which can be selected according to many criteria like supporting object orientation, platform independency, systems requirements and etc. As learning algorithms and programming are the basics of software world, many sources like books, tutorial videos, web sites and courses have been published in the world to teach these subjects. Programming education is so important both for improving the capabilities of programmers and creating better qualified software. Smart phones with mobile operating systems are one of the popular technologies of today. Many people using mobile phones prefer using smart phones with internet connection for the advantages of using many applications created for different purposes like instant messaging applications (WhatsApp), banking applications, games (local or internet connected) etc. As smart phones are widely used and learning computer programming is a popular trend in computer world not only for computer engineering students but also for many young people on different area, we have developed an Android based mobile C# programming education application to support novice users on training C# programming.

Keywords: Android Based Education, C# Education Application

COMPARISON OF NATO BULLETS AND 6.8 MM REMINGTON

BURAK KURSAD YILMAZ^{a*}, SELAHATTIN ALP ERKURTULMUS^a

^aKARADENIZ TECHNICAL UNIVERSITY

*burakkursadyilmaz@gmail.com

Abstract:

In this study, it is aimed to compare the Nato ammunition at medium and heavy level and to observe the field and technical analysis of Remington ammunition as a Nato ammunition. Modeling of the ammunitions used in the project was done with the help of Solidworks Packet Program and static and dynamic analysis with Autodesk Inventor program. After the modeling was done, the method to be used for the field was determined and the materials required for the test were selected and provided. After these operations, the test phase was passed. AW ACCURACY - MC MILAN - KANNAS - G-3 weapons and steel hood, steel vest, compacted snow, soil, wood, mud, dry pine and steel plate. Thus, the drilling powers of ammunition have been tested and observed.

Keywords: Weapons, Ammunition, Nato, Solidworks, Autodesk Inventor

A MODAL ANALYSIS OF TLP WITH TENDONS

SELAHATTIN ALP ERKURTULMUS^{a*}, EMRE PESMAN^a

^aNAVAL ARCHITECTURE AND MARINE MACHINE ENGINEERING, SURMENE FACULTY OF MARINE SCIENCES, KARADENIZ TECHNICAL UNIVERSITY

*alp.erkurtulmus@gmail.com

Abstract:

The offshore industry requires continued development of new Technologies in order to produce oil in regions, which are inaccessible to exploit with the existing technologies. Tension leg platforms (TLPs) have been used exclusively as production and drilling platforms. TLPs consist of columns and pontoons. The unique feature is the mooring system, which consist of vertical tendons (called “tethers”) which restrain the heave motion. Compliant offshore TLPs are essentially meant for deep oil/gas exploration and are usually constructed on the seashore and then towed down to the particular location for anchorage. They are connected to the sea bed by means of pretension cables. The increased use of TLPs in deep waters and necessity of reduction of usually high value of pretension make the effect of variable tension in the tether dynamics more significant. This work presents the modal analysis of tethers and TLPs considering the linearly varying tension along the tether length. For the analysis, the TLP which name is SNORRE-A is modelled for environmental conditions. ANSYS-Mechanical APDL program is used for modelling and analysis. The mod shapes and natural frequencies of TLP is obtained and the results are discussed.

Keywords: Ansys, Offshore, Tlp, Tendons

DESIGN AND ANALYSIS OF LIGHT QUADCOPTER BODY

SELAHATTIN ALP ERKURTULMUS^{a*}, BURAK KURSAD YILMAZ^b, HARUN KORKMAZ^b

^aNAVAL ARCHITECTURE AND MARINE MACHINES ENGINEERING, SURMENE FACULTY OF
MARINE SCIENCES, KARADENIZ TECHNICAL UNIVERSITY

^bMECHANICAL ENGINEERING, ENGINEERING FACULTY, KARADENIZ TECHNICAL UNIVERSITY

*alp.erkurtulmus@gmail.com

Abstract:

In this study, it was aimed to draft the body design and analyse the quadcopters, which is a four-motor multicopter, from composite material. The body design of the quadcopters produced in this project was done using SolidWorks program and only static analyses were carried on Ansys Workbench. The method manufacturing product was determined after the design was made and then the composite materials required were selected and supplied. After these processes, the manufacturing phase was started. The prepreg, which is resin-impregnated fibre was glued to the polyurethane foam (Airex T92.80) with epoxy, after being treated in the hot press and pressed again, so that the designed body was produced from the sandwich panel.

Keywords: Ansys Workbench, Composite Materials, Multicopter, , Solidworks, Quadcopter

GREEN AND SUSTAINABLE APPROACH FOR DESIGN OF ANTIBACTERIAL WOUND CARE DRESSINGS

HUSEYIN AVCI^a, HAZAL GERGEROGLU^a, ESRA AKKULAK^a, YAGMUR TOPTAS^a, Ahmet Cabuk^a

^aESKISEHIR OSMANGAZI UNIVERSITY

havciesogu@gmail.com

Abstract:

One of the most important challenges for antibacterial wound care dressings is their production methods and adverse effects of toxicants on human and living organisms while using and disposing them. Wound dressing with a global market size of 13 billion dollars in 2008, is one of the most developed areas in medicine sector. Approximately 200,000 burn incidents are happening in Turkey every year, of which one of the thousandth is mortal. In addition, increasing earth population and the environmental pollution, much focus has been placed in the recent years to find new health and hygiene related products with the minimum adverse effect on the environment. To address these growing concerns for the mankind and the environment, the development of new antibacterial wound care agents has become one of the most important research areas to combat some pathogens. Assessing the risks associated with the use of synthetic and metal-based antimicrobial agents in commercial products requires a detailed understanding of the materials mobility, biocompatibility, and biodegradability in a physiological environment. Unfortunately, there is not enough research to observe the adverse effects of these active agents and also what they produced, used and released or left to the environment in an unconscious manner in the most of the time. The additive toxicity also becomes an important issue when the compound is actually released to the environment.

Here, we focus on the use of domestic medicinal plants extraction which are cultivated in Turkey, as an effective antibacterial agent for the purpose of open wound treatment by incorporating with nanofibers. We further investigated the performance and morphology of the nanofiber webs as well as characterized their structural properties.

Keywords: Antibacterial, Wound Care, Plant Extract, Nanofiber, Eco-Friendly

CARBON NITRIDE NANOTUBES DECORATED WITH GRAPHENE QUANTUM DOTS AS MICROBIAL FUEL-CELL ELECTRODE

ALIME YILMAZ^{a*}, MEHMET LUTFI YOLA^b, NECIP ATAR^a

^aPAMUKKALE UNIVERSITY

^bSINOP UNIVERSITY

*alimey@pau.edu.tr

Abstract:

In this study, carbon nitride nanotubes (C₃N₄ NTs) decorated with graphene quantum dots (GQDs) modified glassy carbon electrode (GCE) was developed for microbial fuel-cell electrode. The unique C₃N₄ NTs@GQDs nanohybrid was synthesized by hydrothermal treatment. The unique C₃N₄ NTs@GQDs nanohybrid was characterized by spectroscopic and electrochemical techniques. C₃N₄ NTs@GQDs enabled the catalytic reduction of oxygen at the cathode and the electron transfer to the anode. C₃N₄ NTs@GQDs electrode showed high current density and power density.

Keywords: Microbial Fuel Cell; Carbon Nitride Nanotubes; Graphene Quantum Dots

DEVELOPMENT OF MOLECULAR IMPRINTED POLYMER BASED QCM NANOSENSOR FOR DETERMINATION OF AMOXICILLIN

ALIME YILMAZ^{a*}, MEHMET LUTFI YOLA^b, NECIP ATAR^a

^aPAMUKKALE UNIVERSITY

^bSINOP UNIVERSITY

*alimey@pau.edu.tr

Abstract:

In this report, we developed quartz crystal microbalance (QCM) sensor for the sensitive determination of amoxicillin (AMOX) in egg samples. Firstly, the modification of gold surface of QCM chip was performed by allyl mercaptane. Then, AMOX-imprinted poly(2-hydroxyethyl methacrylate–methacryloylamidoglutamic acid) [p(HEMAGA)] nanofilm was generated on the allyl mercaptane modified gold surface. The unmodified and imprinted surfaces were characterized by fourier transform infrared (FTIR) spectroscopy AND ellipsometry. The developed method was validated according to the ICH guideline. The linearity range and the detection limit were obtained as 0.1 – 1.0 ng/mL and 0.030 ng/mL, respectively. The developed imprinted nanosensor was applied to the egg samples for the determination of AMOX.

Keywords: QCM; Molecular Imprinting; Validation; Nanosensor

THE EFFECT OF HYDRAULIC RADIUS ON AERATION PERFORMANCE IN HIGH-HEAD GATED CONDUITS

ALP BUGRA AYDIN^{a*}, MUALLA OZTURK^a, FAHRI OZKAN^a, M. CIHAT TUNA^a

^aFIRAT UNIVERSITY

*alpbugraaydin@gmail.com

Abstract:

The water is indispensable to balance the ecology and functionality of creatures. Hence, water has been used for drinking water supply, irrigation, and various industrial purposes. In the historical process, we are confronted with the "global water crisis" due to the population increase, urbanization, increasing water consumption with industrialization, environmental pollution caused by mixing of waste water to the nature, inadequacy of infrastructure and excessive irrigation in agriculture. The effectively use of freshwater bodies has crucial importance due the limited amount of freshwater sources. Thus, it is vital to improve the properties of polluted freshwater to reuse. The dissolved oxygen concentration is a crucial indicator for continuation of live on the water. There are many researches to keep concentration of dissolved oxygen in the limit level. The aim of these researches is the aeration of water in the most efficient way. Thanks to the aeration, very long distance and time of oxygen transfer in the natural environment will be provided in a short distance and time. In this direction, different flow systems with pressure and free surface for aeration have been widely used in recent years. The main purpose of these systems is to increase the amount of air in contact with water to transfer of oxygen in the air. In this study, the variation of air demand ratio with hydraulic radius in high-head gated conduits was investigated differently from the previous researches. The results of experiments show that, air suction performance decreases with increasing hydraulic radius in small gate openings, and hydraulic radius does not have a significant effect on air suction performance in large gate openings.

Keywords: Aeration Efficiency, Air Entrainment, Hyrdaulic Radius, High-Head Flow, Oxygen Transfer

VARIATION OF MICROSTRUCTURE AND MECHANICAL PROPERTIES OF 2205 DUPLEX STAINLESS STEEL FOR DIFFERENT SOLUTION TREATMENT

ALPTEKIN KISASOZ^{a*}, AHMET KARAASLAN^a

^aYILDIZ TECHNICAL UNIVERSITY

*akisasoz@gmail.com

Abstract:

Duplex stainless steels (DSSs) have austenite and ferrite phases in equal amount and DSSs have both higher mechanical properties and corrosion resistance owing to duplex microstructure. In this study, microstructural and mechanical properties of AISI 2205 alloy after solution treatment at 1150 C with various time are investigated. After the solution treatment, mechanical and microstructural properties of DSSs can be alter, especially changes in austenite-ferrite phase ratio. Mechanical properties changes in austenite and ferrite phases are determined with Vickers hardness test. Moreover, microstructural characterization is carried out by optical microscopy and image analysis.

Keywords: Duplex Stainless Steel, Solution Treatment, Microstructural Properties

THE IMPORTANCE OF SYSTEM SIMULATION SOFTWARES AT INDUSTRIAL ENGINEERING EDUCATION: A CASE STUDY FROM TURKEY

IBRAHIM SABUNCU^{a*}

^aYALOVA UNIVERSITY

*isabuncu@yaloa.edu.tr

Abstract:

Simulation is the general name of the methods and applications used to imitate real systems. System simulation is mathematical modeling of real systems. System simulation is one of the most preferred method by the private sector and one of the most important methods of industrial engineering. It is usually done using computer and special simulation software.

The purpose of this study is to investigate the content of system simulation undergraduate courses in industrial engineering departments as well as the share of the simulation software in the undergraduate education and the given importance. For this purpose, all private universities that has industrial engineering department in Istanbul the city with the most universities in Turkey, were selected. The detected 27 universities were sent an email to heads of industrial engineering departments to ask questions about the contents of their system simulation undergraduate courses. The given answers were examined and, when it is necessary, discussed with other academicians via email. By examining the correspondences, the content of the system simulation training of each university is categorized by the theoretical, software, application, and software name dimensions.

Only 9 universities were able to provide the requested information. 4 of these 9 universities' industrial engineering departments are mainly teaching simulation software. The rest make up theoretical lecture on weight. However, in all of them, a system simulation software is mentioned. The simulation software described and used in the lessons are the Arena at six of them, Simio at two and Promodel at one of them.

As a result, it is seen that training of system simulation software is an important part of the undergraduate education of industrial engineering departments at the private universities in Istanbul. In the further studies, the research population will be extended throughout Turkey.

Keywords: Simulation Software, Industrial Engineering, System Simulation, Undergraduate

ECOLOGICAL APPROACHES IN TEXTILE SECTOR: THE EFFECT OF R-PET BLEND RATIO ON RING SPUN YARN TENACITY

ESIN SARIOGLU^{a*}

^aGAZIANTEP UNIVERSITY

*sarioglu@gantep.edu.tr

Abstract:

Nowadays, climate change has serious problem for all over the world. To overcome this problem some attempts have been performed by governments to minimize waste generation. Polyethylene terephthalate (PET) bottles are produced from raw petrochemical products and waste after use has not affect environment directly. On the other hand, the increasing volume of PET bottle waste causes economical and environmental problems unless to be recycled. Recycling of PET bottles leads to decrease waste problem and use of raw petrochemical products and energy. In addition, this process does not reducing cost but it is essential to conserve ecological balance. PET bottles can be easily separated from other wastes, some additional processes are needed ie. breaking, washing, drying to obtain PET flakes. r-PET fibers to be used in textile industry are produced by melt spinning system from PET flakes. This recycled product can easily be adapted to textile product production instead of virgin PET. This study aims to determine the effect of using r-PET fiber with different blend ratio on ring spun yarn tenacity and elongation. At this respect, r-PET fiber was blended with cotton fiber at 100%, 70/30%, 50/50%, 30/70% and 0% ratios. Yarn samples were manufactured by ring spinning system and all production parameters were kept constant to evaluate the effect of blend ratio variable. It was determined that r-PET fiber ratio has significance effect on tenacity and elongation.

Keywords: R-PET, Recycling, Ring Spinning, Tenacity, Elongation

A NOVEL COLORIMETRIC AND FLUORESCENT CHEMOSENSOR FOR PH IN ORGANO-AQUEOUS MEDIUM

SUKRIYE NIHAN KARUK ELMAS^{a*}, IBRAHIM YILMAZ^a, FURKAN OZEN^b, KENAN KORAN^b,
AHMET ORHAN GORGULU^b

^aKARAMANOGLU MEHMETBEY UNIVERSITY

^bFIRAT UNIVERSITY

*snihankaruk@gmail.com

Abstract:

The detection of pH is crucial roles in the health science, industrial and agricultural process. Intracellular pH plays a significant role in modulation many metabolic process including cell growth, proliferation, apoptosis, and ion transport systems. Abnormal pH values are caused many serious human disease such as Alzheimer's disease and cancers. Therefore, the determination of irregular pH changes is very critical for diagnosis of diseases. Many methods for the detection of intracellular pH such as electrochemistry, absorbance and fluorescence spectroscopy. Among the process, fluorescent studies are suitable due to their low cost, real time detection, high selectivity and sensitivity.

In this study, a 3-(3,5-bis(trifluoromethyl)-6,7-dihydroxy-2H-chromen-2-one was synthesized and characterized. The behavior of receptor toward various cations were studied with using UV-Vis and fluorescence spectroscopy. The receptor displayed that a naked-eye detectable color change 257, 400nm and turn on fluorescent reponse in alkaline pH in comprison with the free chemosensor.

Keywords: Coumarin, Ph, Fluorescent Chemosensor

NEW APPROACHES TO THE PEPTID SYNTHESIS & CHARACTERIZATION

ZAFER OMER OZDEMIR^{a*}, HALIL MUTLUBAS^a

^aKIRKLARELI UNIVERSITY

*ozdemirz@gmail.com

Abstract:

The continuous technological developments increase the variety of the studies in the scientific field. Further, these improvements keep on to add knowledge and new explanation about to definitions, physiological functions, structures and sources of known and unknown many substances. Proteins and peptides play a central role in numerous physiological and biological processes in living organisms. Peptides are synthesized for a variety of applications and research interests. For peptide synthesis applications; Library synthesis sequence, peptide synthesis for biological or separation assays, and separation of reaction conditions. One of the peptide synthesis methods is Solid Phase Peptide Synthesis (SPSS). Therefore in this work, it is take aimed to review new methods for synthesis and characterization of peptides and developments of peptide resins.

Keywords: Characterization, Peptide Synthesis, Resin, Solid Phase Peptide Synthesis

DETERMINING DISPERSING MEDIA IN THE INVERSE SUSPENSION POLYMERIZATION OF POLYACRYLIC ACID

OZGUR CEYLAN^a, M. ARIF KAYA^a, MITHAT CELEBI^a

^aYALOVA UNIVERSITY

*ozgur.ceylan@yalova.edu.tr

Abstract:

Superabsorbent polymers (SAPs) are slightly cross-linked, three-dimensional networks of flexible polymer chains that carry dissociated, ionic functional groups.

They are basically the materials that can absorb fluids of greater than 15 times their own dried weight, either under load or without load, such as water, electrolyte solution, synthetic urine, brines, biological fluids such. They are polymers which are characterized by hydrophilicity containing carboxylic acid, hydroxyl, amine groups and so on, insoluble in water, and are cross-linked polyelectrolytes.

Despite the increasing market growth of SAPs, their industrial production processes have not changed notably and it is mostly done by solution polymerization. In solution polymerization a monomer such as acrylic acid or acrylamide are polymerized in water using polymerizing additives. But high polymerization heat release, toughness of the gel make the manufacturing processes difficult. Thus this method require further processes such as gel preparation, drying, sizing, post reactions and therefore manufacturing processes take time and costs. Each step affects the final properties of SAP particles considerably. In inverse suspension polymerization processes, small droplets of aqueous monomer solution are dispersed into a second phase, usually aromatic or aliphatic hydrocarbon prior to polymerization. Low viscosity remains constant during polymerization process and this help removing heat from media easily. Parameters such as, dispersing media, phase ratio, initiator, cross linking agent, surface active agent should be selected carefully. Type of dispersing media is especially important because the other parameters mostly depend on it. But once these variables adjusted properly the suspension system will work unproblematic. In addition, final granular product will need fewer processes and be ready for packaging.

In our work we evaluated hexane, heptane, cyclohexane and dichlorobenzene as an organic dispersing media in the synthesizing polyacrylic acid and found that cyclohexane and dichlorobenzene are suitable among the selected solvents.

Keywords: Super Absorbent Polymers (Saps), Inverse Suspension Polymerization, Polyacrylic Acid, Dispersing Media.

PRINCIPLES, OBJECTIVES AND TECHNICAL DIFFICULTIES IN SMART GRID CONTROL

KUBRA PEHLIVANOGLU^{a*}, OSMAN SEVAIOGLU^a

^aMETU

*kubrpehlivan1991@gmail.com

Abstract:

Smart grid will along with facilitate novice sources of energy and new forms of requirements. The potential of smart grids are huge. They could revolutionize the way we produce and use energy, enabling new forms of generation to connect and bringing customers into the heart of the equation with their ability to shift demand and balance the system. Smart grid can help us keep the power on at minimum cost to consumers, while creating jobs and improving growth. Participation is informed and enabled new products, service, and markets, accommodating all generation and storage options and provided the power quality for the range of needs in the 21st century economy by smart grid. Power consumption differs based on time; season of the year, the day of the week, and the hour of the day, weather; temperature, humidity, wind, sky coverage and type of consumers; residential, commercial or industrial. Optimizing the power generation according to demand acquisition utilization and operating efficiency. The study shows that smart grid inspects the power control for both consumer side and producer side. Therefore, optimizing the power management which has been demonstrated with the proposed method optimizes the cost savings. The proposed smart grid optimization methodology provides an applicable option for developing the perfect balance among reliability, availability, efficiency and cost.

Keywords: Smart Grid, Optimization Methods, Power Management

DESIGN OF A SOLAR - HIGH TEMPERATURE PEM FUEL CELL HYBRID SYSTEM FOR MICRO COMBINED HEAT AND POWER APPLICATION FOR RENEWABLE ENERGY COMMUNITIES

KUBRA PEHLIVANOGLU^{a*}, YILSER DEVRIM^b

^aMETU

^bATILIM UNIVERSITY

*kubrapehlivan1991@gmail.com

Abstract:

Hybrid system has a combination of mainly different renewable energy sources available and stabilizes the system which ensures the stable output from sources and reduces the bonage on climate changes. Hybrid power generation system with PV panels is a fast growing technology and it is expected that it will play a major role in the future global electricity generation with hydrogen energy. The aim of this study is to provide a theoretical design and analysis for a renewable energy community electricity and heat demand in Ankara (Turkey). In the present study, a high temperature proton exchange membrane fuel cell stack design and analyze for micro-CHP with using photovoltaic (PV) panels and electrolyzer. Integration of PV panel system powers the electrolyzer in order to generate enough hydrogen and oxygen from water to meet energy demand of the communities. This design is environmental, efficient, and independent of coal and oil. Thus, World energy demand is raising quickly with the increasing population and industrialization in the future fossil fuels like coal, natural gas and oil do not meet our energy demand. Renewable energy sources have importance for these reasons. Alternative energy sources are mostly used in hybrid systems in order to increase system overall efficiency. The study shows that this hybrid power micro combined heat and power system provides a viable option for powering stand-alone energy communities in a self-sustained manner.

Keywords: Solar Energy, Hydrogen Energy, Hybrid System, Renewable Energy Communities

COMPARISON OF DIORAMAS AND 2D RENDERINGS AS DESIGN EXPRESSION TOOLS

OMER FARUK BAYRAM^{a*}, FAZIL AKDAG^a

^aERCIYES UNIVERSITY

bayramomerfaruk@yahoo.com

Abstract:

The concept of space can be defined as the part of space in which the space and boundaries that distinguish the basic state at a certain scale that surrounds the human being and are suitable for its actions are perceived by the observer and wrap around the existence of the subject. Throughout the history of humanity, space production has been needed as a result of basic needs like accommodation and protection. The design discipline has emerged due to the designing, producing and, accordingly, the concern of generating space. In this context, space production, which meets the needs of the period within the conditions that existed throughout history, constituted the most fundamental concern of the discipline of architecture.

The spaces that are supposed to be produced need to be expressed. Throughout history, ideas for design have been expressed in various means and methods. Design products can exist and be understood in terms of they can be expressed. When the design expression tools are evaluated in the historical process, it seems that they are constantly changing and transforming within technical and technological developments.

In this study, dioramas and 2D renderings were examined as architectural representation tools. Dioramas and 2D renderings have been compared and the strengths and weaknesses of expressing spaces have been examined. The purpose of the study is to express the contribution of the design expression tools examined in the scope of the study to the different phases of the process and the usability of the representation and expression in the design process.

Keywords: Dioramas, 2D Renderings, Architectural Space, Architectural Expression Tools

INFLUENCE OF SOLUTION HEAT TREATMENT AT 1180 C ON THE PROPERTIES OF 2.4879 ALLOY

ALPTEKIN KISASOZ^{a*}, ERHAN TUFENK^a, AHMET KARAASLAN^a

^aYILDIZ TECHNICAL UNIVERSITY

*akisasoz@gmail.com

Abstract:

Nickel based alloys are widely used in high temperature applications because of their decent creep and fatigue strengths. In spite of higher microstructural stability of the Ni base alloys, physical and microstructural properties are going to change with usage in high temperature applications. In this study, effect of solution heat treatment at 1180°C on the properties of 2.4879 alloy is investigated. Also, effect of cooling conditions after the solution treatment is studied. Microstructural characterization was carried out by optical microscopy and SEM analysis. Also, mechanical properties of the specimens were determined with Vickers hardness test.

Keywords: 2.4879 Alloy, Heat Treatment, Microstructural Characterization

GREEN SUPPLIER SELECTION: A REVIEW OF METHODOLOGIES AND CRITERIA

AHMET ALP SENOCAK^{a*}, HACER GUNER GOREN^a

^aPAMUKKALE UNIVERSITY

*asenocak@pau.edu.tr

Abstract:

Supplier selection, which is one of the key elements for building effective supply chains, has been a prominent topic for over sixty years. Supplier selection along with supplier evaluation have been studied comprehensively in both corporate and academic world. In recent years, companies tend to consider green policies due to the growing body of consciousness about environmental issues such as stakeholders' force to adopt environmentalist approaches, depletion of natural resources and environmental legislations set by governments. Therefore, in order to analyze and review the current literature on green supplier selection problem, this paper provides a systematic literature review on published researches between 2007 and 2016. The major goals of this paper are to determine the most widely used decision criteria in green supplier selection problem and methodologies implemented by the researchers to address the solution of the problem. By summarizing the literature, we present the literature gaps along with possible future research directions.

Keywords: Green Supplier Selection, Literature Review, Multi-Criteria Decision Making

AN ADAPTATION OF MATRIX ENCODING TECHNIQUE FOR DATA HIDING IN RGB IMAGES

ALI ILKER KOCATEPE^a, MUHAMMED ALI KOSAN^{a*}, HACER KARACAN^b

^aCOMPUTER SCIENCE, INSTITUTE OF INFORMATICS, GAZI UNIVERSITY

^bCOMPUTER ENGINEERING, INSTITUTE OF INFORMATICS, GAZI UNIVERSITY

*ceo.muhammed@gmail.com

Abstract:

Hiding data in a digital medium is a modern form of steganography which aims to create an inconspicuous structure by embedding the message to be transmitted into an ordinary cover object. A digital image file is a popular choice for steganographic applications, since it can be found and shared commonly on the Internet. Image steganography methods hide the message data into the cover image by altering the values of bits in the image's pixels. Each single pixel in an image file with RGB color space has certain clusters of bits which correspond to red, green and blue color values. When embedding secret data bits into an RGB image, as in any application of steganography, it is important to ensure that the resulting stego-image has sufficient imperceptibility. Researches and studies on image steganography have lead to the development of techniques that are specialized in making the stego-images less perceptible to both human vision and computerized steganalysis methods. Matrix encoding, which enables to make less changes while message bits are embedded into the cover image, is a special technique that is proven to be an effective solution for the imperceptibility improvement problem. This study proposes an adaptation of matrix encoding technique to be performed in spatial domain image steganography for embedding data into an RGB image with an improved rate of imperceptibility.

Keywords: Image Steganography, RGB Color Space, Matrix Encoding

NOVEL AMPEROMETRIC XANTHINE BIOSENSOR BASED ON XANTHINE OXIDASE IMMOBILIZED ON ELECTROCHEMICALLY POLYMERIZED 10-[4H-DITHIENO(3,2-B:2',3'-D)PYRROLE-4-YL]DECANE-1-AMINE FILM

HACER AZAK^{a*}, MUAMER DERVISEVIC^a, ESMA DERVISEVIC^a, EMRE CEVIK^a, HUSEYIN BEKIR YILDIZ^a

^aKARAMANOGLU MEHMETBEY UNIVERSITY

*hazak@kmu.edu.tr

Abstract:

Polymeric conducting DTP derivatives are becoming visible as useful structures for both molecular and polymeric materials for the biosensor design. They have planar structures, fused ring systems, electron releasing groups and conjugation properties to increase the electron transfer rate in the enzyme based biosensors. Therefore, these properties make them very important for overcoming the difficulty of the direct electron transfer between enzyme and the electrode [1-2] In recent years, in this area, the dithieno (3,2-b:2',3'-d)pyrrole (DTP) moiety received much attention. The synthesis of DTP type conducting polymers is very important due to thiophene-pyrrole-thiophene fused ring system. Meat and meat products are currently one of the most important component of a healthy and well balanced diet due to its nutritional richness. Xanthine is an intermediate of the purine nucleotide and deoxynucleotide metabolism [3] and as the metabolic precursor of uric acid, it is the first indicator of an abnormal purine profile and can serve as a marker of various diseases as well in the food industry elevated levels of hypoxanthine and xanthine are important biomarkers as a sign of meat spoilage.

In this paper, a novel amperometric xanthine (Xa) biosensor is constructed with immobilization of xanthine oxidase (XOx) on the pencil graphite electrode (PGE). Xanthine oxidase (XO) is immobilized on the electrochemically polymerized conducting polymer film with glutaraldehyde (GA). The xanthine detection is based on the xanthine consumed due to the enzymatic reaction involving xanthine oxidase. The effects of polymer thickness, applied potential, pH and temperature were investigated and optimum parameters were found to be 5 cycles, +5 V, 7.0 and 30 °C, respectively. The present xanthine biosensor with the high selectivity, sensitivity and stability is promising for practical applications.

Keywords: Amperometry, Xanthine Oxidase, Conducting Polymer, Biosensor

VOLTAGE OUTPUT AND CURRENT DENSITY OF 3-D PIEZOELECTRIC FABRIC UNDER VARIOUS APPLIED LOADS

DERMAN VATANSEVER BAYRAMOL^{a*}, NAVNEET SOIN^b

^aNAMIK KEMAL UNIVERSITY

^bUNIVERSITY OF BOLTON

*dvbayramol@nku.edu.tr

Abstract:

Increasing energy demand have led to a significant increase in the experimental works on energy harvesting. Material engineers are now intensively working on either finding new ways for green energy generaton or improving the energy output of the existing energy harvesting materials. Concurrently, a new area of research for textile engineers too has opened up, wherein the photovoltaic and piezoelectric materials are now being used in textiles to produce lighth weight, flexible wearable energy harvesting structures. Think of how many hours people are physically active during the day and how much mechanical energy hence produced is wasted. This has encouraged researchers to used this wasted energy to generate electrical power. Piezoelectric materials are good candidates for transforming mechanical energy into electrical energy. The starting point of this work was what if we can produce piezoelectric fibers and than manufacture fabrics from them. Here, we introduce the energy generation characteristic of a 3 dimensional (3-D) piezoelectric fabric, containing piezoelectric filaments, conductive yarns and insulative yarns. The fabric was produced by a 3-D knitting machine. Piezoelectric filaments were used as spacer yarn interconnecting or separating two knitted layers. In this presentation, we will give the information about piezoelectric filament production, 3-D all fiber piezoelectric fabric construction as well as the experimental results for voltage responses and current densities of 3-D spacer fabric under various applied loads. The results proved that the voltage output and current density of the piezoelectric fabric is proportional to the applied mechanical energy.

Keywords: Voltage Output, Current Density, Piezoelectric Fabric

DETERMINING THE EFFECT OF HARDENING TYPE ON CYCLIC PLASTICITY MODELING USING FINITE ELEMENT ANALYSIS

TOROS ARDA AKSEN^a, EMRE ESENER^b, MEHMET FIRAT^{a*}

^aSAKARYA UNIVERSITY

^bBILECIK SEYH EDEBALI UNIVERSITY

*firat@sakarya.edu.tr

Abstract:

Determining fatigue life of a material has an importance from industrial and academic perspectives. Calculations of stress and strain values must be accurate to perform a sensitive fatigue life analysis of a material. However, there are numerous plasticity models to determine cyclic behavior. Selection of a plasticity model has an important role on sensitivity of fatigue life estimations in finite element analysis. Generally, isotropic and kinematic hardening models are used as plasticity models. Determination of kinematic hardening parameters is a crucial and time consuming process.

In this study, displacement, stress and strains on a supported beam structure under dynamic loading will be determined by finite element analysis using different plasticity models. Isotropic and kinematic hardening models will be used in cyclic plasticity modelling. von-Mises and Chaboche material models will be investigated as isotropic and kinematic hardening models respectively. Chaboche parameters will be identified using Hollomon equation. Besides, results will be compared with two different commercial finite element analysis software.

Keywords: Cyclic Plasticity, Finite Element Analysis, Isotropic Hardening, Kinematic Hardening

RESEARCH OF MECHANICAL PROPERTIES OF POLY(LACTIC ACID) AND GREEN COMPOSITES

ABDULLAH TAV^{a*}, MITHAT CELEBI^a, MEHMET ARIF KAYA^a

^aYALOVA UNIVERSITY

*abdtav@gmail.com

Abstract:

Synthetic polymers are produced about 140 million tons per year in worldwide and production of synthetic polymers have increased gradually. Synthetic polymers are resistant to microbial attack. Polyesters can be produced from plant, microorganisms, bio-derived monomers such as lactic acid. Biodegradable polymers are important because of environmental and economic concerns such as waste disposal and intensifying expenses of petroleum production. Polyesters play very active role as biodegradable plastics because of their hydrolyzable ester bonds. Poly(lactic acid) (PLA) is the most available among polyester based biodegradable polymers. The production capacities of biodegradable plastics have been increased in every year. In this study, green composites were prepared with PLA, algae and zeolite at different ratios by using high shear mixer with mode 11. Mechanical properties of green composites was investigated with tensile test machine (Zwick, 1kN). Thin composites films were observed with optical microscopy.

Keywords: Poly(Lactic Acid), Algae, Zeolite, Optical Microscopy

COMPARISON OF ANALYTICAL AND NUMERICAL CALCULATIONS OF A COLD ROLLING PROCESS

MEHMET FIRAT^{a*}, EMRE ESENER^b, AYKUT BASKAYA^a

^aSAKARYA UNIVERSITY

^bBILECIK SEYH EDEBALI UNIVERSITY

*firat@sakarya.edu.tr

Abstract:

Cold rolling process increases the strength by strain hardening and holds tighter tolerances. Typical products for cold-rolled materials includes motorcycle exhaust pipes, computer cabinets, hinges, metal containers, fan blades, etc. Cold rolling processes needs more force application then hot rolling so determining rolling force or material strain becomes important. Today, finite element analysis have a wide usage area to determine process parameters.

In this study, rolling process of 7516 IF steel will be investigated by means of rolling force and strain rate via analytical and numerical calculations. As a first step cold rolling process of IF material will be performed and 4 mm initial thickness will be reduced to 0.8 mm, and process values will be recorded during the experiment. Then, rolling force and strain rate values will be calculated by analytical methods. Tselikov and Sims Methods will be used to determine rolling force and strain rate, respectively. Numerical calculations will be performed by finite element analysis. As a result, analytical and numerical calculations will be compared with experimental results.

Keywords: Cold Rolling, Finite Element Analysis, IF Steels

DESIGN OF A MICROCOMPUTER BASED REALTIME ECG HOLTER DEVICE

AHMET YESEVI TURKER^{a*}, MUHAMMED GULER^a, AYSE NUR AY^a, MUSTAFA ZAHID YILDIZ^a

^aSAKARYA UNIVERSITY,TECNOLOGY FACULTY,ELECTRIC&ELECTRONICS
DEPARTMENT,BIOMEDICAL INSTRUMENTATION LAB.

*yesevi.turker@gmail.com

Abstract:

The main objective of the project is to develop an open source embedded system based ECG Holter device. Due to the limited opportunities and challenges of hospitals, patients are having difficulties for continuous monitoring which is highly vital for the patients. Thereby, portable, easy to use, and mobile devices must be designed for the medical specialists, cardiologists, patients, and engineers that who are willing to contribute developing the system. The project consists of three main parts; a bioinstrumentation amplifier which is responsible for Biosignal detection, an analog filter part and a microcomputer, respectively. At first stage, ECG signals were amplified by a three opamp bioinstrumentation amplifier about 500 times. At the second stage, an analog 50 Hz notch and bandpass filter which has 0.1 and 120 Hz cutoff frequencies were used. Before using the microcomputer, the filtered ECG signals were recorded by an USB data acquisition card for control data. After this stage, an analog-digital converter was controlled by the microcomputer and the digitized data was obtained. The raw data was filtered on the second stage digital fir filter to reduce signal noise as real time. The filtered signal was plotted on a 7-inch touch screen in near real time and recorded to an SD card on the microcomputer. In this project, the algorithm was performed on three different microcomputers and their performances were compared. At first, the sampling rate for ECG analysis was achieved only about 35 Hz of the Beaglebone microcomputer which was not useful for ECG signals. Secondly, the sampling rate of the Raspberry Pi 2 could be about 80 Hz which might only be used for R-R interval detection. Lastly, Odroid microcomputers could achieve about 250 Hz sampling rate which could be shown an important candidate for real-time ECG analyses as holter devices.

Keywords: Ecg, Holter, Biomedical Instrumentation, Open Source, Embedded System

CLOSED LOOP LASER DIODE TEMPERATURE CONTROL SYSTEM DESIGN

OGUZ KAN KAZAN^a, ALI FURKAN KAMANLI^{b*}, MUSTAFA ZAHID YILDIZ^b, HALIL ARSLAN^b,
HYUN SOO LIM^b

^aSAKARYA UNIVERSITY, BIOMEDICAL ENGINEERING, MASTER PROGRAM

^bSAKARYA UNIVERSITY,TECNOLOGY FACULTY,ELECTRIC&ELECTRONICS
DEPARTMENT,BIOMEDICAL INSTRUMENTATION LAB.

*fkamanli@sakarya.edu.tr

Abstract:

In cancer treatments, because of being a minimally invasive method and having no significant harmful side effect to the patient. This method begins with the administration of ALA-5 photosensitizer material prior to treatment in the tissue, which reacts chemically to the specific wavelength light. Dosimetry calculations determine the time required for ALA-5 in the body to remain only in the tumor. At the end of this period, the tumor tissue becomes eligible for targeted treatment. In order to be able to create the thermal effect on the tissue with the laser beam, a laser with a constant wavelength must be used. When ALA-5 provides sufficient energy in the target tissue excited with specific wavelength light energy in the cell, the cancer cells lead to necrosis. In order to complete the treatment successfully, Photodynamic therapy system's laser diode must have a constant temperature and constant output power so that it can generate constant wavelengths. Since the laser diode temperature is directly related to the wavelength and the output power, control of the temperature at a single point is an essential issue.

In the study, the selected laser diode need to be stabilized at a temperature of 15 °C so that it could operate steadily at a wavelength of 635 nm which can excite the ALA-5. The thermoelectric controller (TEC), the thermistor directly connected to the laser diode, detects the temperature of the diode. The sensed temperature value is applied to the (Dspic30f4013) microcontroller's ADC circuit via an analog circuit that will produce 5V for the maximum value and 0V for the minimum value of the thermistor. This feedback from the thermistor with PID control on the microprocessor determines the PWM on and off time ratio. Cooling control is provided instantaneously by PWM signal applied on the thermoelectric material.

Keywords: Phtodynamic Therapy,Laser Diode Temperature Control, Closed Loop,

RAPID SURFACE HARDENING OF AISI 1045 STEEL FOR AUTOMOTIVE APPLICATION BY ELECTROLYTIC PLASMA TREATMENT

AYSUN AYDAY^{a*}, GOZDENUR KURT^a

^aSAKARYA UNIVERSITY

*aayday@sakarya.edu.tr

Abstract:

For low carbon steels surface performance, carburization is often used to improve the surface properties. If the carbon content of steel is enough (C%4) thermal treatments such as induction, flame, laser, etc. can be treated for surface hardening without the need for surface compositional change. This paper presents an experimental study of surface modification and rapid surface hardening on AISI 1045 steel by Electrolytic Plasma Treatment (EPT). Optimum voltage and ampere values were performed to obtain good surface properties. The surface morphology and the phase structure were analyzed with optic microscope, scanning electron microscope and energy-dispersive spectroscopy. The hardness of modified layer was investigated. It was found that the microhardness of the treated samples was much higher. The results show that, the hardness of AISI 1045 steel is approximately 210 HV0,1 and the hardness after EPT surface heat treatment is around 750-850 HV0,1.

Keywords: Surface Hardening, Phase Transformation, Steel, Microhardness

INVESTIGATION OF MECHANICAL AND THERMAL PROPERTIES OF POLY(ETHYLENE)-POLY(LACTIC ACID) MULCH FILMS

MEHMET MUDU^{a*}, MITHAT CELEBI, OZGUR CEYLAN^a

^aYALOVA UNIVERSITY

*mehmet.mudu@yalova.edu.tr

Abstract:

The usage of plastic mulch in agriculture has increased in the last years. Because of increasing benefits such as enhanced in soil temperature, enviromental and moisture control for plants. However, disposing of used conventional plastic films, which cause enviromental pollution. Therefore, photodegradable and biodegradable mulches have been developed. We can use polyolefin and biodegradable blends to produce agricultural mulch films. Low density polyethylene has been commonly used among conventional polymers. These mulch films are placed on the surface of the soil with machine or hand. These mulch films are prevent soil erosion, reduce weeding, protect soil moisture, and increase temperature of the soil. Biodegradable mulches are derived from plant starches and sugars. At the end of the season biodegradable mulches trigger to degradation by heat, light, microorganisms and other enviromental conditionals. In this study, biodegradable and non-biodegradable blends were prepared with polyethylene and poly(lactic acid) using blow film machine (GUiInar, twin screw diameter: 16 mm). Mechanical and termal properties of produced films were determined with tensile testing machine (Zwick 1 kN), DSC and TGA.

Reference

Subrahmaniyan Kasirajan & Mathieu Ngouajio, (2012), Polyethylene and biodegradable mulches for agricultural applications: a review, *Agronomy for Sustainable Development* April 2012, Volume 32, Issue 2, pp 501–529.

Keywords: Biodegradable, Recycling, Poly(Ethylene), Poly(Lactic Acid), Mulch

VARIABLE NEIGHBORHOOD SEARCH FOR THE HETEROGENEOUS FIXED FLEET VEHICLE ROUTING PROBLEM

OLCAY POLAT^{a*}, CAN B. KALAYCI^a, LEYLA OZGUR POLAT^a, OZCAN MUTLU^a

^aPAMUKKALE UNIVERSITY

*opolat@pau.edu.tr

Abstract:

The vehicle routing problem (VRP) is a well-known transportation problem where a fleet of homogenous vehicles deliver goods from the depot to a number of customers. The heterogeneous fixed fleet vehicle routing problem (HFFVRP) is a more practical variant of vehicle routing problem. While the classical VRP assumes that the fleet owner has unlimited number of vehicles from one type, it is assumed that the fleet owner has various types and fixed number of vehicles in the HFFVRP variant. In practice, this variant may commonly be seen in designing daily service network of beverage, food and dairy transportation. Similar to VRP, this problem variation allows vehicles to make the delivery operations by visiting all clients at once with the aim of minimization of total travel distance. In this study, an efficient hybrid approach is proposed to solve the problem. In this approach, variable neighborhood search (VNS), savings heuristic and perturbation mechanism are combined with the help of efficient neighborhood strategies. The numerical results of a well-known number of benchmark instances show that the developed approach achieved best-known solutions reported in the literature. Additionally, the findings of this study indicate that the approach has the potential of enabling the decision maker to make effective decisions related to design of transportation networks.

Keywords: Vehicle Routing Problem, Heterogeneous Fixed Fleet, Variable Neighborhood Search

NOISE REDUCTION OF EMG SIGNALS USING WAVELET TRANSFORM

YUNUS CELIK^a, MUSTAFA TEKIN^{a*}, MAHIT GUNES^a

^aKAHRAMANMARAS SUTCU IMAM UNIVERSITY

*mustafa_tekin40@hotmail.com

Abstract:

Electromyography (EMG) is a technique for evaluating and recording the small electrical signals produced by skeletal muscles. An electromyograph detects the small electric potentials created by muscle cells, when these cells are neurologically activated. The signals can be used to detect abnormalities, activation level in muscles. EMG signals can be contaminated during measurement because of broken cables, weak cable connections, quality of electrodes, fluorescents in the measuring room. It is necessary to amplify EMG signals because of their small voltage range. That's why amplification is a main part of EMG signals to understand and diagnose. It is quite important to filter signals effectively before amplification otherwise any noise can be amplified with the pure signals during amplification and affect negatively accuracy of measurement. The main purpose of this paper is to make it cleaner contaminated EMG signals using wavelet transform to provide efficient and effective ways of understanding of signal and its nature. In this study, arm muscle F12 Extensor Digitorum communis has been measured with a needle EMG method in a hospital with patient's permission and denoised with filters. Wavelet Transform Methods are used to design a filter. Signal To Noise Ratio is a method for evaluating performance of filter by comparing their uncontaminated values. Contaminated signals and filtered signals are exhibited together to point out the difference. Performance of filter is measured using Filter To Noise Ratio (SNR) method. In conclusion, filter works efficiently and signal is uncontaminated according to SNR results.

Keywords: Wavelet Transform, EMG Signals, Signal To Noise Ratio (SNR)

AN EFFECTIVE MODELLING METHOD BASED ON MLP-BASED ARTIFICIAL NEURAL NETWORKS FOR OBTAINING V-CURVE CHARACTERISTICS OF SYNCHRONOUS MOTOR

AHMET GANI^a, MUSTAFA TEKIN^{a*}, O.FATIH KECECIOGLU^a, HAKAN ACIKGOZ^b, MUSTAFA SEKKELI^a

^aKAHRAMANMARAS SUTCU IMAM UNIVERSITY

^bKILIS 7 ARALIK UNIVERSITY

*mustafa_tekin40@hotmail.com

Abstract:

System models are created based on the data obtained from applications or mathematical expressions. Modelling plays a vital role in the determination of dynamic behaviors in a system. Artificial neural networks have been widely used in the modelling of complex and non-linear systems. Various studies have focused on the use of artificial neural networks for system identification and modelling. Multilayered artificial neural networks with a feed-forward and non-linear structure are often used in various applications such as image recognition, classification, system modelling, function approximation, and the estimation of chaotic time series. Multilayered artificial neural networks is the most commonly used type of artificial neural networks in the solution of non-linear problems. Synchronous motor is an alternative current motor in which rotor rotational speed is equal to the rotational speed of the stator rotating field and the rotation speed does not vary in loading. When excitation current of the synchronous motor changes, it absorbs ohmic, inductive and capacitive current from the grid. In a synchronous motor operating at a constant load and voltage, the characteristic which yields the relationship between excitation current and stator current is called V-current. This study proposes an effective modelling method via multilayered artificial neural networks by obtaining excitation current and current load data comprising V-curve characteristics of the synchronous motor in Matlab/Simulink. The proposed modelling method can be applied to all characteristics of the synchronous motor.

Keywords: Modeling, Synchronous Motor, Artificial Neural Network

USE OF GREEN TEA IN DYEING OF CELLULOSIC FIBERS

M. IBRAHIM BAHTIYARI^{a*}, FAZLIHAN YILMAZ^a, HUSEYIN BENLİ^b

^aERCIYES UNIVERSITY TEXTILE ENGINEERING DEPARTMENT

^bERCIYES UNIVERSITY, MUSTAFA CIKRIKCIOGLU VOCATIONAL SCHOOL

*bahtiyari@erciyes.edu.tr

Abstract:

The colors of the textile goods can be important for the sales appeal. So it can be told that textile finishing especially dyeing-printing processes have a great role in steering the customers. Today for the coloration of textile goods generally synthetic dyes are used. However in this study it was aimed to introduce the usability of green tea in coloration of cotton and linen fabrics as a natural dye source. Green tea has been used directly in dyeing of the fabrics, in other words green tea has not been taken to an extraction period previously. So dye extraction and dyeing has been managed at the same time during the dyeing step at boiling temperature. In dyeing period simultaneously mordanting has been managed by the use of different mordants such as $\text{CuSO}_4 \cdot 5\text{H}_2\text{O}$, $\text{FeSO}_4 \cdot 7\text{H}_2\text{O}$, $\text{K}_2\text{Cr}_2\text{O}_7$, $\text{SnCl}_2 \cdot 2\text{H}_2\text{O}$, $\text{KAl}(\text{SO}_4)_2 \cdot 12\text{H}_2\text{O}$. Additionally, the dyeings without use of any mordant has been conducted too. The dyed fabrics were then analyzed in terms of color efficiencies (K/S) and color values (CIE $L^*a^*b^*$). Moreover the fastnesses of the dyed samples were examined too. Finally it was found that green tea can be used for the coloration of both linen and cotton fabrics.

Keywords: Cotton, Linen, Natural Dye, Green Tea

MICROWAVE ENERGY FIXATION FOR DISCHARGE PRINTING ON COTTON FABRIC

ARZU YAVAS^a, ECE KALAYCI^a, OZAN AVINC^{a*}, GAMZE ARAS^a

^aTEXTILE ENGINEERING DEPARTMENT, FACULTY OF ENGINEERING, PAMUKKALE UNIVERSITY

*oavinc@pau.edu.tr

Abstract:

Discharge printing is a printing method based on dye stripping from the previously dyed fabric at desired areas. It is widely used for furnishing and apparel textiles. In this study, the usage of microwave energy for fixation of discharge printing paste on cotton fabric was investigated in comparison to conventional steam fixation. Reactive dyed cotton samples were printed with neutral discharge printing paste and fixed with both conventional steam process (at 102oC for 10 minutes) and microwave energy (for 1, 3 and 5 minutes at 720 and 900 Watt). Afterwards, color strength (K/S) properties of printed fabrics have been evaluated. It was observed that microwave fixations resulted in quite similar discharging effects with classical steam fixation. In other words, microwave energy could be used in fixation process of discharge printing on cotton fabrics.

Keywords: Discharge Printing, Steam, Microwave, Fixation, Color, Printing, Cotton

POTASSIUM PERMANGANATE BLEACHING OF NATURAL PINEAPPLE FIBERS

ECE KALAYCI^a, ARZU YAVAS^a, OZAN AVINC^{a*}

^aTEXTILE ENGINEERING DEPARTMENT, FACULTY OF ENGINEERING, PAMUKKALE UNIVERSITY

*oavinc@pau.edu.tr

Abstract:

Pineapple fiber is a kind of lingo-cellulosic fiber extracted from pineapple plant leaves. Pineapple fiber is abundant in the tropical or subtropical countries due to weather conditions. Pineapple fibers can also be categorized as agro waste fibers. In this paper, the usage of potassium permanganate as a bleaching agent for pineapple fabrics has been investigated. Pineapple fabrics were bleached with potassium permanganate in various conditions (at pH 4 and pH 7; 60 and 90oC; 10 minutes with 1, 3, 5, 7, 10, 20 g/l potassium permanganate concentrations) and then treated with oxalic acid in various concentrations (8, 16, 24 g/l). Bleached pineapple fabrics were evaluated according to their whiteness and yellowness indexes and lightness (L*) properties. Whiteness index of pineapple fabrics increased with an increase in applied potassium permanganate concentration up to 7 g/l, however; higher concentrations resulted in a decrease in whiteness values. The best whiteness and yellowness indexes were observed on pineapple fabrics treated with 7 g/l potassium permanganate at 90oC and pH 7 and followed by 8 g/l oxalic acid treatment.

Keywords: Natural Fiber, Pineapple Fiber, Lignocellulosic Fiber, Agro Waste Fiber, Bleaching, Pretreatment, Potassium Permanganate

VARIABLE NEIGHBORHOOD SEARCH FOR PORTFOLIO OPTIMIZATION

CAN B. KALAYCI^{a*}, OKKES ERTENLICE^a, OLCAY POLAT^a

^aPAMUKKALE UNIVERSITY

*cbkalayci@pau.edu.tr

Abstract:

Portfolio optimization involves a multi-objective problem with two conflicting objectives: profit maximization and risk minimization. If a portfolio cannot provide a better profit for a given risk value or cannot provide a lower risk for a desired return level, then that portfolio is accepted to be on the efficient frontier that is determined with a set of pareto optimal solutions. In this paper, we present a continuous variant of variable neighborhood search (VNS) approach, for solving the cardinality constrained mean-variance portfolio model that provides a practical investment strategy for rational investors. In order to overcome continuous domain difficulties, five local search neighborhood structures that include procedures utilizing derivative information: Steepest-Descent method, Fletcher-Reeves method, Davidon-Fletcher-Powell method and procedures utilizing non-derivative information: Hooke-Jeeves method, Nelder-Mead method are integrated to VNS. The proposed solution approach is tested on seven different capital market indices; namely, Hang Seng, DAX 100, FTSE 100, S&P 100, Nikkei 225, XU030 and XU100 using popular performance measures defined in the literature in order to calculate the errors between heuristic frontier and the standard efficient frontier. The proposed approach has promising insights and by developing strong local search operators designed for continuous domain, the algorithm may be enhanced for providing a superior solution methodology.

Keywords: Portfolio Optimization, Variable Neighborhood Search, Mean-Variance

ANT COLONY OPTIMIZATION FOR PORTFOLIO OPTIMIZATION

CAN BERK KALAYCI^{a*}, OKKES ERTENLICE^a, LEYLA OZGUR POLAT^a, ASKINER GUNGOR^a

^aPAMUKKALE UNIVERSITY

*cbkalayci@pau.edu.tr

Abstract:

In this paper, we focus on solving mean-variance portfolio optimization with cardinality constraints. This multi-objective problem has two conflicting objectives: profit maximization and risk minimization. Therefore, an efficient frontier that presents a tradeoff between the two objectives is sought. Cardinality constraints that impose a restriction on the number of assets to be held and lower-upper limits for the proportion of each asset bring the problem to the class of NP-Complete problems. In general, metaheuristic algorithms may conveniently provide near optimal solutions for the problems in this class. A popular algorithm, ant colony optimization that was firstly introduced for solving travelling salesman problem, has widely been adapted to solve various discrete optimization problems in the literature. However, there are not many applications on continuous domains. Portfolio optimization requires a search in the continuous search space and therefore in this study, a continuous variant of ant colony optimization technique is adapted. The method was tested on five well-known publicly available benchmark problems along with two new data sets from a developing country that intends to further extend the publicly available benchmark data sets to the attention of researchers. Initial results are promising to enable the design of an efficient algorithm for both practitioners and researchers.

Keywords: Ant Colony Optimization, Portfolio Optimization, Mean-Variance Model

ACTIVITY AND STABILITY OF TiO₂ CATALYSTS IN CATALYTIC DECOMPOSITION OF FORMALDEHYDE IN SUPERCRITICAL WATER

AYTEN ATES^{a*}

^aCUMHURİYET UNIVERSITY ENGINEERING FACULTY

*aytates@gmail.com

Abstract:

Heterogeneous catalytic reaction in the presence of supercritical water (SCW) provides various advantages such as controlling of reaction rate, improvement of activity, stability and lifetime of the catalysts. However, the stability and mechanical strength of catalysts cannot be remained in SCW and these are generally the solid- solid transformations of the conventional catalysts. In addition, the structural changing such as the aggregation of solid catalysts, phase transformation and dissolution of solid can be occurred in SCW. The degree of the structural changing depends on the composition and preparation method of catalysts and operation conditions in the reactor. In this study, a series of TiO₂ has been prepared by sol-gel method using different calcination temperatures in order to determine stability and catalytic activity decomposition of formaldehyde in SCW. The catalysts were characterized by surface area (Brunauer-Emmett-Teller, BET method), TGA, FTIR, SEM and SEM/TEM-EDS, XRD, zeta potential, Temperature-Programmed Reduction (TPR) and Temperature-Programmed Oxidation (TPO) experiments. The reactions were carried out in a batch reactor (Parr 4591) (inner volume of 100 cm³). 50 g of formaldehyde solutions and 0.5 g of the catalyst were loaded in the reactor. After 30 min at 400 oC, gas and liquid samples were analyzed by using an on-line GC and HPLC. Although anatase phase of TiO₂ mostly formed until 600oC of calcination temperature, above this temperature, rutile phase formed. The characterization results show that an increase of calcination temperature from 350 oC to 900 oC decreases surface area of the sample and increases crystallinity and stability of TiO₂ in SCW. All of the formaldehyde (HCHO) was converted to CH₃OH, CO, CO₂, and H₂ at 400oC under supercritical conditions for all TiO₂ morphologies. The highest H₂ yield (57.6 (mole) %) was determined on the TiO₂ catalyst calcined at 550 oC.

Keywords: TiO₂, Sol-Gel, SCW, Folmadehyde Decomposition

URBAN GREEN SPACES IN THE CONTEXT OF CHANGE AND INTERACTION

ALI HEYIK^a, ASLI SUNGUR ERGENOGLU^{a*}

^aYILDIZ TECHNICAL UNIVERSITY

*asungur@gmail.com

Abstract:

Public green spaces have a very critical place within social life, in terms of the functions they have in environment-human and individual-society interaction. Today, the community is becoming less and less connected with public green spaces, mostly due to small-scale designs that have been carried out without a holistic perspective. Achieving the efficient use of these areas depends on moving beyond the stereotypes and acting with the awareness that the interaction between the individual and environment is one of the basic needs of society.

Especially in developing countries, there are unqualified and unhealthy green areas allocated to the public use. Scattered unplanned and undersized green spaces and parks are not able to represent a powerful meaning for its environment in terms of their use and this leads to inefficient use of the areas in question. Public green spaces can be recovered by first determining the reasons of them being idle and then rehabilitating these areas. In the paper, best-practice examples of rehabilitation are given and discussed. In order to carry out the recovery process of the various scaled green spaces with certain order and level in a healthy manner, it is necessary to establish a frame in which the public spaces can be assessed within the context of change, use and interaction in today's conditions. In the paper; the factors affecting the use of the green areas positively and/or negatively are determined and then the effects of rehabilitation applications through "AlaCatı Yel DeGirmenleri Parkı" are evaluated in line with these criteria, with the aim to contribute to the rehabilitation of the public green areas.

Keywords: Design For Interaction, Public Green Spaces, Rehabilitation, AlaCatı

PREPARATION AND PROPERTIES OF CONTROLLED-RELEASE FERTILIZERS COATED WITH CROSSLINKED HYDROGELS

MUHAMMED SELMAN DOGAN^{a*}, MEHMET ARIF KAYA^a

^aUNIVERSITY OF YALOVA

*mselmandogan@gmail.com

Abstract:

Controlled-release fertilizers (CRF) can be prepared by encapsulation of fertilizers with water-insoluble polymers currently has popular usage and offer great advantages. Solubility characteristics of coated fertilizer in the soil is most important factor for releasing behaviour. In this study urea based granule shaped fertilizer samples were coated with aqueous poly(vinyl alcohol) (PVA) solutions containing DMSO via crosslinking with using various ratio of glutaraldehyde as crosslinker. Coating process was carried out in a rotary drum and polymer solutions were sprayed on the granules. Coating thickness of fertilizers were determined by optical microscopy method. In order to understand the release behaviour of CRFs with encapsulated, samples were tested in the water. With using spectrophotometer concentration of urea was calculated for samples in the water. Consequently, desired coating thickness, surface properties and release behaviour were reached. Releasing of urea takes longer time was observed with increasing cross-linking ratio.

Keywords: Controlled-Release Fertilizer, Urea Fertilizer (EUF), Polymer-Coated Fertilizer, Crosslinked Polyvinyl Alcohol (PVA)

DETERMINING THE LOCATION OF A WASTE ELECTRICAL AND ELECTRONIC EQUIPMENT (WEEE) RECYCLING PLANT IN THE AGEAN REGION OF TURKEY

ZEYNEP OZSUT BOGAR^a, LEYLA OZGUR POLAT^a, OZAN CAPRAZ^b, ASKINER GUNGOR^{a*}

^aPAMUKKALE UNIVERSITY

^bNAMIK KEMAL UNIVERSITY

*askiner@pau.edu.tr

Abstract:

Recycling electronic waste has become an important research area in recent years due to its potential benefits to economy and sustainable environment. The recycling of WEEE is also crucially important since it handles hazardous waste according to regulations and retrieves the valuable materials. One of the important issues in creating appropriate infrastructure to recycle WEEE is the selection of optimal location for the recycling plants. Although, there is a growing interest in the related literature, there are limited studies in developing countries to manage WEEE based on scientific findings. In order to contribute to the fulfillment of this need, a mixed integer linear programming (MILP) model is proposed to determine the optimal location of a WEEE recycling plant. The MILP model is applied to the case of Aegean Region of Turkey.

Keywords: Weee, Recycling, Facility Location, Mixed Integer Linear Programming

REVIEW OF ESTIMATION METHODS FOR E-WASTE QUANTITIES AND THE APPLICATION OF SIMPLE DELAY METHOD FOR THE CASE OF TURKEY

OZAN CAPRAZ^a, LEYLA OZGUR POLAT^b, ZEYNEP OZSUT BOGAR^b, ASKINER GUNGOR^{b*}

^aNAMIK KEMAL UNIVERSITY

^bPAMUKKALE UNIVERSITY

*askiner@pau.edu.tr

Abstract:

Electronic waste or e-waste is the fastest growing waste stream in the world. Both governments and civil initiatives are working together to create social awareness to struggle with sharply increasing e-waste production and to develop necessary management practices. Due to environmental, social, health and legal outcomes of e-waste, it has become important to construct sustainable e-waste management system. In order to create such an efficient system, the crucial data are related to the quantities of various type of e-waste coming into the waste recovery system. Therefore, estimation of these quantities becomes valuable. This study aims to review different estimation methods which mainly depend on input output analysis. The methods are evaluated in terms of their advantages, disadvantages and information needed to implement them for e-waste estimation. Then, in the study, The Simple Delay Method is used to estimate the quantities of waste white goods in Turkey. Refrigerators, washing machines, dishwashers, dryers, ovens and freezers are taken into account as white goods. The study contributes to the advancement of the e-waste related literature and adds benefit to understanding the e-waste potential of Turkey.

Keywords: E-Waste, Estimation, White Goods, Simple Delay Method

INHIBITORY EFFECTS OF ZINC OXIDE NANOPARTICLES ON ANAMMOX PROCESS

SAFIYE CAN^{a*}, DENIZ AKGUL^a

*safiscan@hotmail.com

Abstract:

Nowadays, biological nitrogen removal in wastewater is commonly achieved by conventional nitrification denitrification processes. Nitrification is a process that requires large volumes due to slow growing nitrifiers and high energy for aeration. In addition, organic carbon is needed for the denitrification process. Wastewaters containing low organic carbon require the addition of carbon externally, which increases the cost of treatment. For these reasons, new microorganisms have been discovered as a result of researches and Anammox (Anaerobic Ammonia Oxidation) species have been nominated to find application area as an innovative technology instead of conventional nitrification denitrification processes. Anammox is a process that oxidizes ammonium nitrogen to nitrogen gas in anoxic environment where nitrite is used as an electron acceptor. Compared to conventional nitrification denitrification processes, the Anammox process requires less energy, does not require external carbon addition and produces less sludge. Therefore, the Anammox process is an innovative, effective and low-cost alternative for the treatment of wastewaters containing high nitrogen. In recent years, application of nanotechnology rapidly increased and the use of nanoparticles is now very common in industrial products. Because of their small size (1-100 nm), nanoparticles can be more toxic than the larger particles in the bulk material. Nanoparticles after being used are discharged to domestic wastewater treatment plants and they effect the biological processes. Although there are numerous nanoparticles which are frequently used in industrial applications (ZnO, TiO₂, Ag, CuO, Al₂O₃, SiO₂, CrO₂, etc.) zinc oxide nanoparticles are most common. The objective of this study is to investigate the zinc oxide nanoparticle inhibition in enriched Anammox culture in both batch and continuous systems. In this context, inhibition levels of zinc oxide nanoparticles will be demonstrated in batch systems. Thereafter, inhibition effects on continuous systems will be observed by increasing the nanoparticle concentration gradually.

Keywords: Anammox, Inhibition, Nitrogen Removal, ZnO Nanoparticles

PREPARATION AND PROPERTIES OF POLYPHENYL ETHERS CONTAINING MULTIPLE BONDS IN THE MAIN CHAIN

MEHMET ARIF KAYA^{a*}, HILAL GUNDUZ^a

*marifkaya@yaloa.edu.tr

Abstract:

Polyphenyl ethers (PPE) are an important family of polymers known for their high thermo-oxidative strength properties. In addition, PPEs often work in extreme applications such as aircraft-space applications due to their superior resistance to radiation. Multiple bonds are real attraction point from the standpoint of differentiation of the molecule it enters into, its ability to modify and function in the desired direction. In the study, it is aimed to reveal the structure-property relationship of polyphenyl ethers containing multiple bonds in the main chain.

Recently, the Glaser coupling reaction between alkyne and alkyne groups has been widely used in organic and polymer chemistry. Glaser coupling reactions can be carried out under mild conditions need no oxygen removal and heating procedures makes the copper-catalyzed alkynyl homocoupling cyclization a valuable method for the preparation of cyclic polymers. Glaser coupling can be used as a clean and efficient method for combining and obtaining polymers. Omission of copper is advantageous to suppress Glaser-type coupling of the alkynes as side reaction. In this study the intramolecular cyclization was performed by Glaser coupling reaction in THF/Cu(I)Br/pentamethyldiethylenetriamine system at room temperature and under an air atmosphere. Structural, thermal and physical properties of obtained polyphenyl ether samples were investigated.

Keywords: Glaser Coupling, Polyphenyl Ether, Multiple Bonds

MESENCHYMAL STEM CELL RELEASED FROM CYTOKINES AND CHEMOKINES, ITS EFFECT ON COLON PRIMER, METASTATIC ADENOCARCINOMA AND CANCER STEM CELLS

FEYZAN OZDAL KURT^{a*}, CANAN TURKOGLU^a, REMZIYE KENDIRCI^b, SEDA VATANSEVER^b

^aCELAL BAYAR UNIVERSITY, FACULTY OF SCIENCES & LETTERS, DEPARTMENT OF BIOLOGY,
MANISA TURKEY

^bCELAL BAYAR UNIVERSITY, SCHOOL OF MEDICINE, DEPARTMENT, HISTOLOGY AND
EMBRYOLOGY, MANISA TURKEY

*feyzanozdalkurt@yahoo.com

Abstract:

Cancer is a group of diseases involving abnormal cell growth with the potential to invade or spread to other parts of the body. The gastrointestinal cancer is a frequently met malign tumor oriented case and its cure is still uncertain. Cancer stem cells (CSCs) are cells that drive tumorigenesis, as well as give rise to a large population of differentiated progeny that make up the bulk of the tumor.

In this study, the human metastatic colon carcinoma cell line (Colo 741), human primary colon cancer cell line (HCT 116) and Human mesenchymal stem cell string of bone marrow PCS-500-012 were cultured in DMEM containing 10% FCS, 1% L-glutamine and 1% penicilin-streptomycine. Colon carcinoma stem cells were isolated from both types of cells by magnetic-activated cell sorting (MACS) technique and characterized by CD133 surface protein using immunohistochemical analyses.

Primary and metastatic colon carcinoma cell line and cancer stem cells obtained from from both types of cells was sprinkled to the bottom of 24 partitioned- culture cups and mesenchymal stem cell line of bone marrow was expected to cling to the cup then, was added to the upper parts of the cups and their cultures was one by one prepared. On the 7. and 14. days of the culture CXCL1, IL-6, IL8 and CCL2 values was examined in supernatant by ELISA, on the 14. day IL-6, IL-8, CXCL1, CCL2 was examined with an immunohistochemical method.

The results indicated that Colo 741, HCT116 and the cancer stem cells separated from them cocultured with human mesenchymal stem cell secreted an increased level of cytokines and chemokines after 14 days. The inflammatory mediators released by mesenchymal stem cells related to the micro-environmental factors survival of the colon cancer cells. Mesenchymal stem cells start a reaction with the new micro-environment and they secrete different mediators.

Keywords: Stem Cells, Cytokine, Chemokine, Cancer

THERAPEUTIC EFFICACY OF HONEY LOADED SCAFFOLDS IN FULL-THICKNESS WOUNDS OF RATS

OMER AKTURK^{a*}, DILEK KESKIN^b

^aFACULTY OF ENGINEERING, DEPARTMENT OF BIOENGINEERING, KIRIKKALE UNIVERSITY

^bDEPARTMENT OF ENGINEERING SCIENCES, MIDDLE EAST TECHNICAL UNIVERSITY, ANKARA, TURKEY

*omerakturk@kku.edu.tr

Abstract:

The aim of this study was to evaluate the therapeutic efficacy of honey loaded silk fibroin matrices (SFM) on full-thickness cutaneous wound healing of rats. SFM were fabricated by wet electrospinning of silk fibroin of Bombyx mori origin and poly(ethylene oxide) aqueous solutions, then treated with ethanol (SFM-E) to increase their stability, and eventually loaded with diluted honey (SFM-HE). The scaffolds had desirable porous and 3D nanofibrous structure for skin tissue engineering. Full-thickness skin wounds in a rat model were treated with scaffolds or left untreated (untreated control: UTC). Wound closure of SFM-HE ($69 \pm 7\%$) was found to be significantly higher than that of UTC ($45 \pm 12\%$) on post-operative 14th day. In biomechanical evaluations, SFM-HE groups were shown to restore only 44% of the tensile strength and 29% of tensile modulus of original unwounded skin of rats, forming the softest, weakest and the most extensible skin. Honey loaded scaffolds had significantly higher re-epithelialization, neovascularization and granulation than UTC according to histopathological scoring. Inflammation level of SFM-HE were also lower than UTC, but the results were not statistically significant. In brief, the utilization of honey as an adequate medication in skin tissue scaffolds might hold a great promise in the future.

Keywords: Silk Fibroin, Honey, Wet Electrospinning, Full-Thickness Rat Skin Wound

PROPERTIES IN THE COMPOSITES OF EPOXY-CEMENT-PZT CERAMICS POWDER

AYLIN AKYILDIZ^{a*}, DERMAN VATANSEVER BAYRAMOL^a, AHMET OZGUR AGIRGAN^a

*aakyildiz@nku.edu.tr

Abstract:

Lead zirconate titanate (PZT) is one of the most widely studied ceramic materials for various areas. This ceramic material can be produced as a piezoelectric material which makes it desirable for many applications. Its extraordinary behavior has been known since mid 20th century. It is slightly a new material in civil engineering but a good candidate for many applications. In this work, PZT was mixed with normal Portland cement at different ratios to produce composites. The influences of filler content and composite thickness on the composite properties were investigated. Morphology of the composites was characterized by scanning electron microscopy, mechanical properties of the samples were studied by uniaxial tension.

Keywords: Cement. Epoxy. Lead Zirconate Titanate Ceramic Powder. Composite.

DESIGN OF IPM SYNCHRONOUS MOTOR FOR GEARLESS ELEVATOR APPLICATIONS

HICRET YETIS^{a*}, ERKAN MESE^b

^aYILDIZ TECHNICAL UNIVERSITY, ISTANBUL / DEPARTMENT OF ELECTRICAL ENGINEERING

^bEGE UNIVERSITY, IZMIR / DEPARTMENT OF ELECTRICAL AND ELECTRONICS ENGINEERING

*hicretyetis@gmail.com

Abstract:

Interior permanent magnet synchronous motors (IPMSM) have been commonly used to meet challenging demands of high performance industrial applications. IPMSM have several advantages such as elimination of rotor copper loss, high power density and efficiency, high starting torque. In this paper, the design of IPMSM for gearless elevator has been investigated. Gearless elevator systems driven by PMSM have many advantages compared to traditional asynchronous motor applications. Due to highly sensitive absolute encoder coupled to motor and closed-loop driver system providing sensitive control, PMSM based gearless elevators show high performance at lifting up, stopping and moving. However, drawbacks of IPM machines are high torque ripple and rising cost of rare-earth permanent magnets such as NdFeB and SmCo. The variation of magnetic reluctance between the flux barriers and teeth causes the torque ripple. In this study, different slot/pole combinations and number of flux-barrier layer have been investigated to reduce torque ripple. Furthermore whole design is based on ferrite magnet which is cheaper and more common. MotorSolve BLDC Finite Element Analysis based software has been used. Eventually attributes such as low cost, high efficiency, high torque density and lowest possible torque ripple have been achieved for the design of IPMSM in gearless elevator applications.

Keywords: : Interior Permanent Magnet (IPM), Machine Design, Gearless Elevator Application, Torque Ripple, Ferrite Magnet.

CORRELATING SURFACE POTENTIAL WITH IRREGULAR PLASTIC DEFORMATION

AHMET YILMAZ^{a*}

^aYALOVA UNIVERSITY

*yilmaz5@hotmail.com

Abstract:

Surface potential of AA 3204 undergoing a serrated plastic flow (PLC effect) was monitored in a dilute brine electrolyte under various strain rates at 30 oC. Significant potential bursts at the launch of the stress drop regimes of the flow were revealed. The serration counts and frequency of the PLC effect matched with that of the bursts precisely, and average burst magnitude ($\approx V$) was found to be directly proportional with that of the stress drops ($\approx \sigma$). The bursts were attributed to the electrons in strain fields of the slip steps exposed to the electrolyte during the local banding events. The utility of the electrochemical set-up for investigation of the PLC effect and monitoring deformation and damage progress of materials were affirmed.

Keywords: Plastic Deformation, PLC Effect, Surface Potential, Surface Films, Dislocations.

AN EXAMINATION OF DAYLIGHT USAGE OF FIRAT UNIVERSITY FACULTY OF ARCHITECTURE BUILDING WITH BIM

EBRU DOGAN^{a*}, HASAN POLAT^b

^aBINGOL UNIVERSITY

^bFIRAT UNIVERSITY

*ebrudogan2334@hotmail.com

Abstract:

The surfaces of building envelope are the intersections that create connections between buildings and external environment in terms of aesthetics, physics, and chemistry. The interior spatial conditions of a building are determined by the visual, thermal, and radial permeability of the building envelope. Daylight taken from the surfaces of building envelope has an effect on the indoor spatial comfort conditions like the users' health and the building's energy use. The use of daylight should be in sufficient amount especially for the needs of the places used during the day. In cases in which daylight is deficient, the need of artificial lighting and heating arises. Therefore, the users face the places that are uncomfortable in terms of interior spatial comfort and that consume a lot of energy. The effect of the use of daylight is a lot especially on the user comfort in education buildings. Benefitting from daylight is important for the users who spend most of their times at school in terms of mental efficiency and psychology. On the other hand, the need for an efficient building envelope design emerges in order to avoid physical problems' occurring among the users because intensive daylight tires their eyes and heats the place a lot. Firat University Architecture Faculty Building, still under construction, was chosen as a sample case in this study. Sixty-five percent of the rough framing of the building has been completed. The building envelop was designed by considering construction and operation cost. The analyzes were made on the effect of the building envelop on the indoor daylight usage. The faculty building was modelled in Revit depending on the project assumptions such as like the building's plan layout, floor heights, envelop...i.e factors. Daylight analysis of the created model was made with BIM on the date of equinox.

Keywords: Educational Building Design, Daylighting Analysis, Revit, Bim

THE COMPARISON OF MONE'S BUILDING TYPES PROJECTS WITH MONE'S EDUCATION BUILDING STANDARDS AND THE EVALUATION OF THEIR CONSISTENCY

HASAN POLAT^{a*}, EBRU DOGAN^b

^aFIRAT UNIVERSITY

^bBINGOL UNIVERSITY

hpolat@firat.edu.tr

Abstract:

The right to education that is guaranteed by several laws of the constitution reaches the individuals through the state's executive power. The executive tries to fulfill its actions depending on the mechanisms of equality and justice in education. The right to plan buildings and facilities belonging to education institutions of every level and kind was given to the Ministry of National Education (MoNE) by the Basic Law of National Education. The Ministry developed standards under the light of education standards and produced building types projects in order to meet the need of educational buildings around the country quickly and economically. By taking manufacturing cost, management, function, aesthetics, and the level of efficiency in education into consideration, the improved standards are definitely important for the students' and teachers' spatial comfort. In this study, the consistency between the Ministry's current project preparation regulations and its 2000.07-numbered sixteen-classroom high school building type project was evaluated by comparing them with each other.

Keywords: Educational Building Design, Project Standarts

A MATHEMATICAL MODEL FOR ALLOCATION AND DISTRIBUTION OF HUMANITARIAN RELIEF TO DISASTER AREA

YUSUF SAHIN^a, HASAN AKYER^b, TUGCE TASKINER^b, OLCAY POLAT^{b*}

^aMEHMET AKIF ERSOY UNIVERSITY

^bPAMUKKALE UNIVERSITY

*opolat@pau.edu.tr

Abstract:

Natural, technological or man-induced events that have the unpredictability in time, the intensity and the location are called as disaster. Disasters have a serious disruption on the functioning of a society and affect human life negatively due to destruction they create in the region. Existing local resources are often inadequate to remove these effects. Preparing societies and communities to crisis is a crucial task before and after the disasters and people are in the center of these preparation processes. Today, societies are aware of the need on developing efficient disaster management systems to minimize the loss of life and property caused by the disaster. Humanitarian logistics includes post disaster management activities such as search and rescue, evacuation, allocation of humanitarian relief and the establishment of the temporary shelter areas. The relief need by exposed people are met from the logistics warehouses established in different cities by the authorized institutions. A mixed integer linear programming model is developed to allocate relief to disaster area points from the warehouse in the transportation network with the aim of minimization of service time. Numerical results show that the developed model may be very useful in effectively planning distribution of humanitarian relief after disasters. Thus, the relief items can be delivered to the exposed people as early as possible.

Keywords: Humanitarian Logistics, Disaster, Relief, Mathematical Model

STABILITY AND ACTIVITY OF ZIRCONIUM OXIDE IN CATALYTIC SUPERCRITICAL WATER GASIFICATION OF FORMALDEHYDE

AYTEN ATES^{a*}, OSMAN MERT^a

^aCHEMICAL ENGINEERING, ENGINEERING FACULTY

*aytates@gmail.com

Abstract:

The presence of heterogeneous catalysts in the reaction occurring in supercritical water (SCW) is required to increase the reaction rate and the selectivity of the desired product (such as H₂, CH₄). However, many of the heterogeneous catalysts in the reactions occurring in supercritical water (SCW) do not maintain thermal and hydrothermal stability. Also, in the present studies, there is little information on the changes in the thermal and hydrothermal stability of catalysts in SCW. For this reason, ZrO₂ material, which is transparent, resistant to heat and electrical conductivity, chemically stable and has ionic conductivity at high temperatures, was selected to be tested in the gasification of formaldehyde in SCW. ZrO₂ was synthesized by sol-gel method and calcined at 500, 900 and 1400 °C. Stability of ZrO₂ samples which is fresh and used in the catalytic gasification of formaldehyde in the presence of SCW was determined by various methods such as FTIR, XRD, TEM, SEM, BET, TPO, H₂-TPR, zeta potential. In addition, the effect of catalyst amount, temperature, and reactant concentration and retention time on the yield of SCW gasification of formaldehyde with ZrO₂ catalysts was investigated. ZrO₂ samples calcined at 500 and 1400 °C mostly involve monoclinic and tetragonal phase, respectively and have nano-sized particles. However, ZrO₂ calcined at 900 °C was found to exhibit amorphous structure. Based on formaldehyde activity results, the highest H₂ yield was found at 0.5 g of ZrO₂ for 20 (v/v) % formaldehyde in water at 400 °C.

Keywords: SCW, Formaldehyde, Zirconium Oxide, Gasification, Stability

INVESTIGATION OF THE EFFECTS OF DIFFERENT CHEMICAL STRUCTURES ON THE COLOR OF THE SOFTENERS USED IN THE FINISH

ASLIHAN KORUYUCU^{a*}

^aNAMIK KEMAL UNIVERSITY DEPARTMENT OF TEXTILE ENGINEERING

*adelituna@nku.edu.tr

Abstract:

In textile, finishing are performed after bleaching, painting or printing. During finishing operations; attention must be paid to the extent to which the chemical constituents of the materials used influence the color of the dyed product. Purpose of this study; it has been investigated to what extent the dyed fabric sample of finishing chemistry with different chemical structure and different ionic character influences the color. In this study; softeners with four different chemical structure and finishing chemicals with three different ionic characters were used. Softeners with different ionic character and different chemical structure are diluted with water at a certain ratio and adjusted to pH 5-5.5 with acetic acid. The softeners were applied at three different concentrations and at two different drying temperatures according to the method of impregnation with 30/1 suprem. After the applications; untreated fabric was accepted as the standard and color measurement on the spectrophotometer. While the cationic (aminofunctional silicone) and nonionic (polyethylene and macro-micro silicone emulsion) characteristic softener concentrations are constant. As the drying temperature increased after application, it was observed that the fabric samples color was opened. When the drying temperature is constant; as the finish chemical concentration increases, the fabric samples become darker. In softeners with weak cationic character; when the drying temperature is held constant (at 130 ° C), the color of the fabric samples is increased as the softener concentration increases.

Keywords: Finishing, Softener, Chemical Structure, Ionic Character

IMPROVING THE COLOR YIELD AND WET FASTNESSES BY SYNTHESIZING THE NEW DISPERSE AZO DYE

ASLIHAN KORUYUCU^{a*}

^aNAMIK KEMAL UNIVERSITY DEPARTMENT OF TEXTILE ENGINEERING

*adelituna@nku.edu.tr

Abstract:

The most important class of organic dyestuffs are azo dyestuffs. Azo dyes are characterized by the azo group, which is a chromophore group in their structure. The nitrogen atoms in this group are bonded to carbon atoms by sp² hybridization. One of the carbon atoms attached to the azo group is the aromatic cyclic heterocyclic ring. The other is; an enolizable aliphatic group. The color yield and fastness properties of azo disperse dyes containing aliphatic groups are low. The purpose of this study is to improve the color yield and wet fastness of the azo dye by synthesizing the new azo disperse dyestuff. For this purpose; a new dyestuff has been synthesized in acidic medium which can be used instead of disperse blue 321 which is one of the most used dyestuffs in textile. The synthesis was carried out in two steps, namely diazotization and chelation. The absorbance values of the dyes synthesized in standard and acidic media were measured by UV-visible spectrophotometer. Color yield values were obtained from these values by the calculation method. According to standard dyes, a 44% increase in the color yield of the disperse blue 321 dyes synthesized was obtained. It has been found that the new dye synthesized has less contamination of the multifiber fabric as a result of washing fastness according to ISO 105 C06, B2S standard.

As seen in the structure of newly synthesized Dispers Blue 321 dye; there are two interconnected benzene rings connected to the azo group at the clamping part. This leads to increased unsaturation and color yield in the structure. At the same time it causes less pollution in washing fastnesses.

Keywords: Organic Dyestuff, Azo, Color Yield, Wet Fastness

RESEARCH OF GROWTH MECHANISM OF MICRO ARC OXIDATION COATINGS ON MAGNESIUM ALLOYS

AYSUN AYDAY^{a*}, S.CAN KURNAZ^a

^aSAKARYA UNIVERSITY

*aayday@sakarya.edu.tr

Abstract:

Porous ceramics coatings were formed on magnesium substrates by micro arc oxidation (MAO) in glycerol phosphate calcium electrolyte for different times at the constant current and voltage. The MAO process and growth mechanism were investigated by scanning electron microscopy (SEM) and energy dispersive spectrometer (EDS), X-ray diffraction (XRD). The coating layer grows inward and outward at the same time in the initial stage, but outward growth of the coating is dominant later. Mg, Mg₂SiO₄ and MgO are the main phases of ceramic coating.

Keywords: Micro Arc Oxidation, Oxidation Time, Microstructure

OPTIMIZATION AND VALUATION OF EXPANSION FLEXIBILITY IN MANUFACTURING INDUSTRY

MEHMET AKTAN^{a*}, KEMAL ALAYKIRAN^a

^aNECMETTIN ERBAKAN UNIVERSITY

*endustri@gmail.com

Abstract:

Flexibility allows firms to compete more effectively in a world of substantial price and demand uncertainty, product variety, short product life cycles, and rapid product development. Throughout the life of a project, managers must react to events as they unfold. Real options approach seeks to quantify the value of flexibility and to determine the optimal managerial decisions. In this study, real options approach is presented to evaluate the flexibility to expand the capacity using a case study for a cell phone manufacturing firm that is unsure of the market demand of its new products. Valuation of the option is demonstrated using binomial trees. Optimal decisions for each state are shown on the tree.

Keywords: Flexibility, Real Options, Decision Making, Valuation, Optimization

DIAGNOSIS OF DIABET DISEASE BY USING DIFFERENT MACHINE LEARNING TECHNIQUES

EMINE YAMAN^{a*}, JUSUF KORIC^a

^aINTERNATIONAL UNIVERSITY OF SARAJEVO

*eyaman@ius.edu.ba

Abstract:

In today's world, diabetes is one of the most dangerous and most frequent diseases in the world that hits people's life. In the last few decades there have been developed many ways of predicting diabetes. This paper helps in predicting diabetes by applying data mining techniques and some machine learning algorithms. The aim of data mining is to extract knowledge from information stored in dataset and generate clear and understandable description of patterns. Since diabetes is mayor disease in people's life, in this paper it has been given effort to improve prediction of diabetes using a population of woman who were at least 21 year old of Pima Indian heritage living in Phoenix. In this research, Python with Anaconda3 was used to implement Naïve Bayes, Logistic Regression and Random Forest to classify our dataset and tried to do as more as it is possible to predict and improve prediction for this very important field in medicine and help people to do something in order to prevent or decrease the chance of getting diabetes.

Keywords: Pima Indian Dataset, Diabetes, Classification, Logistic Regression, Naïve Bayes, Random Forest

NEOANTIGEN BASED IMMUNOTHERAPY IN PERSONALIZED CANCER TREATMENT

Betul AKCESME^{a*}, Seid MALANOVIĆ^a

^aINTERNATIONAL UNIVERSITY OF SARAJEVO, SARAJEVO, BASNIA&HERZEGOVINA

Abstract:

Recent advances in sequencing technologies and personalized medicine enable new approaches in cancer treatment by utilizing immune system. One of these applications is the vaccination with tumor-specific antigens so called neoantigens, described by peptides containing amino acid substitutions caused by nonsynonymous mutations. The biggest advantage of neoantigens is that they are not subjected to immune tolerance. Groundbreaking studies demonstrate in vitro and in vivo success for T cell response and tumor eradication. Despite of the success of the human vaccination based on neoantigens, they need to pass clinical trials and regulatory issues in order to be fully available in medical care. Moreover, they largely depend on sequencing technologies and computational analysis so with the improvement of these two components, neoantigen vaccination will also be improved. This review brings insight into current mechanism of neoantigen recognition and methods used to identify them. Another aim of this review is to emphasize the importance of research on neoantigens which might bring new era of cancer treatment.

Key words: Neoantigens, personalized medicine, tumor infiltrating lymphocytes, T cells, MHC complex

COMPRESSION PROPERTIES OF WOVEN CARPET PERFORMANCE UNDER DYNAMIC LOADING

DENIZ VURUSKAN^{a*}, ESIN SARIOGLU^a, HALIL IBRAHIM CELIK^a, HATICE KUBRA KAYNAK^a

^aGAZIANTEP UNIVERSITY, DEPT. OF TEXTILE ENG. GAZIANTEP, TURKEY

*vuruskan@gantep.edu.tr

Abstract:

Carpet is predominantly used in home floor covering as an indispensable decorative product and also preferred by its heat and sound insulation feature. Compression performance in general terms of mechanical properties influences carpet performance based on usage are dynamic or static loads. Thickness loss of carpet is affected negatively under dynamic and static load which are created by walking and furniture, respectively. During use of carpet thickness loss is directly affected by raw material, pile thickness, carpet construction, pile density. There are a lot of studies focused on effects of these parameters on carpet performance. In this study, the influences of pile thickness and pile density on woven carpet compression performance under dynamic loading are investigated. Woven carpet samples were produced as Wilton face-to-face with two different pile density as 2400 piles/dm² and 2880 piles/dm² and three different pile thickness as 7 mm, 11 mm and 16 mm. Raw material of pile was selected as acrylic fiber with 5.6 denier linear density. All carpet production parameters were kept constant such as machine speed, weft and warp yarns used, construction. Dynamic loading tests were achieved by WIRA dynamic loading machine. Thickness of carpet samples were measured after 50,100,200 and 1000 impacts. Test results were analyzed to determine the significance effect of pile density and pile thickness on thickness loss of carpet performance by SPSS package program. Statistical analysis showed that the pile density and pile thickness have a significant effect on thickness loss of carpet samples.

Keywords: dynamic loading, woven carpet, face-to-face, acrylic

ICETI

INTERNATIONAL CONFERENCE ON ENGINEERING
TECHNOLOGY AND INNOVATION

www.iceti.org

